

INSTALLATION INSTRUCTIONS FOR

LYRA

- This product is ETL listed.
- This product is suitable for indoor dry locations only.
- This product can mount to either a 4" square electrical box with round plaster ring or an octagon electrical box. The rectangle canopy can be used with a rectangular junction box.
- This product can be dimmed with a standard incandescent dimmer

CAUTION-RISK OF FIRE

This product requires installation by a qualified electrician.
Before installing, be sure to read all instructions and
TURN THE POWER TO THE ELECTRICAL BOX OFF.

INSTALLATION

STEP 1

Attach universal crossbar to electrical box using two 8-32nd X 3/4" screws provided. Use toggle bolt anchors to mount the four suspension wire bases and attach suspension clips to fixture.

Note: The electrical box should be in the middle of one of the two end support wires.



STEP 2


Adjust fixture height to a minimum of 7ft. from floor and 1ft. from ceiling and CUT OFF EXCESS STEEL SUSPENSION CABLE.

Note: This applies to ceilings of minimum 8 ft.



STEP 3

Connect brown and blue marked wire to the hot (black) power line using wire nut provided. **Note:** Fluorescent bulbs can not be dimmed. If no dimmer is used, the fluorescent and halogen lamps may be controlled by the same switch.



STEP 4

Connect white marked wire from fixture to the neutral (white) power line wire using wire nut provided. Connect green marked wire from fixture to the ground (green) wire from power line or junction box, depending on applicable electrical codes in your area.



STEP 5

Using the cable ties provided, secure power supply cord to one of the suspension wires. Use strain relief to secure end of cord.



STEP 6

Secure fixture canopy over electrical box with 8-32nd screws provided.

