

PUREEDGE LIGHTING LLC

TEST REPORT

SCOPE OF WORK

LED Performance Testing

MODEL NUMBER

CFDW-7W-***-48-**K-**

PROJECT NUMBER

G104797632

REPORT NUMBER

104797632CHI-032

ISSUE DATE

6/20/2022

REVISED DATE

None

TEST DATES

2022-06-03 through 2022-06-08.

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



REPORT NUMBER

104797632CHI-032

MODEL NUMBER(s)

CFDW-7W-***-48-**K-**

REPORT RENDERED TO:

PUREEDGE LIGHTING LLC
1718 W. FULLERTON AVE
CHICAGO, IL 60614
USA

STATEMENT OF LIMITATION

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION

The testing performed was authorized by signed quote number Qu-01199885-2.

TEST STANDARDS

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

ANSI/IES LM-79-19 Optical and Electrical Measurements of Solid-State Lighting Products

ANSI NEMA ANSLG C78.377: 2017: Specifications for the Chromaticity of Solid State Lighting (SSL) Products

IES TM-30-18: IES Method for Evaluating Light Source Color Rendition

In Charge of Testing:



Maximilian Carvajal
Engineer
Lighting Division

Reviewer:



Jeff Davis
N.A. Technical Lead
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SAMPLE INFORMATION

REPORT NO. 104797632CHI-032


ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Type	Received
1	AH05192022111730	CFDW-7W-***-48-**K-**	LINEAR LOW VOLTAGE	Production	5/19/2022

TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	CFDW-7W-***-48-**K-**	1

SAMPLE PHOTOS - TESTED CONFIGURATIONS



SUMMARY

REPORT NO. 104797632CHI-032

PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	CFDW-7W-***-48-**K-**
Product Description:	LINEAR LOW VOLTAGE
LED Model No.:	Lumileds 2835
Driver Model No.:	LTF Uni Driver / PSB-96W-UNI-24VDC
Light Source:	LED

Criteria	Results	
	Goniophotometer	Integrating Sphere
Light Output (lumens)	2963.3	2984.1
Input Power (W) @ 24VCD THROUGH 0-10 POWER SUPPLY	38.90	39.49
Lumen Efficacy (lm/W)	76.2	75.6
Input Power Factor (I) @ 24VCD THROUGH 0-10 POWER SUPPLY	0.945	0.948

Criteria	Results
Input ATHD (%) @ 24VCD THROUGH 0-10 POWER SUPPLY (Vac)	21.56
Correlated Color Temperature (K)	3435
Color Rendering Index - Ra (I)	93.8
Color Rendering Index - R9 (I)	84.6
Duv (I)	-0.0009
Chromaticity Coordinate (x)	0.408
Chromaticity Coordinate (y)	0.390
Chromaticity Coordinate (u')	0.238
Chromaticity Coordinate (v')	0.511
Input Power (W) @ 277 (Vac)	43.98
Input Power Factor (I) @ 277 (Vac)	0.744
Input ATHD (%) @ 277 (Vac)	35.99

TEST METHODS

SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

INTEGRATING SPHERE TESTING

A spectroradiometer and integrating sphere were used to measure the spectral distribution for each EUT resulting in photometric and colorimetric data. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position inside the sphere and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

REPORT NO. 104797632CHI-032

Test Configuration	Tested Model No.	Pass/Fail/NA
1	CFDW-7W-***-48-**K-**	NA

PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation	Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor ()
Up	120.03	342.8	38.90	0.945

Light Output (lm)	Lumen Efficacy (lm/W)
2963.3	76.2

INTENSITY SUMMARY - CANDELA


Angle	0	22.5	45	67.5	90
0	2102.2	2102.2	2102.2	2102.2	2102.2
5	2078.0	2064.2	2079.6	2100.1	2149.8
10	2029.6	2031.4	2047.3	2081.6	2133.8
15	1967.1	1967.4	1987.3	2035.3	2096.0
20	1887.0	1869.2	1900.8	1952.0	2014.6
25	1755.6	1728.2	1758.3	1808.2	1875.0
30	1568.1	1536.5	1562.1	1600.4	1661.5
35	1296.6	1291.3	1307.6	1330.1	1288.7
40	673.4	812.9	1025.5	749.3	533.1
45	224.6	309.7	633.0	259.1	187.3
50	144.3	148.0	223.5	147.5	144.5
55	126.1	125.2	131.5	126.9	127.3
60	111.1	110.6	111.7	110.7	109.6
65	94.4	93.8	92.4	91.8	90.4
70	75.3	75.0	72.0	71.2	69.7
75	56.0	54.7	50.7	49.8	48.2
80	36.2	33.0	29.2	27.5	26.6
85	15.9	11.8	8.6	6.5	5.5
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file



REPORT NO. 104797632CHI-032

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	1,586.1	53.5%	0-10	198.9	6.7%
0-40	2,376.5	80.2%	10-20	567.1	19.1%
0-60	2,804.9	94.7%	20-30	820.1	27.7%
60-90	158.5	5.3%	30-40	790.4	26.7%
70-100	67.0	2.3%	40-50	310.6	10.5%
90-120	0.0	0.0%	50-60	117.7	4.0%
0-90	2,963.3	100.0%	60-70	91.5	3.1%
90-180	0.0	0.0%	70-80	54.5	1.8%
0-180	2,963.3	100.0%	80-90	12.5	0.4%
			90-100	0.0	0.0%
			100-110	0.0	0.0%
			110-120	0.0	0.0%
			120-130	0.0	0.0%
			130-140	0.0	0.0%
			140-150	0.0	0.0%
			150-160	0.0	0.0%
			160-170	0.0	0.0%
			170-180	0.0	0.0%

INTEGRATING SPHERE TESTING

REPORT NO. 104797632CHI-032

Test Configuration	Tested Model No.	Pass/Fail/NA
1	CFDW-7W-***-48-**K-**	NA

PHOTOMETRIC, COLORIMETRIC, AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation
Up

Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor ()	Input ATHD (%)
199.98	347.3	39.49	0.948	21.56
277.04	213.5	43.98	0.744	35.99

Measured at 199.98(Vac)

Light Output (lm)	Lumen Efficacy (lm/W)	CCT (K)	CRI - Ra ()	CRI - R9 ()
2984.1	75.6	3435	93.8	84.6

Duv ()	1931 Chrom (x)	1931 Chrom (y)	1976 Chrom (u')	1976 Chrom (v')
-0.0009	0.408	0.390	0.238	0.511




REPORT NO. 104797632CHI-032

SPECTRAL DISTRIBUTION OVER WAVELENGTHS

nm	mW/nm		nm	mW/nm		nm	mW/nm		nm	mW/nm
350	0.3		460	20.9		570	40.6		680	33.1
355	0.3		465	17.0		575	40.9		685	30.2
360	0.3		470	13.3		580	41.4		690	27.4
365	0.3		475	11.9		585	42.0		695	24.7
370	0.3		480	12.5		590	42.7		700	22.1
375	0.3		485	14.0		595	43.6		705	19.6
380	0.4		490	16.6		600	44.8		710	17.4
385	0.5		495	19.6		605	46.0		715	15.3
390	0.6		500	22.9		610	47.4		720	13.4
395	0.6		505	25.7		615	48.6		725	11.8
400	0.7		510	28.3		620	49.7		730	10.3
405	0.9		515	30.3		625	50.6		735	8.9
410	1.2		520	32.0		630	50.9		740	7.7
415	2.0		525	33.7		635	51.0		745	6.7
420	3.3		530	34.8		640	50.6		750	5.8
425	5.7		535	36.0		645	49.6		755	5.0
430	9.3		540	37.1		650	48.3		760	4.3
435	15.1		545	38.0		655	46.4		765	3.7
440	25.3		550	38.6		660	44.2		770	3.2
445	37.1		555	39.3		665	41.7		775	2.7
450	37.6		560	39.8		670	38.9		780	2.3
455	26.6		565	40.2		675	36.2		---	---

Without correction of sample absorption.



Portrayed color in graphic is estimated by wavelength (nm) and may not be exact - it is a visual representation only

EQUIPMENT LIST

REPORT NO. 104797632CHI-032

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	Yokogawa Power Meter	WT310E	CHI0664	3/30/2022	3/30/2023
2	Omega Thermometer	DPI8-C24	146920	10/4/2021	10/4/2022
3	LSI High Speed Mirror Goniometer	6440T	146928	VBU	VBU
4	Newport Thermohygrometer	iServer	CHI0452	2/3/2022	2/3/2023
5	Chroma Power Supply	61604	CHI0371	VBU	VBU
8	Newport Humidity Recorder	iServer	146961	9/21/2021	9/21/2022
9	Labsphere Spectroradiometer	CDS2600	CHI0539	VBU	VBU
10	3 Meter Sphere	SPR600	CHI0088	VBU	VBU
11	Elgar AC Power Supply	CW1251	146112	VBU	VBU
12	Sorenson DC Power Supply	XFR150-8	146846	VBU	VBU
13	Yokogawa Power Meter	WT1600	146767	4/4/2022	4/4/2023
17	Omega thermometer	USB TC08	EQAH002615	4/5/2022	4/5/2023

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

REVISION HISTORY







#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---

Test Configuration	Tested Model No.	Pass/Fail/NA
1	CFDW-7W-***-48-**K-**	NA

ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD
Date: 6/8/2022

Manufacturer: PureEdge Lighting LLC
Model: CFDW-7W-***-48-**K-**



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4080
y 0.3900
u' 0.2378
v' 0.5114