

PURE EDGE LIGHTING

TEST REPORT

SCOPE OF WORK

LED Performance Testing

MODEL NUMBER

SUN3-HDL2-RD-WW-SA

PROJECT NUMBER

G104373788

REPORT NUMBER

104373788CHI-026

ISSUE DATE

9/14/2020

REVISED DATE

None

TEST DATES

09/04/2020 through 09/10/2020.

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



REPORT NUMBER

104373788CHI-026

MODEL NUMBER(s)

SUN3-HDL2-RD-WW-SA

REPORT RENDERED TO:

PURE EDGE LIGHTING
1718 W. FULLERTON AVE.
CHICAGO, IL 60614
USA

STATEMENT OF LIMITATION

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION

The testing performed was authorized by signed quote number Qu-01087644-1.

TEST STANDARDS

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

ANSI NEMA ANSLG C78.377: 2017: Specifications for the Chromaticity of Solid State Lighting (SSL) Products

In Charge of Testing:



Ian Smith
Engineer
Lighting Division

Reviewer:



Jeff Davis
NA Technical Lead
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SAMPLE INFORMATION

REPORT NO. 104373788CHI-026



ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Type	Received
1	AH09022020034516	SUN3-HDL2-RD-WW-SA	Led fixture	Production	9/2/2020

TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	SUN3-HDL2-RD-WW-SA	1

SAMPLE PHOTOS - TESTED CONFIGURATIONS



SUMMARY

REPORT NO. 104373788CHI-026

PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	SUN3-HDL2-RD-WW-SA
Product Description:	Led fixture
LED Model No.:	LUXEON-M
Driver Model No.:	L.T.F/TA60WA12LEDS65B15-000
Light Source:	LED

Criteria	Results	
	Goniophotometer	Integrating Sphere
Light Output (lumens)	467.4	466.6
Input Power (W) @ 120VAC (Vac)	8.83	8.84
Lumen Efficacy (lm/W)	52.9	52.8
Input Power Factor (I) @ 120VAC (Vac)	0.661	0.687

Criteria	Results
Input ATHD (%) @ 120VAC (Vac)	90.50
Correlated Color Temperature (K)	3006
Color Rendering Index - Ra (I)	95.0
Color Rendering Index - R9 (I)	75.8
Duv (I)	0.0003
Chromaticity Coordinate (x)	0.437
Chromaticity Coordinate (y)	0.405
Chromaticity Coordinate (u')	0.250
Chromaticity Coordinate (v')	0.522

TEST METHODS

SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

INTEGRATING SPHERE TESTING

A spectroradiometer and integrating sphere were used to measure the spectral distribution for each EUT resulting in photometric and colorimetric data. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position inside the sphere and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

REPORT NO. 104373788CHI-026

Test Configuration	Tested Model No.	Pass/Fail/NA
1	SUN3-HDL2-RD-WW-SA	NA

PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation	Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor ()
Up	120.0	111.3	8.83	0.661

Light Output (lm)	Lumen Efficacy (lm/W)
467.4	52.9

INTENSITY SUMMARY - CANDELA


Angle	0	22.5	45	67.5	90
0	1695	1695	1695	1695	1695
5	1527	1527	1527	1527	1527
10	1108	1108	1108	1108	1108
15	680	680	680	680	680
20	376	376	376	376	376
25	197	197	197	197	197
30	110	110	110	110	110
35	63	63	63	63	63
40	31	31	31	31	31
45	9	9	9	9	9
50	3	3	3	3	3
55	2	2	2	2	2
60	1	1	1	1	1
65	1	1	1	1	1
70	1	1	1	1	1
75	1	1	1	1	1
80	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file



REPORT NO. 104373788CHI-026

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	394.8	92.2%	90-100	0.0	0.0%
0-40	419.0	97.8%	100-110	0.0	0.0%
0-60	424.6	99.1%	110-120	0.0	0.0%
60-90	2.3	0.5%	120-130	0.0	0.0%
70-100	1.3	0.3%	130-140	0.0	0.0%
90-120	0.5	0.1%	140-150	0.0	0.0%
0-90	426.9	99.6%	150-160	0.0	0.0%
90-180	1.5	0.4%	160-170	0.0	0.0%
0-180	428.4	100.0%	170-180	0.0	0.0%

INTEGRATING SPHERE TESTING

REPORT NO. 104373788CHI-026

Test Configuration	Tested Model No.	Pass/Fail/NA
1	SUN3-HDL2-RD-WW-SA	NA

PHOTOMETRIC, COLORIMETRIC, AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation
Up

Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor ()	Input ATHD (%)
120.01	107.4	8.84	0.687	90.50

Measured at 120.01(Vac)

Light Output (lm)	Lumen Efficacy (lm/W)	CCT (K)	CRI - Ra ()	CRI - R9 ()
466.6	52.8	3006	95.0	75.8

Duv ()	1931 Chrom (x)	1931 Chrom (y)	1976 Chrom (u')	1976 Chrom (v')
0.0003	0.437	0.405	0.250	0.522




REPORT NO. 104373788CHI-026

SPECTRAL DISTRIBUTION OVER WAVELENGTHS

nm	mW/nm		nm	mW/nm		nm	mW/nm		nm	mW/nm
350	0.5		460	3.7		570	6.7		680	5.6
355	0.5		465	2.9		575	6.9		685	5.0
360	0.4		470	2.5		580	7.1		690	4.5
365	0.4		475	2.3		585	7.3		695	4.0
370	0.3		480	2.1		590	7.6		700	3.6
375	0.4		485	2.2		595	7.9		705	3.2
380	0.3		490	2.5		600	8.2		710	2.9
385	0.3		495	2.9		605	8.6		715	2.5
390	0.2		500	3.3		610	8.9		720	2.2
395	0.2		505	3.7		615	9.1		725	1.9
400	0.2		510	4.1		620	9.3		730	1.7
405	0.2		515	4.5		625	9.5		735	1.5
410	0.2		520	4.8		630	9.5		740	1.3
415	0.3		525	5.1		635	9.4		745	1.2
420	0.4		530	5.4		640	9.2		750	1.0
425	0.7		535	5.7		645	9.0		755	0.9
430	1.1		540	5.9		650	8.6		760	0.8
435	1.5		545	6.0		655	8.2		765	0.8
440	2.1		550	6.2		660	7.7		770	0.6
445	2.7		555	6.3		665	7.2		775	0.7
450	3.8		560	6.5		670	6.6		780	0.6
455	4.4		565	6.6		675	6.1		---	---

Without correction of sample absorption.



Portrayed color in graphic is estimated by wavelength (nm) and may not be exact - it is a visual representation only

EQUIPMENT LIST

REPORT NO. 104373788CHI-026

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	Yokogawa Power Meter	WT210	146919	7/1/2020	7/1/2021
2	Omega Thermometer	DPI8-C24	146920	10/3/2019	10/3/2020
3	LSI High Speed Mirror Goniometer	6440T	146928	VBU	VBU
4	Newport Thermohygrometer	iServer	146957	12/2/2019	12/2/2020
5	Pacific AC Power Supply	118-ACX	CHI0153	VBU	VBU
6	Newport Humidity Recorder	iServer	CHI0456	10/11/2019	10/11/2020
7	Labsphere Spectroradiometer	CDS-600	146923	VBU	VBU
8	2M Rotating Sphere	7660-ROT	146923	VBU	VBU
9	Omega thermometer	USB TC08	EQAH002615	4/7/2020	4/7/2021
10	Ametek DC Power Supply	XFR150-8	1468464	VBU	VBU
11	Yokogawa Power Meter	WT210	146880	10/2/2019	10/2/2020
12	Chroma Power Supply	61604	CHI0371	VBU	VBU
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

REVISION HISTORY

#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---