

# PURE EDGE LIGHTING

## TEST REPORT

### SCOPE OF WORK

LED Performance Testing

### MODEL NUMBER

TUBL-NF-30K-WH

### PROJECT NUMBER

G104430061

### REPORT NUMBER

104430061CHI-004

### ISSUE DATE

3/10/2021

### REVISED DATE

None

### TEST DATES

02/25/2021 through 03/03/2021.

### DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



**REPORT NUMBER**

104430061CHI-004

**MODEL NUMBER(s)**

TUBL-NF-30K-WH

**REPORT RENDERED TO:**

PURE EDGE LIGHTING  
1718 WEST FULLERTON AVE  
CHICAGO  
USA

**STATEMENT OF LIMITATION**

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

**AUTHORIZATION**

The testing performed was authorized by signed quote number Qu-01100816-1.

**TEST STANDARDS**

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

ANSI NEMA ANSLG C78.377: 2017: Specifications for the Chromaticity of Solid State Lighting (SSL) Products

IES TM-30-18: IES Method for Evaluating Light Source Color Rendition

In Charge of Testing:



Ian Smith  
Engineer  
Lighting Division

Reviewer:



Jeff Davis  
NA Technical Lead  
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## SAMPLE INFORMATION

REPORT NO. 104430061CHI-004


## ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Type	Received
1	AH02182021102128	TUBL-NF-30K-WH	LED ACCENT LIGHT	Prototype	2/18/2021

## TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	TUBL-NF-30K-WH	1

## SAMPLE PHOTOS - TESTED CONFIGURATIONS



## SUMMARY

REPORT NO. 104430061CHI-004

### PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	TUBL-NF-30K-WH
Product Description:	LED ACCENT LIGHT
LED Model No.:	LUMINUS/CXM-9-30-90-36-AC40-F5-3
Driver Model No.:	HUARI/DR-24V-1100-33D
Light Source:	LED

Criteria	Results	
	Goniophotometer	Integrating Sphere
Light Output (lumens)	1111.0	1127.0
Input Power (W) @ 120 (Vac)	16.96	16.95
Lumen Efficacy (lm/W)	65.5	66.5
Input Power Factor ( ) @ 120 (Vac)	0.983	0.983

Criteria	Results
Input ATHD (%) @ 120 (Vac)	13.76
Correlated Color Temperature (K)	2963
Color Rendering Index - Ra ( )	89.9
Color Rendering Index - R9 ( )	62.8
Duv ( )	0.0005
Chromaticity Coordinate (x)	0.441
Chromaticity Coordinate (y)	0.407
Chromaticity Coordinate (u')	0.252
Chromaticity Coordinate (v')	0.523

### TEST METHODS

#### SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

#### INTEGRATING SPHERE TESTING

A spectroradiometer and integrating sphere were used to measure the spectral distribution for each EUT resulting in photometric and colorimetric data. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position inside the sphere and stabilization procedures to LM-79 were followed.

#### TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

**TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING**

**REPORT NO. 104430061CHI-004**

Test Configuration	Tested Model No.	Pass/Fail/NA
1	TUBL-NF-30K-WH	NA

**PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)**


Base Orientation	Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor (I)
Up	120.04	143.7	16.96	0.983

Light Output (lm)	Lumen Efficacy (lm/W)
1111.0	65.5

**INTENSITY SUMMARY - CANDELA**


Angle	0	22.5	45	67.5	90
0	2780	2780	2780	2780	2780
5	2668	2662	2656	2655	2652
10	2286	2275	2272	2270	2271
15	1696	1693	1688	1691	1689
20	1083	1086	1083	1082	1081
25	593	597	599	597	592
30	292	293	292	293	292
35	133	136	137	137	136
40	62	64	64	64	64
45	28	29	29	29	29
50	15	16	16	16	16
55	10	11	11	11	11
60	6	6	6	6	7
65	3	3	3	3	3
70	1	1	1	1	1
75	0	0	0	0	0
80	0	0	0	0	0
85	0	0	0	0	0
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file



REPORT NO. 104430061CHI-004

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	980.3	88.2%	0-10	240.7	21.7%
0-40	1,072.6	96.6%	10-20	459.2	41.3%
0-60	1,107.1	99.7%	20-30	280.5	25.2%
60-90	3.9	0.3%	30-40	92.3	8.3%
70-100	0.6	0.1%	40-50	24.9	2.2%
90-120	0.0	0.0%	50-60	9.6	0.9%
0-90	1,111.0	100.0%	60-70	3.3	0.3%
90-180	0.0	0.0%	70-80	0.4	0.0%
0-180	1,111.0	100.0%	80-90	0.2	0.0%
			90-100	0.0	0.0%
			100-110	0.0	0.0%
			110-120	0.0	0.0%
			120-130	0.0	0.0%
			130-140	0.0	0.0%
			140-150	0.0	0.0%
			150-160	0.0	0.0%
			160-170	0.0	0.0%
			170-180	0.0	0.0%

**INTEGRATING SPHERE TESTING**

**REPORT NO. 104430061CHI-004**

Test Configuration	Tested Model No.	Pass/Fail/NA
1	TUBL-NF-30K-WH	NA

**PHOTOMETRIC, COLORIMETRIC, AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)**


Base Orientation
Up

Input Voltage (Vac)	Input Current (mA)	Input Power (W)	Input Power Factor (I)	Input ATHD (%)
120.02	143.7	16.95	0.983	13.76

**Measured at 120.02(Vac)**

Light Output (lm)	Lumen Efficacy (lm/W)	CCT (K)	CRI - Ra (I)	CRI - R9 (I)
1127.0	66.5	2963	89.9	62.8

Duv (I)	1931 Chrom (x)	1931 Chrom (y)	1976 Chrom (u')	1976 Chrom (v')
0.0005	0.441	0.407	0.252	0.523




REPORT NO. 104430061CHI-004

SPECTRAL DISTRIBUTION OVER WAVELENGTHS

nm	mW/nm		nm	mW/nm		nm	mW/nm		nm	mW/nm
350	0.1		460	6.2		570	14.6		680	11.1
355	0.1		465	4.9		575	15.0		685	10.0
360	0.1		470	4.1		580	15.3		690	9.0
365	0.1		475	3.3		585	15.7		695	8.0
370	0.1		480	3.2		590	16.2		700	7.1
375	0.1		485	3.4		595	16.8		705	6.3
380	0.1		490	3.9		600	17.4		710	5.5
385	0.1		495	4.6		605	18.0		715	4.8
390	0.1		500	5.5		610	18.6		720	4.2
395	0.1		505	6.4		615	19.0		725	3.6
400	0.1		510	7.5		620	19.4		730	3.1
405	0.2		515	8.6		625	19.5		735	2.7
410	0.3		520	9.6		630	19.5		740	2.3
415	0.5		525	10.5		635	19.3		745	2.0
420	0.8		530	11.3		640	18.9		750	1.7
425	1.3		535	12.1		645	18.2		755	1.5
430	2.1		540	12.7		650	17.5		760	1.3
435	3.2		545	13.1		655	16.6		765	1.1
440	4.8		550	13.5		660	15.6		770	1.0
445	7.4		555	13.9		665	14.5		775	0.8
450	9.9		560	14.2		670	13.4		780	0.7
455	9.0		565	14.4		675	12.2		---	---

Without correction of sample absorption.



Portrayed color in graphic is estimated by wavelength (nm) and may not be exact - it is a visual representation only

## EQUIPMENT LIST

REPORT NO. 104430061CHI-004

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	Yokogawa Power Meter	WT210	146919	7/1/2020	7/1/2021
2	Omega Thermometer	DPI8-C24	146920	10/1/2020	10/1/2021
3	LSI High Speed Mirror Goniometer	6440T	146928	VBV	VBV
4	Newport Thermohygrometer	iServer	146957	1/29/2021	1/29/2022
5	Pacific AC Power Supply	118-ACX	CHI0153	VBV	VBV
6	Newport Humidity Recorder	iServer	146961	9/3/2020	9/3/2021
7	Labsphere 2M Sphere & Spectroradiometer	CDS1100	146137	VBV	VBV
8	Elgar AC Power Supply	CW1251	146113	VBV	VBV
9	Sorenson DC Power Supply	XFR150-8	146847	VBV	VBV
10	Yokogawa Power Meter	WT1600	146767	4/6/2020	4/6/2021
11	Omega Thermometer	MDSi8	146873	7/1/2020	7/1/2021

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

## REVISION HISTORY

#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---

Test Configuration	Tested Model No.	Pass/Fail/NA
1	TUBL-NF-30K-WH	NA







## ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: Pure Edge Lighting

Date: 3/3/2021

Model: TUBL-NF-30K-WH



**Notes:** This is a recommended method for displaying ANSI/IES TM-30-18 information.

 $x$  0.4405 $y$  0.4070 $u'$  0.2516 $v'$  0.5231