



BSF-MR16-12V-FL-TC-BK
SHOWN WITH BSF-MR16-ECL



BSF-MR16-12V-FL-TC-BK
SHOWN WITH BSF-MR16-SNT



BSF-MR16-12V-WZ-TC-SN



BSF-MR16-12V-WZ-TC-SN
SHOWN WITH MR16-ECL



BSF-MR16-12V-WZ-TC-WH
SHOWN WITH BSF-MR16-SNT



BSF-MR16-12V-WZ-TC-WH

DESCRIPTION

The BIG-Shorty yields BIG illumination in a shorty profile. The BIG-Shorty offers an adjustable floor lamp that incorporates a Pure Smart TruColor™ RGBTW MR16. The lamp is 12V, and with the proprietary color mixing from Pure Smart produces a wide spectrum of tunable white tones from 1500-6500K as well as 16 million saturated and secondary colors. TruColor™ RGBTW4K delivers a tunable range from 2000K to 4000K, allowing for greater fine-tuning of warm white tones using the Pure Smart room controller or remote. In addition to the color tuning technology the lamp allows for wireless control with the WiZ Pro Software Suite and Pure Smart Wi-Fi Room Controller (sold separately). For custom quotes and layout assistance, send your drawings and ideas to our design team: design@PureEdgeLighting.com.

COLOR TEMPERATURE:

- **RGBTW:** Red, Blue, Green, Tunable White from 1500K-6500K
- **RGBTW4K:** Red, Blue, Green, Tunable White from 2000K-4000K

SIZE: 4.5" High x 2.36 Diameter

FINISH: White, Black, or Satin Nickel

WEIGHT: 2 lb (0.9 kg)

LAMP SPECIFICATION

MR16 - Pure Smart TruColor™ RGBTW MR16-GU5.3-4W-XWF-RGBTW Red, Green, Blue + Tunable White (1500-6500K)

TRANSFORMER

Built in plug-in LED driver. Soft start short circuit and overload protected. For use with 12 volt LED MR16*. Output Type Class 2.

*Pure Smart MR16 Included with Fixture

INPUT: 120V AC, 0.6A 50/60Hz

OUTPUT: 12V AC, 0.08A MAX

APPLICATIONS/COMPLIANCE: Suitable for Dry Locations. UL Listed E364143.

DIMMING

- [Home Integration Solutions](#)
- [Pure Smart™ 5 Channel Wi-Fi Controller](#)
- [Pure Smart™ Battery Remote Wi-Fi Controller](#)


NETWORK: Wi-Fi access point should be within 30ft of fixture



STB16-BK




MR16-ECL




PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

DIMENSIONS




ACCESSORIES



MR16-SNT

Product	Finish
STB16	BK


STB16 Conical Snoot **BK** Black



MR16-ECL

Product	Accessory
MR16	ECL


MR16 MR16 Lamp Size **ECL** Egg Crate Louver



LF2.0-WF

Lamp	Accessory
LF2.0	WF

LF2.0 2.0" Lens Film **WF** 40° Wide Flood Beam Spread Film
VWF 60° Very Wide Flood Beam Spread Film



LF2.0-VWF

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

PURE SMART TRUCOLOR™ MR16-GU5.3-4W-XWF-RGBTW

12V, 4 WATT WI-FI ENABLED SMART LAMP



DESCRIPTION

The Pure Smart Wi-Fi enabled MR16, GU5.3 base lamp uses TruColor™ RGBTW Technology – With 5 channels (Red, Green, and Blue + Tunable White) of proprietary color mixing we create over 16 million vivid saturated colors and pastels along with 85,000 tunable white tones. Promote a healthy Circadian rhythm and experience the beauty of natural light in its purest form. Tunable White ranges from 1500K to 6500K. TruColor™ RGBTW4K delivers a tunable range from 2000K to 4000K, allowing for greater fine-tuning of warm white tones using the Pure Smart room controller or remote. Bring out the best of your world by saturating it in 97+ CRI light with TruColor™ Technology. Dial in just the right ambiance for any occasion just by changing the preset color mode. Harness the beauty of the sunset and paint your living room with the amber glow of the golden hour. Experience life in TruColor™.

- Controls - Easily control from anywhere with the WiZ app or with the WiZ Pro Dashboard on your computer. At home, experience the convenience of voice control with Alexa or Google Home. Take control to the next level by utilizing the available wall controls.
- Wall Controller - On/Off, Dimming, CCT selection, and scene control. Must use Pure Smart **CWW-TW-SCENE-WH** wall controller or Wall/Table Battery Remote Controller **CWR-TW-SCENE-WH** (Sold Separately).
- WiZ SpaceSense™ - Wi-Fi sensing technology that detects motion from disruptions in the Wi-Fi signal and triggers the lights to turn on or off when you enter or exit the room. *Not compatible with mesh networks.
- Schedule & Automation - Customizable schedules, circadian rhythm, vacation mode, energy monitoring, and predictive maintenance.
- Wi-Fi/Bluetooth - Easily setup over Wi-Fi or Bluetooth. No hub required.
- 3rd party log-in and cloud security provide a safe and protected connection. WiZ does not store nor share any personal information.

For custom quotes and layout assistance, send your drawings and ideas to our design team: design@PureEdgeLighting.com.

DIMMING & CONTROLS (SOLD SEPARATELY)

- [Home Integration Solutions](#)
- [Pure Smart™ 5 Channel Wi-Fi Controller](#)
- [Pure Smart™ Battery Operated Remote Wi-Fi Controller](#)

SPECIFICATIONS

APP	WiZ Mobile App
WI-FI/BLUETOOTH	Easily setup over Wi-Fi or Bluetooth. No hub required. 2.4GHz 802.11b/g/n WPA3 Personal
BULB SHAPE	MR16
BASE TYPE	GU5.3
WATTAGE	4 Watts
WATTAGE EQUIVALENCY	40 watt Incandescent, 28 watt Halogen
INPUT VOLTAGE	12 Volts AC
FREQUENCY	60 Hz
COLOR TEMPERATURE	<ul style="list-style-type: none"> • RGBTW: Red, Blue, Green, Tunable White from 1500K-6500K • RGBTW4K: Red, Blue, Green, Tunable White from 2000K-4000K
LUMENS	386 Lumens at 3000K
CRI	97 CRI at 3000K
EFFICACY	94 lumens per watt
DUV	.0003 average across 2000K-5500K
RF	92 average across 2000K-5500K
RG	102 average across 2000K-5500K
R9	84 average across 2000K-5500K
SCHEDULES & AUTOMATION	Customizable schedules, circadian rhythm, vacation mode, energy monitoring, and predictive maintenance
LOCATION	Indoor, damp location. Suitable for use in enclosed and open fixtures
MATERIAL	Polycarbonate
OPTICAL	Frosted Lens
L70 LIFESPAN	30,000 Hours
TITLE 20 COMPLIANCE	Meets Title 20 regulations and standards for efficiency. Suitable for use in California
WARRANTY	3 years/30,000 hours

APPLICATIONS

Ideal applications in residential, commercial, retail, and hospitality environments.


Product	Base	Wattage	Beam Spread	Color Temperature
MR16	GU5.3	4W	XWF	RGBTW
MR16 MR16 Smart Lamp	GU5.3 GU5.3 12VAC	4W 4 Watts	XWF Extra Wide Flood	RGBTW Red, Blue, Green, Tunable White from 1500K-6500K RGBTW4K Red, Blue, Green, Tunable White from 2000K-4000K

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


TM30 DATA
WI-FI ENABLED LED FLOOR UPLIGHT

TM-30-15 DATA: The data below is for Pure Smart TruColor™ RGBTW Lamps.


2000K (TruColor™ RGBTW)
View Angle: 2 Deg




2200K (TruColor™ RGBTW)
View Angle: 2 Deg




2400K (TruColor™ RGBTW)
View Angle: 2 Deg




2700K (TruColor™ RGBTW)
View Angle: 2 Deg




3000K (TruColor™ RGBTW)
View Angle: 2 Deg




3500K (TruColor™ RGBTW)
View Angle: 2 Deg



4000K (TruColor™ RGBTW)
View Angle: 2 Deg



5700K (TruColor™ RGBTW)
View Angle: 2 Deg



6500K (TruColor™ RGBTW)
View Angle: 2 Deg




Table with 3 columns: PROJECT, FIXTURE TYPE, DATE