





REV 02.11.21







DESCRIPTION:

Accepts input voltage of 120VAC and outputs 24VDC power up to 3x96 watts. Can be used as a dimmable or non-dim Power Supply*. Power Supply features short circuit and overload protection. Indoor applications only.

electrical Panels using Seimens/Murray AFCI breakers are not compatible with this ELV transformer. Use 0-10 Volt power supplies with this breaker.

**ELV power supplies are not compatible with nLight, use only 0-10 volt or Uni driver power supplies

APPLICATIONS: Indoor

*To avoid overheating the power supply, install it in a ventilated remote location where air flows. Maintain proper spacing among power supplies when multiple power supplies are installed in the same remote location.

POWER INPUT:

120 volts AC, 50/60Hz

POWER OUTPUT:

Class 2; 24 Volts DC 3 x 4A, 3x96 watts maximum

DIMENSIONS:

14" x 10" x 3"

COMPATIBLE DIMMERS:

Legrand: Adorne ADTP703TU; Lutron: Diva DVELV-300P, Skylark SELV-300P, Maestro MAELV-600 and Radio RA 2

96W, 24VDC Low Voltage Wire Size Chart: 3% Voltage Drop

| WIRE LENGTH (FT) | UP TO 33' | 34'-52' | 53'-86' | 87'-130' |
|------------------------|-----------|----------|----------|----------|
| WIRE SIZE | 14 AWG | 12 AWG | 10 AWG | 8 AWG |
| VOLTAGE AT END OF WIRE | 23.28VDC | 23.29VDC | 23.28VDC | 23.28VDC |



