

CIRRUS CEILING WALL WASH WITH GLARE SHIELD

REMOTE POWER WITH TUNABLE WHITE

DESIGNED BY GREGORY KAY | ASSEMBLED IN AMERICA | PATENT PENDING

REV 03.28.25



DESCRIPTION

The New Generation of our Cirrus Wall Wash with Shield and Tunable White is precision-engineered to block glare and illuminate vertical surfaces from the top of the ceiling to the floor at a 3.3:1 ratio. Available in 5, 7 or 10 watts per foot with designer-grade 92+ CRI LEDs, rendering art and colors in their truest forms. Using the latest in LED Technology Tunable White 2000K-6500K (2K6K) or 2700K-6500K (27K6) grants independent control and adjustment of color temperature and intensity from 2000K (Sunset) through 6500K (Day Light White). 2K6K is ideal for residential spaces including, dining rooms, bedrooms, living spaces, and bathrooms by allowing the user to achieve a warm glow during the golden hours of the early mornings and evenings. For commercial environments, 27K6 promotes focus and alertness which is ideal for offices, healthcare and education, while still achieving warmer color temperatures best for hospitality and retail environments. Human-Centric lighting, or tunable white, promotes performance, mood, and overall well-being by fine-tuning the emotional effects that light has on the circadian cycle. Mounted 24" from the wall, and offered with a Split Canopy that mounts on Standard Junction Box or with a Slim Profile Channel Junction Box (C-1RE-JBOX) with no visible canopy on the ceiling becoming one with the architecture. Clips are provided every 18". Powered by Class 2, 24VDC remote power supplies that can be located up to 40' away. Ordered in various increments, from 12"-240". For lengths greater than 240" (84" chrome) or making 90° turns contact us for a custom quotation. *Remote Power Supplies are Required and Sold Separately. Fixtures include a 5 year pro-rated warranty. For custom designs and quotes, email our design team: design@PureEdgeLighting.com.

FINISHES



System	Wattage Per Foot	Canopy	Nominal Size	Color Temperature	Finish
CCWSH	5W	1R	240	27K6	SN
CCWSH Cirrus Ceiling with Glare Shield Wall Wash CCWSHW Cirrus Ceiling with Glare Shield Wall Wash with White Louver CCWSHB Cirrus Ceiling with Glare Shield Wall Wash with Black Louver	5W 4.4 Watts (240", max 20') 7W 7.4 Watts (144", max 12') 10W 9.6 Watts (120" max, 10')	1R 1" Rectangle Canopy 4S 4.6" Square Split Canopy TBA Mounting clips are compatible with 15/16" and 9/16" T-Bar systems where the ceiling panels are flush with the grid, and 15/16" tegular ceiling panels. TBB Mounting clips are compatible with 15/16" and 9/16" T-Bar systems where the ceiling panels sit below T-Bar grid (includes spacer). TBC Mounting clips are compatible with Armstrong PB Vector 15/16" T-Bar systems with 1/4" reveal ceiling panels. TBE Mounting clips are compatible with Slotted T-Bar Drop Ceiling systems with 1/4" openings, and mounts flush anywhere along the T-Bar grid. TBI Mounting clips are compatible with Armstrong Interlude™ T-Bar systems where the ceiling panels are flush with the bottom of the grid.	12-240 Order in various increments from 12"-240" *Maximum shipping length 120" *See length chart for exact dimensions	2K6K Tunable White 2000K-6500K 27K6 Tunable White 2700K-6500K	BK Satin Black BZ Antique Bronze SN Satin Nickel WH White XX Custom Finish

LENS

- Diffused White Wall Wash Lens with Glare Shield, optional Black or White Louvers

LAMP

- 5, 7 or 10 watts per foot
- Tunable White (2K6K or 27K6)
- Designer Grade High CRI 95+ LEDs
- 50,000 Hour Lamp Life

INSTALLATION

- Mounts to a Standard Junction Box, pre-wired from 120V/24VDC Remote Power Supply up to 100 Watts (sold separately) at maximum 40' away
- Includes your choice of Canopy: 1" Rectangle Junction Box or 4.6" Square Canopy Feed
- 6' Whip
- Includes drywall ceiling Mounting Clips, TBar clips order separately
- Power Supply sold separately

REMOTE POWER SUPPLIES, DIMMERS & CONTROLS (SOLD SEPARATELY)*

24VDC, Class 2 wiring

- [Home Integration Solutions](#)
- [Pure Smart™ WiZ Pro Power Supplies & Controls](#)
- [0-10V](#) Requires two dimmers, one for intensity and one for color temperature
- [DMX Dynamic Color Changing](#): Must be used with PureEdge [Controllers](#)

*In-Wall Mounting and drop ceiling Kits available for select power supplies

APPLICATIONS

Designed for indoor use only. Ideal applications include residential, commercial, retail, and hospitality environments

APPROVALS

Damp Location, Class 2 wiring, ETL Listed, RoHS, Made in America, Patent Pending

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

CIRRUS CEILING WALL WASH WITH GLARE SHIELD

REMOTE POWER WITH TUNABLE WHITE

NOMINAL LAMP DATA: Lamp data Cirrus Ceiling Wall Wash with Glare Shield

	CCWSH															
DESCRIPTION	CIRRUS WALL WASH															
WATTS PER FOOT	2K6K 5W (4.6 watts)								27K6 5w (4.6 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	246	256	266	276	286	306	328	331	334	323	332	342	352	338	334	324
LUMENS PER WATT (lm/w)	54	53	55	58	60	64	68	69	73	81	83	83	82	82	84	82
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+
DESCRIPTION																
WATTS PER FOOT	2K6K 7w (7.3 watts)								27K6 7w (7.3 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	342	358	375	391	407	439	462	467	471	375	384	398	413	408	405	404
LUMENS PER WATT (lm/w)	54	50	52	54	56	61	64	65	74	59	53	55	57	57	56	63
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+
DESCRIPTION																
WATTS PER FOOT	2K6K 10W (9.2 watts)								27K6 10w (9.2 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	699	706	706	745	719	706	706	706	699	613	631	649	668	643	635	615
LUMENS PER WATT (lm/w)	82	74	74	78	75	74	74	74	82	77	69	71	73	70	69	77
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+

	CCWSHW															
DESCRIPTION	CIRRUS WALL WASH, WHITE LOUVER															
WATTS PER FOOT	2K6K 5W (4.6 watts)								27K6 5w (4.6 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	192	200	207	215	223	239	256	258	261	251	259	266	274	264	261	252
LUMENS PER WATT (lm/w)	42	42	43	45	46	50	53	54	57	63	65	65	64	64	65	64
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+
DESCRIPTION																
WATTS PER FOOT	2K6K 7w (7.3 watts)								27K6 7w (7.3 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	267	279	292	304	317	342	360	364	367	292	299	310	322	318	315	314
LUMENS PER WATT (lm/w)	42	39	41	42	44	47	50	51	57	46	42	43	45	44	44	49
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+
DESCRIPTION																
WATTS PER FOOT	2K6K 10W (9.2 watts)								27K6 10w (9.2 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	545	550	550	580	560	550	550	550	545	478	491	506	520	501	495	479
LUMENS PER WATT (lm/w)	64	57	57	60	58	57	57	57	64	60	53	55	57	54	54	60
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+

	CCWSHB															
DESCRIPTION	CIRRUS WALL WASH, BLACK LOUVER															
WATTS PER FOOT	2K6K 5W (4.4 watts)								27K6 5w (4.4 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	112	116	121	126	130	139	149	151	152	147	151	155	160	154	152	147
LUMENS PER WATT (lm/w)	24	24	25	26	27	29	31	31	33	37	38	38	37	37	38	37
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+
DESCRIPTION																
WATTS PER FOOT	2K6K 7w (7.3 watts)								27K6 7w (7.3 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	156	163	170	177	185	199	210	212	214	171	174	181	188	185	184	183
LUMENS PER WATT (lm/w)	24	23	24	25	26	28	29	29	33	27	24	25	26	26	26	29
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+
DESCRIPTION																
WATTS PER FOOT	2K6K 10W (9.6 watts)								27K6 10w (9.6 watts)							
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	318	321	321	338	327	321	321	321	318	279	287	295	304	292	289	279
LUMENS PER WATT (lm/w)	37	33	33	35	34	33	33	33	37	35	31	32	33	32	31	35
CRI	91+	91+	91+	91+	91+	94+	94+	94+	91+	93+	93+	94+	94+	94+	93+	93+

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

CIRRUS CEILING WALL WASH WITH GLARE SHIELD

REMOTE POWER WITH TUNABLE WHITE

8' | 5W @ 30K
FOOT CANDLE DISTRIBUTION

	2'	4'	6'	8'	10'
0"	36	36	34	36	36
1"	44	44	41	42	42
3"	53	53	52	51	51
6"	75	75	72	70	70
1'	83	83	80	79	79
18"	84	84	83	81	81
2'	73	73	75	72	72
3'	55	55	62	59	59
4'	46	46	50	47	47
5'	37	37	37	37	37
6'	33	33	33	32	32
7'	28	28	28	27	27
8'	22	22	23	23	23
9'					


8' | 7W @ 30K
FOOT CANDLE DISTRIBUTION

	2'	4'	6'	8'	10'
0"	40	40	42	44	44
1"	53	53	51	55	55
3"	67	67	85	67	67
6"	97	97	103	92	92
1'	107	107	109	100	100
18"	111	111	111	106	106
2'	98	98	100	95	95
3'	79	79	83	79	79
4'	65	65	68	64	64
5'	52	52	54	51	51
6'	44	44	44	43	43
7'	37	37	39	37	37
8'	31	31	32	32	32
9'					

8' | 10W @ 30K
FOOT CANDLE DISTRIBUTION

	2'	4'	6'	8'	10'
0"	44	44	49	52	52
1"	61	61	61	68	68
3"	81	81	81	82	82
6"	118	118	118	114	114
1'	130	130	134	121	121
18"	138	138	138	131	131
2'	122	122	124	118	118
3'	102	102	104	99	99
4'	83	83	85	80	80
5'	67	67	70	65	65
6'	54	54	54	53	53
7'	46	46	49	47	47
8'	39	39	41	40	40
9'					

CANDLE POWER DISTRIBUTION



FIXTURE MOUNTED 24" FROM WALL
10W @ 2K4K CHANNEL AND DIFFUSED LENS

	2'	4'	6'	8'	10'
1"	64	72	74	73	55
3"	76	83	87	91	67
6"	96	104	106	111	83
1'	132	138	142	135	110
2'	139	155	157	151	119
3'	119	136	137	129	107
4'	94	110	113	105	89
5'	77	88	91	85	73
6'	62	69	69	69	55
7'	50	56	61	57	51
8'	43	48	51	45	43
9'	34	40	41	35	32
10'	26	30	32	30	26

DIRECTION OF LIGHT





CIRRUS CEILING WALL WASH WITH GLARE SHIELD


REMOTE POWER WITH TUNABLE WHITE



CIRRUS CEILING WALL WASH WITH GLARE SHIELD



CIRRUS CEILING WALL WASH WITH GLARE SHIELD AND BLACK LOUVER




CIRRUS CEILING WALL WASH WITH GLARE SHIELD



CIRRUS CEILING WALL WASH WITH GLARE SHIELD AND WHITE LOUVER

DRAWINGS Canopy & Channel drawings for the Cirrus Ceiling D1



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

CIRRUS CEILING WALL WASH WITH GLARE SHIELD

REMOTE POWER WITH TUNABLE WHITE

Length Chart: Actual lengths for Cirrus Ceiling Wall Wash

ORDERING CODE (NOMINAL SIZE)	ACTUAL LENGTH	5W		10W	
		WITH TWO DIMMERS: YOU NEED TWO POWER SUPPLIES, ONE FOR EACH KELVIN	DMX POWER AND CDMX CONTROLLER: YOU NEED ONE POWER SUPPLY ONLY	WITH TWO DIMMERS: YOU NEED TWO POWER SUPPLIES, ONE FOR EACH KELVIN	DMX POWER AND CDMX CONTROLLER: YOU NEED ONE POWER SUPPLY ONLY
		5 WATTS PER FT	POWER SUPPLY	10 WATTS PER FT	POWER SUPPLY
12	13	5	PSB-96W-010-24VDC-2XK	10	PSB-2X96W-010-24VDC-2XK
15	15.4	6	PSB-96W-010-24VDC-2XK	12	PSB-2X96W-010-24VDC-2XK
17	17.8	7	PSB-96W-010-24VDC-2XK	14	PSB-2X96W-010-24VDC-2XK
20	20.2	8	PSB-96W-010-24VDC-2XK	17	PSB-2X96W-010-24VDC-2XK
22	22.6	9	PSB-96W-010-24VDC-2XK	18	PSB-2X96W-010-24VDC-2XK
24	25	10	PSB-96W-010-24VDC-2XK	20	PSB-2X96W-010-24VDC-2XK
27	27.4	11	PSB-96W-010-24VDC-2XK	22	PSB-2X96W-010-24VDC-2XK
29	29.8	12	PSB-96W-010-24VDC-2XK	24	PSB-2X96W-010-24VDC-2XK
32	32.2	13	PSB-96W-010-24VDC-2XK	27	PSB-2X96W-010-24VDC-2XK
34	34.6	14	PSB-96W-010-24VDC-2XK	28	PSB-2X96W-010-24VDC-2XK
36	37	15	PSB-96W-010-24VDC-2XK	30	PSB-2X96W-010-24VDC-2XK
39	39.4	16	PSB-96W-010-24VDC-2XK	32	PSB-2X96W-010-24VDC-2XK
41	41.8	17	PSB-96W-010-24VDC-2XK	34	PSB-2X96W-010-24VDC-2XK
44	44.2	18	PSB-96W-010-24VDC-2XK	37	PSB-2X96W-010-24VDC-2XK
46	46.6	19	PSB-96W-010-24VDC-2XK	38	PSB-2X96W-010-24VDC-2XK
48	49	20	PSB-96W-010-24VDC-2XK	40	PSB-2X96W-010-24VDC-2XK
51	51.4	21	PSB-96W-010-24VDC-2XK	42	PSB-2X96W-010-24VDC-2XK
53	53.8	22	PSB-96W-010-24VDC-2XK	44	PSB-2X96W-010-24VDC-2XK
56	56.2	23	PSB-96W-010-24VDC-2XK	47	PSB-2X96W-010-24VDC-2XK
58	58.6	24	PSB-96W-010-24VDC-2XK	48	PSB-2X96W-010-24VDC-2XK
60	61	25	PSB-96W-010-24VDC-2XK	50	PSB-2X96W-010-24VDC-2XK
63	63.4	26	PSB-96W-010-24VDC-2XK	52	PSB-2X96W-010-24VDC-2XK
65	65.8	27	PSB-96W-010-24VDC-2XK	54	PSB-2X96W-010-24VDC-2XK
68	68.2	28	PSB-96W-010-24VDC-2XK	57	PSB-2X96W-010-24VDC-2XK
70	70.6	29	PSB-96W-010-24VDC-2XK	58	PSB-2X96W-010-24VDC-2XK
72	73	30	PSB-96W-010-24VDC-2XK	60	PSB-2X96W-010-24VDC-2XK
75	75.4	31	PSB-96W-010-24VDC-2XK	62	PSB-2X96W-010-24VDC-2XK
77	77.8	32	PSB-96W-010-24VDC-2XK	64	PSB-2X96W-010-24VDC-2XK
80	80.2	33	PSB-96W-010-24VDC-2XK	67	PSB-2X96W-010-24VDC-2XK
82	82.6	34	PSB-96W-010-24VDC-2XK	68	PSB-2X96W-010-24VDC-2XK
84*	85	35	PSB-96W-010-24VDC-2XK	70	PSB-2X96W-010-24VDC-2XK
87	87.4	36	PSB-96W-010-24VDC-2XK	72	PSB-2X96W-010-24VDC-2XK
89	89.8	37	PSB-96W-010-24VDC-2XK	74	PSB-2X96W-010-24VDC-2XK
92	92.2	38	PSB-96W-010-24VDC-2XK	77	PSB-2X96W-010-24VDC-2XK
94	94.6	39	PSB-96W-010-24VDC-2XK	78	PSB-2X96W-010-24VDC-2XK
96	97	40	PSB-2X96W-010-24VDC-2XK	80	PSB-2X96W-010-24VDC-2XK
99	99.4	41	PSB-2X96W-010-24VDC-2XK	82	PSB-2X96W-010-24VDC-2XK
101	101.8	42	PSB-2X96W-010-24VDC-2XK	84	PSB-2X96W-010-24VDC-2XK
104	104.2	43	PSB-2X96W-010-24VDC-2XK	87	PSB-2X96W-010-24VDC-2XK
106	106.6	44	PSB-2X96W-010-24VDC-2XK	88	PSB-2X96W-010-24VDC-2XK
108	109	45	PSB-2X96W-010-24VDC-2XK	90	PSB-2X96W-010-24VDC-2XK
111	111.4	46	PSB-2X96W-010-24VDC-2XK	92	PSB-2X96W-010-24VDC-2XK
113	113.8	47	PSB-2X96W-010-24VDC-2XK	94	PSB-2X96W-010-24VDC-2XK
116	116.2	48	PSB-2X96W-010-24VDC-2XK	97	PSB-2X96W-010-24VDC-2XK
118	118.6	49	PSB-2X96W-010-24VDC-2XK	98	PSB-2X96W-010-24VDC-2XK
120**	121	50	PSB-2X96W-010-24VDC-2XK	100	PSB-2X96W-010-24VDC-2XK
123	123.4	51	PSB-2X96W-010-24VDC-2XK		
125	125.8	52	PSB-2X96W-010-24VDC-2XK		
128	128.2	53	PSB-2X96W-010-24VDC-2XK		
130	130.6	54	PSB-2X96W-010-24VDC-2XK		
132	133.0	55	PSB-2X96W-010-24VDC-2XK		
135	135.4	56	PSB-2X96W-010-24VDC-2XK		

*Maximum Chrome Length **Maximum Shipping Length

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

CIRRUS CEILING WALL WASH WITH GLARE SHIELD

REMOTE POWER WITH TUNABLE WHITE

Length Chart: Actual lengths for Cirrus Ceiling Wall Wash continued


		5W					5W		
		WITH TWO DIMMERS: YOU NEED TWO UNI DRIVER POWER SUPPLIES, ONE FOR EACH KELVIN (SEE PAGES BELOW)		DMX POWER AND CDMX CONTROLLER: YOU NEED ONE POWER SUPPLY ONLY (SEE PAGES BELOW)			WITH TWO DIMMERS: YOU NEED TWO UNI DRIVER POWER SUPPLIES, ONE FOR EACH KELVIN (SEE PAGES BELOW)		DMX POWER AND CDMX CONTROLLER: YOU NEED ONE POWER SUPPLY ONLY (SEE PAGES BELOW)
ORDERING CODE (NOMINAL SIZE)	ACTUAL LENGTH	5 WATTS PER FT	POWER SUPPLY	POWER SUPPLY	ORDERING CODE (NOMINAL SIZE)	ACTUAL LENGTH	5 WATTS PER FT	POWER SUPPLY	POWER SUPPLY
137	137.8	57	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	190	190.6	79	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
140	140.2	58	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	192	193.0	80	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
142	142.6	59	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	195	195.4	81	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
144	145.0	60	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	197	197.8	82	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
147	147.4	61	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	200	200.2	83	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
149	149.8	62	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	202	202.6	84	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
152	152.2	63	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	204	205.0	85	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
154	154.6	64	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	207	207.4	86	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
156	157.0	65	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	209	209.8	87	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
159	159.4	66	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	212	212.2	88	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
161	161.8	67	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	214	214.6	89	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
164	164.2	68	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	216	217.0	90	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
166	166.6	69	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	219	219.4	91	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
168	169.0	70	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	221	221.8	92	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
171	171.4	71	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	224	224.2	93	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
173	173.8	72	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	226	226.6	94	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
176	176.2	73	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	228	229.0	95	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
178	178.6	74	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	231	231.4	96	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
180	181.0	75	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	233	233.8	97	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
183	183.4	76	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	236	236.2	98	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
185	185.8	77	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	238	238.6	99	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK
188	188.2	78	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK	240	241.0	100	PSB-2X96W-010-24VDC-2XK	PSB-100W-24VDC-2XK

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

CIRRUS CEILING WALL WASH WITH GLARE SHIELD


REMOTE POWER WITH TUNABLE WHITE

ADDITIONAL COMPONENTS



1" RECTANGLE CANOPY & J-BOX
(INCLUDED WITH 1R SELECTED IN FIXTURE ORDERING CODE)
 The Slim-Profile Junction Box with Hanger Bars mounts to studs spaced between 14.5" and 25" apart behind drywall. Allows low voltage DC wires from Remote Power Supply to connect to channel wires. The Junction Box opening is covered by the fixture for a clean, safe connection. Includes a Goof Plate, for poor plastering around J-box.

System	Canopy	Product
C	1RE	JBOX
C Channel	1RE 1" Rectangle	JBOX Junction Box



4" SQUARE SPLIT CANOPY
(INCLUDED WITH 4S SELECTED IN FIXTURE ORDERING CODE)
 The 4" Square Canopy fits on a standard 4" electrical box with round plaster ring. It fits flush along channel while covering Junction Box. The Canopy may float anywhere along the channel and comes in six finishes.

System	Canopy	Finish
CC	4SQ	SN
CC Cirrus Ceiling	4SQ 4.6" Split Square	BK Satin Black BZ Antique Bronze CH Chrome SB Satin Brass SN Satin Nickel WH White




CIRRUS CEILING WALL WASH WITH GLARE SHIELD

REMOTE POWER WITH TUNABLE WHITE

REV 03.28.25

T-Bar Mounting Options for Cirrus Channels

9/16" TBAR 15/16" TBAR





CEILING MOUNTING T-BAR CLIPS FOR 15/16" AND 9/16" CEILING GRID

TBA mounting clips are compatible with 15/16" and 9/16" T-Bar systems where the ceiling panels are flush with the grid, and 15/16" tegular ceiling panels.

System	Component	Type	Finish
CCD1M	MCL	TBA	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBA T-Bar Clip	WH White BK Black

15/16" TBAR






CEILING MOUNTING T-BAR CLIPS FOR 15/16" CEILING GRID

TBB mounting clips are compatible with 15/16" T-Bar systems where the ceiling panels sit below T-Bar grid (includes spacer).

System	Component	Type	Finish
CCD1M	MCL	TBB	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBB T-Bar Clip	WH White BK Black

OPTIMA PB VECTOR






T-BAR CLIP FOR ARMSTRONG® OPTIMA® PB VECTOR

TBC Mounting clips are compatible with Armstrong® Optima® PB Vector 15/16" T-Bar systems with 1/4" reveal ceiling panels.

System	Component	Type	Finish
CCD1M	MCL	TBC	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBC T-Bar Clip	WH White BK Black

SLOTTED T-BAR






T-BAR SLOT MOUNTING CLIP

TBE Mounting clips are compatible with Slotted T-Bar Drop Ceiling systems with 1/4" openings, and mounts flush anywhere along the T-Bar grid.

System	Component	Type	Finish
CCD1M	MCL	TBE	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBE T-Bar Clip	WH White BK Black

SLOTTED T-BAR FINELINE 1/8"



T-BAR FINELINE® SLOT MOUNTING CLIP

TBF Mounting clips are compatible with Donn® Fineline® Slotted T-Bar Drop Ceiling systems with 1/8" openings, and mounts flush anywhere along the T-Bar grid.

System	Component	Type	Finish
CCD1M	MCL	TBF	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBF T-Bar Clip	WH White BK Black


PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

CIRRUS CEILING WALL WASH WITH GLARE SHIELD


REMOTE POWER WITH TUNABLE WHITE

REV 03.28.25



ARMSTRONG®
INTERLUDE XL HRC



TBI



ARMSTRONG
INTERLUDE™ T-BAR,
CIRRUS BELOW
DROP CEILING TILES




T-BAR INTERLUDE CLIP AND 9/16" FLAT GRID WITH REGULAR TILES


TBI Mounting clips are compatible with Armstrong Interlude™ T-Bar systems where the ceiling panels are flush with the bottom of the grid and compatible with 9/16" flat grid with regular tiles that sit below the grid up to 3/8".

System	Component	Type	Finish
CCD1M	MCL	TBI	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBI T-Bar Clip	WH White BK Black


FLAT 9/16" TBAR GRID



CIRRUS BETWEEN
AND ACROSS
DROP CEILING TILES



TBM



METAL CEILING




MAGNETIC TAPE


TBM Magnetic Tape is compatible with flat metal ceilings such as Armstrong® Metalworks™.

System	Component	Type	Finish
CCD1M	MCL	TBM	WH
CCD1M Cirrus Ceiling	MCL Mounting Clip	TBM T-Bar Magnetic Tape	WH White BK Black



Drywall Mounting Options for Cirrus Channels



CC-MCL




DRYWALL CEILING




CEILING MOUNTING SPRING CLIP

Ceiling Mounting Spring clips are provided with every 2ft of Cirrus Ceiling Channel. The Clip snaps into the channel, staying securely fastened to the ceiling or wall.



System	Component
CC	MCL
CC Cirrus Ceiling	MCL Mounting Clip



CC-MCL-L



DRYWALL CEILING



CEILING MOUNTING LOCKING CLIP

Ceiling Mounting Locking Clips may be ordered separately for extra support. The channel slides into the clip and locks in place staying securely fastened to the ceiling or to the wall.

System	Component	Type
CC	MCL	L
CC Cirrus Ceiling	MCL Mounting Clip	L Locking


TM30 DATA

REMOTE POWER WITH TUNABLE WHITE

TM-30-15 DATA: The data below is for Tunable White bare LED Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

2000K ONLY (2K6K/27K6) | Rf: 90.6 | Rg: 98.5

Color Vector Graphic




■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	87.7	-5.5%	1.2%
2	88.7	-3.9%	4.2%
3	90.5	-1.5%	4.3%
4	95.0	-1.7%	0.8%
5	95.2	-0.2%	2.1%
6	94.2	1.6%	1.9%
7	95.9	-0.8%	-2.2%
8	95.5	-1.7%	1.3%
9	93.8	-1.4	2.6%
10	91.9	-0.7%	4.2%
11	91.3	3.6%	3.7%
12	91.2	4.2%	-1.0%
13	86.6	3.8%	-12.7%
14	67.2	-3.0%	-16.3%
15	84.9	-3.3%	-9.4%
16	84.2	-5.7%	-7.5%

3000K (2K6K/27K6) | Rf: 90.5 | Rg: 100.7

Color Vector Graphic




■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	91.5	-3.5%	1.2%
2	92.4	-1.8%	2.7%
3	89.8	0.3%	4.5%
4	92.4	-1.7%	0.4%
5	93.3	-0.1%	1.4%
6	94.5	2.1%	-0.6%
7	91.0	-2.5%	0.3%
8	96.9	-0.8%	-0.2%
9	91.6	-0.9%	4.6%
10	86.7	0.7%	7.8%
11	86.3	3.8%	8.5%
12	88.3	6.1%	0.6%
13	90.9	3.1%	-5.2%
14	87.3	4.7%	-7.9%
15	92.1	-1.9%	-2.5%
16	84.5	-0.9%	-10.9%

4000K ONLY (2K6K/27K6) | Rf: 86.4 | Rg: 96.1

Color Vector Graphic



■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	86.5	-5.5%	1.3%
2	90.4	-3.0%	2.3%
3	89.8	-2.1%	3.6%
4	89.1	-3.4%	0.4%
5	88.5	-5.9%	0.1%
6	93.6	-3.0%	-0.4%
7	88.9	-6.2%	1.7%
8	87.3	-5.0%	4.9%
9	82.4	-3.6%	11.3%
10	77.4	-1.8%	12.7%
11	79.8	4.9%	11.4%
12	88.7	4.4%	2.7%
13	88.7	4.0%	-5.1%
14	91.2	2.2%	-3.8%
15	82.7	-0.1%	-9.2%
16	82.8	-2.2%	-7.6%