


MTC48 MicroTrack™ CEILING MOUNT

48VDC CLASS 2, CEILING MOUNT TRACK SYSTEM

ASSEMBLED IN AMERICA

REV 12.16.25



DESCRIPTION

MTC48 MicroTrack™ is a 48VDC surface-mounted system, engineered with a sleek and compact aluminum profile measuring just 1/2" deep by 7/16" wide and featuring a 1/4" slot. Designed for a clean, contemporary aesthetic, it supports a variety of fixture options. The track mounts directly to drywall ceilings, offering precision-engineered flexibility that allows it to seamlessly curve and turn along ceilings and walls. For a refined architectural finish in black or white, each track includes a matching Slot Cover to conceal the copper bus bars and mounting screws. For custom quotes and layout assistance, send your drawings and ideas to our design team: design@PureEdgeLighting.com.

FEATURES

- Track Heads easily attach to the track and adjust, tilt, and rotate. Quick Connect- and Teeny track heads can be installed with one hand (no screwdriver necessary).
- Designed for use with Class 2, 48VDC Universal Remote Power Supplies up to 40' away with low voltage wire
- Power Feeds offered with End and Center Feeds, with up to two-96W Remote Power Supplies with Center Feed before re-feeding
- Straight Channels are available in 4' (44") and 8' (92") lengths, with the ability to be cut in the field
- Curved Channels are available in 12" and 20" radii
- Includes an opaque Slot Cover to conceal the copper bus bars and mounting screws
- T-Bar MicroTrack™ fits on 9/16" and 15/16" T-Bar ceiling with MTT48 TRACK (1/8" higher track)

LAMP

- Lumens: Up to 1776 lm at 3000K
- Lumens Per Watt: Up to 127 lm/w at 3000K
- CRI: Minimum 90 color rendering index
- CCT: 2400K, 2700K, 3000K, 3500K, 4000K (Warm Dim available for 3000K color temperature with a great color consistency (within 3.0- step MacAdam ellipse)
- LED Lamp Life: Minimum 50,000hr with 85% of lumen maintenance in 25C ambient temperature, in compliance with IES LM-80 testing measurements

FINISH & MATERIAL

- Slot Cover: Black or Matte White PVC
- Extruded Aluminum Channel, conductors are a pair of #12 Gauge Copper Busbar

POWER SUPPLY AND DIMMING (SOLD SEPARATELY)

2 x 96W 48VDC, Remote Power

- [48VDC UNI Driver: Universal Dimming](#) (ELV, TRIAC, 0-10V)
- ELV & TRIAC [Smart Dimmer & Switch](#)
- [2-in-1 Power Driver and Dimmer](#)

APPLICATIONS

Indoor use only. Ideal applications in residential, commercial, retail and hospitality environments.

WARRANTY / LABELS


5 year pro-rated warranty. Assembled in America
 ETL (Conforms to UL 1598 and CSA 22.2 #250.0), Class 2 Under 100 Watts, Title 24

MTC48 MicroTrack™ CEILING MOUNT

48VDC CLASS 2, CEILING MOUNT TRACK SYSTEM

COMPONENTS


MICROTRACK™ CEILING 48VDC



STRAIGHT 1 CIRCUIT CHANNEL


Extruded Aluminum Channel with a 12 gauge bus bar to help eliminate voltage drop. For use with 48VDC Remote Power Supply, sold separately. Includes an End Cap, a Straight Connector, and an opaque Slot Cover to conceal the track slots.

System	Circuit	Nominal Length in Feet	Finish
MTC48	1C	8FT	BK
MTC48 MicroTrack Ceiling 48VDC	1C Single Circuit	4FT 44"	BK Black
MTT48 MicroTrack with 9/16" & 15/16" T-Bar Clip		8FT 92"	MW Matte White RAL 9003



CURVE 1 CIRCUIT CHANNEL

May be used with Flex Light. Comes with one Straight Connector




System	Circuit	Radius in Inches	Finish
MTC48	1C	20R	BK
MTC48* MicroTrack Ceiling Curved 48VDC	1C Single Circuit	12R 12" Radius	BK Black
MTT48* MicroTrack Ceiling Curved 48VDC with T-Bar Clip, one every 2ft		20R* 20" Radius	MW Matte White RAL 9003

*Curved track is not compatible with a Slot Cover

*Track Heads fit in 20R 20" radius track only

END OR CENTER POWER FEED

The End Power Feed delivers 48VDC from a single 96-watt remote power supply, while the Center Power Feed supports up to two 96-watt, 48VDC remote power supplies. Both options are Class 2 with Power supplies on the same line voltage circuit (same phase). Includes Straight Connector, End Power, and a Slot Cover.



System	Circuit & Type	Canopy	Finish
MTC48	EP	4SQ	BK
MTC48 MicroTrack Ceiling 48VDC	EP End Power Feed Single Circuit, with 12" long track	4SQ 4.5" Square Junction Box Cover	BK Black
MTT48 MicroTrack with T-Bar Clip	CP1 Center Power Feed Single Circuit, with 12" long track	1RE* 1" Rectangle Junction Box Cover (Jbox Plaster Ring included)	MW Matte White RAL 9003
	CP2 Two Center Power Feeds Both Directions, with 12" long track		

*Cannot be used with T-Bar Track

T-BAR CEILING MOUNTING CLIP (INCLUDED WITH THE MTT48 TRACK).

For 15/16" and 9/16" ceiling grid.



System	Component	Type	Finish
MT48	MCL	TBA	BK
MT48 MicroTrack 48VDC	MCL Mounting Clip	TBA T-Bar Clip	BK Black
			MW Matte White RAL 9003


MTC48 MicroTrack™ CEILING MOUNT

48VDC CLASS 2, CEILING MOUNT TRACK SYSTEM


ACCESSORIES



L-CONNECTOR



VERTICAL CONNECTOR




L-SHAPED / VERTICAL CONNECTORS

L-Shaped and Vertical 48VDC Connector joins two sections of track at 90°


System	Circuit	Type	Finish
MTC48	1C	LC	BK
MTC48 MicroTrack Ceiling 48VDC	1C Single Circuit	LC L-Connector Conductive LNC L-Connector Non-Conductive VC Vertical Connector Conductive VNC Vertical Connector Non-Conductive	BK Black MW Matte White RAL 9003

FLEX CONNECTOR

Flexible 48VDC Connector joins two sections of track at any angle.




System	Circuit	Type	Finish
MT48	1C	FXC	BK
MT48 MicroTrack 48VDC	1C Single Circuit	FXC Flex Connector	BK Black MW Matte White RAL 9003



System	Circuit	Type	Finish
MT48	1C	FXCL	BK
MT48 MicroTrack 48VDC	1C Single Circuit	FXCL Flex Connector Long 12"	BK Black MW Matte White RAL 9003

ADDITIONAL PARTS




STRAIGHT CONNECTOR (INCLUDED WITH EACH TRACK)

Straight 48VDC Connector joins two track sections end to end and is concealed by the Slot Covers.

System	Circuit	Type	Finish
MT48	1C	SC	BK
MT48 MicroTrack 48VDC	1C Single Circuit	SC Straight Connector Conductive SNC Straight Connector Non-Conductive	BK Black MW Matte White RAL 9003

END POWER FEED (INCLUDED WITH POWER TRACK)


End Power feed up to 96 watts at 48VDC. Can be used to replace lost part.



System	Circuit	Type	Finish
MT48	1C	EP	BK
MT48 MicroTrack 48VDC	1C Single Circuit	EP End Power Feed	BK Black MW Matte White RAL 9003


MTC48 MicroTrack™ CEILING MOUNT

48VDC CLASS 2, CEILING MOUNT TRACK SYSTEM



END CAPS (INCLUDED WITH EACH TRACK)


System	Circuit	Type	Finish
MT48	1C	CA	BK
MT48 MicroTrack 48VDC MTC48 for T-Bar MicroTrack	1C Single Circuit	CA End Cap	BK Black MW Matte White RAL 9003



REINFORCEMENT JOINER

Reinforcement joiner used for cutting and mechanically joining two tracks together.

System	Type
MT48	J1
MT48 MicroTrack 48VDC	J1 Reinforcement Joiner



OPAQUE SLOT COVER (INCLUDED WITH EACH TRACK)

Slot Covers included to conceal conductor and track slots.

System	Type	Length in Feet	Cover Color
MT48	SCO	8FT	BK
MT48 MicroTrack 48VDC	SCO Opaque Cover for Track Slot	8FT 8'	BK Black MW Matte White RAL 9003

MT48 MicroTrack™ TRACK HEADS


48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

PureEdge MT48 Track Heads are compatible with all MicroTrack™ Systems. May also be ordered with a [MonoPoint Canopy](#).

TEENY (BUT POWERFUL)

712 LM @ 3000K, 6 WATT, TITLE 24



*For lenses and lens accessories, refer to the accessories page


System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	TEE	6W	NF	30K	BK
MT48 MicroTrack 48VDC	TEE Teeny Track Head	6W 6 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 36° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D* 3000K dims to 1800K 35K 3500K Neutral White 40K 4000K Cool White *Uses 5 Watts and is not compatible with NS (15°) lens	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	TEENY (WITH NARROW SPOT 15° LENS)					
COLOR TEMPERATURE	24K	27K	30K	30D*	35K	40K
TOTAL LUMENS	676	684	712	373	817	862
WATTS	6	6	6	5	6	6
LUMENS PER WATT (lm/w)	113	114	119	75	136	144
CRI	95+	95+	95+	95+	95+	95+

*30D - Warm Dim (5 Watts)

SLIM

671 LM @ 3000K, 6 WATT, TITLE 24



*For lenses and lens accessories, refer to the accessories page

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	SLM	6W	NF	30K	BK
MT48 MicroTrack 48VDC	SLM Slim Track Head	6W 6 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 36° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D* 3000K dims to 1800K 35K 3500K Neutral White 40K 4000K Cool White *Not compatible with the NS (15°) lens	BK Black Powder Coat MW Matte White Powder Coat RAL 9003 SB Satin Brass SN Satin Nickel

	SLIM (WITH NARROW SPOT 15° LENS)					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	637	644	671	505	770	812
WATTS	6	6	6	6	6	6
LUMENS PER WATT (lm/w)	106	107	112	84	128	135
CRI	95+	95+	95+	95+	95+	95+

MT48 MicroTrack™ TRACK HEADS



48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

PureEdge MT48 Track Heads are compatible with all MicroTrack™ Systems.

PICO & PICO ZOOM

965 LM @ 3000K, 10 WATT, TITLE 24 (PICO) / 750 LM @ 3000K, 10 WATTS, TITLE 24 (PICO ZOOM)



*For lenses and lens accessories, refer to the accessories page



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	PCO	10W	FL	30K	BK
MT48 MicroTrack 48VDC	PCO Pico Track Head	10W 10 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 36° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D 3000K Warm Dim 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003, Matte White stem SB* Satin Brass SN* Satin Nickel
	PCZ Pico Zoom Track Head, Beam Spread NSFL 15°-50°		NSFL Narrow Spot 15° to Flood 50° (Pico Zoom Only)		

*Not available with Pico Zoom

	PICO (WITH SPOT 24° LENS)						PICO ZOOM (WITH 50° BEAM SPREAD)					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	917	926	965	853	1107	1168	713	720	750	578	860	908
WATTS	10	10	10	10	10	10	11	11	11	11	11	11
LUMENS PER WATT (lm/w)	92	93	97	85	111	117	65	65	68	53	78	83
CRI	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+

POP & POP ZOOM

1865 LM @ 3000K, 15 WATT, TITLE 24 (POP) / 1062 LM @ 3000K, 15 WATT, TITLE 24 (POP ZOOM)



*For lenses and lens accessories, refer to the accessories page

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	POP	15W	NS	30K	BK
MT48 MicroTrack 48VDC	POP Pop Track Head	15W 15 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 35° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D* 3000K Warm Dim 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003, Matte White stem SB* Satin Brass SN* Satin Nickel
	POZ Pop Zoom Track Head, Beam Spread NSFL 15°-50°		NSFL Narrow Spot 15° to Flood 50° (Pop Zoom Only)		

*Not compatible with FL (50°) lens

*Not available with Pop Zoom

	POP (WITH FLOOD 50° LENS)						POP ZOOM (WITH 50° BEAM SPREAD)					
COLOR TEMPERATURE	24K	27K	30K	30D*	35K	40K	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	1772	1790	1865	1051	2140	2257	1009	1020	1062	878	1218	1285
WATTS	15	15	15	12	15	15	15	15	15	15	15	15
LUMENS PER WATT (lm/w)	118	119	124	88	143	150	67	68	71	55	81	86
CRI	95+	95+	95+	97+	95+	95+	98+	98+	98+	98+	98+	98+

*30D - Warm Dim (12 Watts), Narrow Flood 35° Lens

MT48 MicroTrack™ TRACK HEADS


48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

PureEdge MT48 Track Heads are compatible with all MicroTrack™ Systems.

FRAME 1 & 2

570 LM @ 3000K, 10 WATT 48VDC CLASS 2, TITLE 24 (FRAME 1) / 571 LM @ 3000K, 15 WATT 48V CLASS 2, TITLE 24 (FRAME 2)



*For color filters and Gobo lenses, refer to the accessories page

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	FRM2	15W	SPNF	30K	BK
MT48 MicroTrack 48VDC	FRM1 Frame 1 Track Head FRM2 Frame 2 Track Head	10W 10 Watts 15W 15 Watts	SPNF Spot 20° to Narrow Flood 30°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D 3000K Warm Dim 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	FRAME 1 (WITH 30° BEAM SPREAD)						FRAME 2 (WITH 30° BEAM SPREAD)					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	542	547	570	439	654	690	542	548	571	440	655	691
WATTS	10	10	10	11	10	10	15	15	15	14	15	15
LUMENS PER WATT (lm/w)	54	55	57	40	65	69	36	37	38	31	44	46
CRI	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+

MINI LIGHT BAR

134 LM @ 3000K, 5 WATT, 12" LENGTH



5W12: 11-7/16" (29cm)
9W24: 22-13/16" (58cm)
14W36: 34-5/8" (87cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	MLB	5W12	30K	BK
MT48 MicroTrack 48VDC	MLB Mini Light Bar	5W12 5 Watts, 12" Length 9W24 9 Watts, 24" Length 14W36 14 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK* Black Powder Coat *Mini Light Bar is tucked into track, only lens is visible

	MINI LIGHT BAR											
WATTAGE	6W				11W				17W			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	129	134	154	162	273	284	326	344	427	445	511	538
LUMENS PER WATT (lm/w)	26	27	31	32	30	32	36	38	31	32	36	38
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+



MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

LIGHT BAR

400 LM @ 3000K, 6 WATT, 12" LENGTH, TITLE 24





6W12: 11-11/16" (29.7cm)
11W24: 23-1/4" (59cm)
17W36: 34-13/16" (88.4cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	LB	6W12	30K	BK
MT48 MicroTrack 48VDC	LB Light Bar	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR WITH 140° LENS											
WATTAGE	6W - 12" (11-11/16")				11W - 24" (23-1/4")				17W - 36" (34-13/16")			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	384	400	459	484	768	800	918	968	1152	1200	1377	1452
LUMENS PER WATT (lm/w)	64	67	76	81	128	133	153	161	192	200	229	242
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR LOUVER

129 LM @ 3000K, 6 WATT, 12" LENGTH, TITLE 24



6W12: 11-11/16" (29.7cm)
11W24: 23-1/4" (59cm)
17W36: 34-13/16" (88.4cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	LBL	6W12	30K	BK
MT48 MicroTrack 48VDC	LBL Light Bar Louver	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR LOUVER & 120° LENS											
WATTAGE	6W - 12" (11-11/16")				11W - 24" (23-1/4")				17W - 36" (34-13/16")			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	124	129	148	156	248	258	296	312	372	387	444	468
LUMENS PER WATT (lm/w)	21	22	25	26	41	43	49	52	62	65	74	78
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+



MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

LIGHT BAR HEXCELL LOUVER

168 LM @ 3000K, 6 WATT, 12" LENGTH, TITLE 24





6W12: 11-11/16" (29.7cm)
 11W24: 23-1/4" (59cm)
 17W36: 34-13/16" (88.4cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	LBH	6W12	30K	BK
MT48 MicroTrack 48VDC	LBH Light Bar Hexcell Louver	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR WITH HEXCELL LOUVER & 120° LENS											
WATTAGE	6W - 12" (11-11/16")				11W - 24" (23-1/4")				17W - 36" (34-13/16")			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	161	168	193	203	323	336	385	407	484	504	578	610
LUMENS PER WATT (lm/w)	27	28	32	34	54	56	64	68	81	84	96	102
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR ACCENT

548 LM @ 3000K, 9 WATT, 6" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BA	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BA Bar Accent	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle MB Matte White Fixture Black Baffle

	LIGHT BAR ACCENT WITH 30° LENS							
WATTAGE	9W				16W			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	526	548	629	663	1005	1047	1201	1267
LUMENS PER WATT (lm/w)	88	91	105	111	168	175	200	211
CRI	90+	90+	90+	90+	90+	90+	90+	90+



MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

LIGHT BAR ACCENT HEXCELL LOUVER

270 LM @ 3000K, 9 WATT, 16" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BAH	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BAH Bar Accent Hexcell Louver	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle MB Matte White Fixture Black Baffle

LIGHT BAR ACCENT WITH HEXCELL LOUVER & 30° LENS

	9W				16W			
WATTAGE	9W	9W	9W	9W	16W	16W	16W	16W
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	259	270	310	327	493	514	590	622
LUMENS PER WATT (lm/w)	43	45	52	54	82	86	98	104
CRI	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR ACCENT TILT

548 LM @ 3000K, 9 WATT, 6" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BAT	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BAT Bar Accent Tilt	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle MB Matte White Fixture Black Baffle



LIGHT BAR ACCENT ROTATABLE WITH 30° LENS

	9W				16W			
WATTAGE	9W	9W	9W	9W	16W	16W	16W	16W
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	526	548	629	663	1005	1047	1201	1267
LUMENS PER WATT (lm/w)	88	91	105	111	168	175	200	211
CRI	90+	90+	90+	90+	90+	90+	90+	90+




MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED


REV 12.16.25

LIGHT BAR ACCENT TILT HEXCELL LOUVER

270 LM @ 3000K, 9 WATT, 16" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BATH	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BATH Bar Accent Tilt Hexcell Louver	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle MB Matte White Fixture Black Baffle






LIGHT BAR ACCENT ROTATABLE WITH HEXCELL LOUVER & 30° LENS

	9W				16W			
WATTAGE	9W	9W	9W	9W	16W	16W	16W	16W
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	259	270	310	327	493	514	590	622
LUMENS PER WATT (lm/w)	43	45	52	54	82	86	98	104
CRI	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR WALL WASH

548 LM @ 3000K, 9 WATT, 16" LENGTH, TITLE 24



System	Fixture	Wattage	Color Temperature	Finish
MT48	BWW	9W6	30K	BK
MT48 MicroTrack 48VDC	BWW Bar Wall Wash	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

LIGHT BAR WALL WASH

	9W				16W			
WATTAGE	9W	9W	9W	9W	16W	16W	16W	16W
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	526	548	629	663	1005	1047	1201	1267
LUMENS PER WATT (lm/w)	88	91	105	111	168	175	200	211
CRI	90+	90+	90+	90+	90+	90+	90+	90+

MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED


REV 12.16.25

MICROTRACK™ FLEX LIGHT

70 LM@ 3000K, 3 WATT



Flex Light in White & Black Ceiling Curved Track (MTCC48)



System	Fixture	Wattage	Length	Color Temperature
MT48	FN2	3W	16FT	30K
MT48 MicroTrack 48VDC	FN2 Flex Light	3W 3 Watts per foot	1-16FT 1-16 Feet	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White

	FLEX LIGHT			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	95	99	114	85
WATTS	3	3	3	3
LUMENS PER WATT (lm/w)	32	33	38	28
CRI	90+	90+	90+	90+

HILO PENDANT

350 LM @ 3000K, 12 WATT



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	HLP	12W	VW	30K	BK
MT48 MicroTrack 48VDC	HLP HiLo Pendant	12W 12 Watts	VW Very Wide 100°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	HILO PENDANT			
WATTAGE	12W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	336	350	403	424
LUMENS PER WATT (lm/w)	28	29	34	35
CRI	90+	90+	90+	90+


MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

TOTEM PENDANT

596 LM @ 3000K, 7 WATT




System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	TTP	7W	SP	30K	BK
MT48 MicroTrack 48VDC	TTP Totem Pendant	7W 7 Watts	SP Spot 20° NF Narrow Flood 24° FL Flood 36° WF Wide Flood 56°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White

	TOTEM PENDANT			
WATTAGE	7W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	572	596	685	721
LUMENS PER WATT (lm/w)	82	85	98	103
CRI	90+	90+	90+	90+

TOWER PENDANT

707 LM @ 3000K, 7 WATT



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	TOP	7W	SP	30K	BK
MT48 MicroTrack 48VDC	TOP Tower Pendant	7W 7 Watts	SP Spot 20° NF Narrow Flood 24° FL Flood 36° WF Wide Flood 47°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White

	TOTEM PENDANT			
WATTAGE	7W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	679	707	813	855
LUMENS PER WATT (lm/w)	97	101	116	122
CRI	90+	90+	90+	90+


MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

MIDAS PENDANT

1776 LM @ 3000K, 15 WATT




System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	MIP	15W	SP	30K	BSB
MT48 MicroTrack 48VDC	MIP Midas Pendant	15W 15 Watts	SP Spot 20° NF Narrow Flood 25° FL Flood 38° WF Wide Flood 50°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White BSB Black and Satin Brass

	MIDAS PENDANT			
WATTAGE	15W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	1705	1776	2042	2149
LUMENS PER WATT (lm/w)	114	118	136	143
CRI	90+	90+	90+	90+

*For lens accessories, refer to the accessories page

DROP PENDANT

1755 LM @ 3000K, 15 WATT



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	DP	15W	SP	30K	BK
MT48 MicroTrack 48VDC	DP Drop Pendant	15W 15 Watts	SP Spot 20° NF Narrow Flood 25° FL Flood 38° WF Wide Flood 50°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White

	DROP PENDANT			
WATTAGE	15W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	1685	1755	2018	2124
LUMENS PER WATT (lm/w)	112	117	135	142
CRI	90+	90+	90+	90+

MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25

Accessories

TEENY / SLIM OPTICAL LENS		GLASS LENS	LOUVER	FOCUS LENS	LINEAR SPREAD FILM
					
ORDERING CODE	(STATIC WHITE) OPL-SLM-NS-SW OPL-SLM-SP-SW OPL-SLM-NF-SW OPL-SLM-FL-SW		GL9-AS (ASYMMETRIC) GL9-SF (SOFT DIFFUSER)	L09-H	LF09-SF (SOFT FOCUS), LF09-MF (MEDIUM FOCUS), LF09-WF (WIDE FOCUS) LF09-LS
LENS SIZE	ø1-5/16" (3.3cm) Diameter				
DESCRIPTIONS	NS (15°), SP (24°), NF (36°), FL (50°)		Glass Lens	Hexcell louver eliminates glare.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination. 1-1/8" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 15°, 24°.

PICO OPTICAL LENS		GLASS LENS	LOUVER	FOCUS LENS	LINEAR SPREAD FILM
					
ORDERING CODE	(STATIC WHITE) OPL-PCO-NS-SW OPL-PCO-SP-SW OPL-PCO-NF-SW OPL-PCO-FL-SW	(WARM DIM) OPL-PCO-NS-WD OPL-PCO-SP-WD OPL-PCO-NF-WD OPL-PCO-FL-WD	GL10-VLS	L010-H	LF10-SF (SOFT FOCUS), LF10-MF (MEDIUM FOCUS), LF10-WF (WIDE FOCUS) LF10-LS
LENS SIZE	ø2" (5.1cm) Diameter				
DESCRIPTIONS	NS (18°), SP (24°), NF (40°), FL (50°)		Glass Oval Spread Lens	Hexcell louver eliminates glare.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination. 1-1/4" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 18°, 24°.

POP OPTICAL LENS		GLASS LENS	LOUVER	FOCUS LENS	LINEAR SPREAD FILM	SNOOT	
							
ORDERING CODE	(STATIC WHITE) OPL-POP-NS-SW OPL-POP-SP-SW OPL-POP-NF-SW OPL-POP-FL-SW	(WARM DIM) OPL-POP-NS-WD OPL-POP-SP-WD OPL-POP-NF-WD OPL-POP-FL-WD	GL16-LS	L016-H	LF16-SF (SOFT FOCUS), LF16-MF (MEDIUM FOCUS), LF16-WF (WIDE FOCUS) LF16-LS	POP-ST-BK POP-ST-MW	POP-STA-BK POP-STA-MW
LENS SIZE	ø2-1/2" (6.4cm) Diameter						
DESCRIPTIONS	NS (15°), SP (24°), NF (36°), FL (50°)		Glass Linear Spread Lens	Hexcell louver eliminates glare. 2" Dia.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination. 2" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 15°, 25°.	POP Snoot is designed to reduce spill and control glare. In Black or Matte White RAL 9003	Asymmetrical Snoot for Wall Wash with GL12-LS. Reduces spill and control glare. In Black or Matte White RAL 9003

*Cannot be used in Groove Track

MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 12.16.25


Accessories

PICO & POP ZOOM		SPREAD LENS	
			
ACCESSORIES FOR PICO & POP		(PICO) PCZ-VLS-BK PCZ-VLS-MW	(POP) POZ-VLS-BK POZ-VLS-MW
LENS SIZE	ø2-1/2" (6.4cm) Diameter	Oval Spread Lens. In Black or Matte White	

FRAME 1 & 2		LENS FILM COLOR FILTER		GOBO LENS	
					
ACCESSORIES FOR FRAME 1 & 2		(FRAME COLOR LENS)		(FRAME GOBO LENS)	
		LF-FRM1-BLU LF-FRM1-RED LF-FRM1-YLW	LF-FRM2-BLU LF-FRM2-RED LF-FRM2-YLW	(FRAME 1) GB-FRM1	(FRAME 2) GB-FRM2
LENS SIZE	ø2-1/2" (6.4cm) Diameter	Frame 1 & 2 Lens Film Color filter produces beams of light. Choose for any of Rosco Color films. Custom color filters available.		Frame 1 & 2 with a Gobo lens projects your logo or design onto any surface using full color options. For custom Gobo, send your drawings and ideas to our design team: design@PureEdgeLighting.com	

MIDAS PENDANT		LOUVER	FOCUS LENS	LINEAR SPREAD FILM
				
ACCESSORIES FOR MIDAS PENDANT		L016-H	LF16-SF (SOFT FOCUS), LF16-MF (MEDIUM FOCUS), LF16-WF (WIDE FOCUS)	LF16-LS
LENS SIZE	ø2-1/2" (6.4cm) Diameter	Hexcell louver eliminates glare. 2" Dia.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination.	2" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 15°, 25°.


2400K | Rf: 84.5 | Rg: 84.4
 Color Vector Graphic



■ Test ■ Reference

GRAPHIC SHIFTS %			
HUE BIN	Rf	CHROMA	HUE
1	92	-2.4%	1.5%
2	94.7	-2.1%	-0.0%
3	95.4	-1.9%	-0.1%
4	95.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.8	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-5.3%


2700K | Rf: 87.7 | Rg: 96.1
 Color Vector Graphic



■ Test ■ Reference

GRAPHIC SHIFTS %			
HUE BIN	Rf	CHROMA	HUE
1	88.0	-4.3%	2.6%
2	91.6	-2.4%	2.0%
3	93.7	-1.4%	1.9%
4	88.9	-5.6%	-3.1%
5	92.3	-5.5%	-0.5%
6	92.9	-3.5%	0.1%
7	84.5	-7.5%	4.6%
8	90.8	-3.0%	4.4%
9	84.5	-1.3%	6.3%
10	83.9	2.0%	9.8%
11	87.2	5.3%	7.1%
12	89.2	5.4%	-2.6%
13	88.7	0.3%	-7.3%
14	86.8	1.7%	-9.3%
15	87.6	-5.4%	-1.3%
16	83.6	-3.3%	-9.5%


3000K | Rf: 88.1 | Rg: 89.7
 Color Vector Graphic



■ Test ■ Reference

GRAPHIC SHIFTS %			
HUE BIN	Rf	CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.5%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.9%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%


3500K | Rf: 88.1 | Rg: 95.5
 Color Vector Graphic



■ Test ■ Reference

GRAPHIC SHIFTS %			
HUE BIN	Rf	CHROMA	HUE
1	90.8	-3.6%	0.3%
2	92.3	-2.8%	2.1%
3	89.7	-1.0%	4.3%
4	92.8	-1.4%	1.7%
5	91.8	-3.1%	1.3%
6	95.2	0.8%	-0.4%
7	92.9	-3.2%	0.2%
8	94.3	-2.5%	1.5%
9	90.4	-2.5%	5.2%
10	84.3	-1.4%	9.5%
11	83.1	3.5%	9.8%
12	88.2	4.8%	3.4%
13	94.0	2.7%	-2.0%
14	88.7	5.9%	-5.9%
15	88.7	0.7%	-5.9%
16	86.8	-0.7%	-6.7%

4000K | Rf: 87.8 | Rg: 86.8
 Color Vector Graphic



■ Test ■ Reference

GRAPHIC SHIFTS %			
HUE BIN	Rf	CHROMA	HUE
1	88.9	-2.4%	2.5%
2	93.3	-0.4%	0.8%
3	94.6	-1.0%	-0.6%
4	87.9	-4.9%	-3.6%
5	85.3	-9.4%	-2.6%
6	90.2	-5.0%	0.2%
7	85.3	-7.6%	4.6%
8	83.7	-4.1%	8.2%
9	79.5	-1.1%	13.6%
10	76.6	1.5%	12.1%
11	83.5	6.4%	7.8%
12	90.9	3.6%	-1.1%
13	86.3	1.7%	-6.3%
14	91.9	-0.4%	-2.2%
15	84.5	-0.9%	-5.5%
16	84.7	-1.1%	-4.4%