


MTS48 MicroTrack™ SUSPENSION


48VDC CLASS 2, SINGLE CIRCUIT, SUSPENSION TRACK SYSTEM

ASSEMBLED IN AMERICA

REV 07.13.26



Teeny Track Head
 702 lumens @3000K
 2 5/8" Long x 1 5/16" Dia



DESCRIPTION

MTS48 MicroTrack™ is a 48VDC suspension track system housed in the smallest of 5/8" deep x 7/16" wide track with a 1/4" slot profile which offers multiple fixture options in a clean, contemporary style. Suspended from the ceiling with cables. For a clean architectural aesthetic, a paintable Slot Cover is supplied with track channels for hiding the 12 AWG copper busbars and mounting screws. For custom quotes and layout assistance, send your drawings and ideas to our design team: design@PureEdgeLighting.com.

FEATURES

- Track Heads easily attach to the track and adjust, tilt, and rotate. Light Bars and Teeny track heads can be installed with one hand (no screwdriver necessary).
- Designed for use with 2 x 96W 48VDC Universal Remote Power Supplies up to 40' away with low voltage wire, before refeeding power
- Power Feeds offered with End and Center Feeds
- Straight Channels are available in 4' (44") and 8' (92") lengths, with the ability to be cut in the field
- Curved Channels are available in 12" and 20" radii
- Opaque plastic Slot Cover is included with channel concealing slot

LAMP

- Lumens: Up to 1776 lm at 3000K
- Lumens Per Watt: Up to 127 lm/w at 3000K
- CRI: Minimum 90 color rendering index
- CCT: 2400K, 2700K, 3000K, 3500K, 4000K (Warm Dim available for 3000K) color temperature with a great color consistency (within 3.0- step MacAdam ellipse)
- LED Lamp Life: Minimum 50,000hr with 85% of lumen maintenance in 25.0C ambient temperature, in compliance with IES LM-80 testing measurements

FINISH & MATERIAL

- Slot Cover: Black or Matte White PVC
- Extruded Aluminum Channel, conductors are a pair of #12 Gauge Copper Busbars

POWER SUPPLY AND DIMMING (SOLD SEPARATELY)

- 2 x 96W 48VDC, Remote Power
- [48VDC UNI Driver: Universal Dimming](#) (ELV, TRIAC, 0-10V) ELV & TRIAC [Smart Dimmer & Switch](#)
 - [2-in-1 Power Driver and Dimmer](#)

APPLICATIONS

Indoor use only. Ideal applications in residential, commercial, retail and hospitality environments.

WARRANTY / LABELS

5 year pro-rated warranty. Assembled in America
 ETL (Conforms to UL 1598 and CSA 22.2 #250.0), Class 2 Under 100 Watts, Title 24

MTS48 MicroTrack™ SUSPENSION

48VDC CLASS 2, SINGLE CIRCUIT, SUSPENSION TRACK SYSTEM


COMPONENTS

MICROTRACK™ 48VDC SUSPENSION CHANNEL



SLOT COVER PROVIDED



STRAIGHT CONNECTOR



STRAIGHT 1 CIRCUIT CHANNEL

Extruded Aluminum Channel with 12 AWG busbars to help eliminate voltage drop. For use with 48VDC Remote Power Supply, sold separately. Includes a Joiner Connector, End Caps, a Straight Connector, Suspension Cables, and paintable opaque Slot Covers to conceal the 12 AWG copper busbars and mounting screws.

System	Circuit	Length in Feet	Finish
MTS48	1C	8FT	BK
MTS48 MicroTrack Suspension 48VDC	1C Single Circuit	4FT 44" 8FT 92"	BK Black MW Matte White RAL 9003



CURVE 1 CIRCUIT CHANNEL

May be used with Flex Light. Comes with a Joiner, 12ft Suspension Cable, and a Straight Connector.





System	Circuit	Radius in Inches	Finish
MTS48	1C	12R	BK
MTS48 MicroTrack Suspension Curved 48VDC*	1C Single Circuit	12R* 12" Radius 20R 20" Radius 24R 24" Radius	BK Black MW Matte White RAL 9003

*Curved track is not compatible with a Slot Cover

*Track Heads do not fit into 12R 12" radius track

POWER FEEDS


The End Power Feed uses 48VDC 96-watt from Remote Power Supplies. The Center Feed powers the track using two 96-watt, 48VDC Remote Power Supplies. Power supplies must be connected to the same line voltage circuit (same phase).



System	Circuit & Type	Canopy	Canopy & Track Finish
MTS48	CP1	4RD	BK
MTS48 MicroTrack Suspension 48VDC	EP1 End Power Feed Single Circuit with 12" long track CP1 Center Power Feed Single Circuit with 12" long track CP2 Two Center Power Feed, 2 Directions with 12" long tracks CPT1 Center T Power Feed, 1 Direction power with 12" long tracks CPT2 Center T Power Feed, 2 Direction power with 12" long tracks CPT3 Center T Power Feed, 3 Direction power with 12" long tracks CPX1 Center X Power Feed, 1 Direction power with 12" long tracks CPX2 Center X Power Feed, 2 Direction power with 12" long tracks CPX3 Center X Power Feed, 3 Direction power with 12" long tracks CPX4 Center X Power Feed, 4 Direction power with 12" long tracks	4RD 4" Round Junction Box Cover with 12' Suspension Cable	BK Black MW Matte White RAL 9003

MTS48 MicroTrack™ SUSPENSION


48VDC CLASS 2, SINGLE CIRCUIT, SUSPENSION TRACK SYSTEM



SUSPENSION CABLES & MOUNTING CLIP

Suspension Mounting Clip suspends the track up to 12ft from the ceiling. One included for every 3ft of track.

System	Type	Finish
MTS48	MCL	CH
MTS48 MicroTrack Suspension 48VDC	MCL Mounting Clip with 12' Suspension Cable	CH Chrome




L-SHAPED CONNECTOR

L-Shaped Connector joins two sections of track 90° apart.


System	Circuit	Type	Finish
MTS48	1C	LC	BK
MTS48 MicroTrack Suspension 48VDC	1C Single Circuit	LC L-Connector Conductive LNC L-Connector Non-Conductive TNC T-Connector Non-Conductive XNC X-Connector Non-Conductive TC2 T-Connector Conductive 2 Ways XC2 X-Connector Conductive 2 Ways	BK Black MW Matte White RAL 9003

FLEX CONNECTOR

Flexible 48VDC Connector joins two sections of track at any angle.




System	Circuit	Type	Finish
MT48	1C	FXC	BK
MT48 MicroTrack 48VDC	1C Single Circuit	FXC Flex Connector, 5/8" length	BK Black MW Matte White RAL 9003



System	Circuit	Type	Finish
MT48	1C	FXCL	BK
MT48 MicroTrack 48VDC	1C Single Circuit	FXCL Flex Connector Long, 12" length	BK Black MW Matte White RAL 9003

ADDITIONAL PARTS



STRAIGHT CONNECTOR (INCLUDED WITH EACH TRACK)

Straight 48VDC Connector joins two track sections end to end and is concealed by the slot covers.

System	Circuit	Type	Finish
MT48	1C	SC	BK
MT48 MicroTrack 48VDC	1C Single Circuit	SC Straight Connector Conductive SNC Straight Connector Non-Conductive	BK Black MW Matte White RAL 9003

MTS48 MicroTrack™ SUSPENSION


48VDC CLASS 2, SINGLE CIRCUIT, SUSPENSION TRACK SYSTEM



SUSPENSION POWER FEED CONNECTOR (INCLUDED IN POWER CANOPY)


Includes 12ft power cable.

System	Circuit	Type	Finish
MTS48	1C	EP	BK
MTS48 MicroTrack Suspension 48VDC	1C Single Circuit	EP End Power Feed	BK Black MW Matte White RAL 9003



END CAP (INCLUDED WITH EACH TRACK)


System	Circuit	Type	Finish
MTS48	1C	CA	BK
MTS48 MicroTrack Suspension 48VDC	1C Single Circuit	CA End Cap	BK Black MW Matte White RAL 9003



OPAQUE SLOT COVER (INCLUDED WITH EACH TRACK)

Slot Covers included to conceal conductors and track slots.

System	Type	Length in Feet	Cover Color
MT48	SCO	8FT	BK
MT48 MicroTrack 48VDC	SCO Opaque Cover for Track Slot	8FT 8'	BK Black MW Matte White RAL 9003




REINFORCEMENT JOINER (INCLUDED WITH EACH TRACK)

Reinforcement joiner used for cutting and mechanically joining two tracks together, 1 PC.

System	Type
MT48	J1
MT48 MicroTrack 48VDC	J1 Reinforcement Joiner

WIRING DIAGRAM



MT48 MicroTrack™ TRACK HEADS


48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

PureEdge MT48 Track Heads are compatible with all MicroTrack™ Systems. May also be ordered with a [MonoPoint Canopy](#).

TEENY (BUT POWERFUL)

712 LM @ 3000K, 6 WATT, TITLE 24



*For lenses and lens accessories, refer to the accessories page


System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	TEE	6W	NF	30K	BK
MT48 MicroTrack 48VDC	TEE Teeny Track Head	6W 6 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 36° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D* 3000K dims to 1800K 35K 3500K Neutral White 40K 4000K Cool White *Uses 5 Watts and is not compatible with NS (15°) lens	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	TEENY (WITH NARROW SPOT 15° LENS)					
COLOR TEMPERATURE	24K	27K	30K	30D*	35K	40K
TOTAL LUMENS	676	684	712	373	817	862
WATTS	6	6	6	5	6	6
LUMENS PER WATT (lm/w)	113	114	119	75	136	144
CRI	95+	95+	95+	95+	95+	95+

*30D - Warm Dim (5 Watts)

SLIM

671 LM @ 3000K, 6 WATT, TITLE 24



*For lenses and lens accessories, refer to the accessories page

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	SLM	6W	NF	30K	BK
MT48 MicroTrack 48VDC	SLM Slim Track Head	6W 6 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 36° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D* 3000K dims to 1800K 35K 3500K Neutral White 40K 4000K Cool White *Not compatible with the NS (15°) lens	BK Black Powder Coat MW Matte White Powder Coat RAL 9003 SB Satin Brass SN Satin Nickel

	SLIM (WITH NARROW SPOT 15° LENS)					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	637	644	671	505	770	812
WATTS	6	6	6	6	6	6
LUMENS PER WATT (lm/w)	106	107	112	84	128	135
CRI	95+	95+	95+	95+	95+	95+

MT48 MicroTrack™ TRACK HEADS


48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

PureEdge MT48 Track Heads are compatible with all MicroTrack™ Systems.

PICO & PICO ZOOM

965 LM @ 3000K, 10 WATT, TITLE 24 (PICO) / 750 LM @ 3000K, 10 WATTS, TITLE 24 (PICO ZOOM)



*For lenses and lens accessories, refer to the accessories page


System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	PCO	10W	FL	30K	BK
MT48 MicroTrack 48VDC	PCO Pico Track Head	10W 10 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 36° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D 3000K Warm Dim 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003, Matte White stem SB* Satin Brass SN* Satin Nickel
	PCZ Pico Zoom Track Head, Beam Spread NSFL 15°-50°		NSFL Narrow Spot 15° to Flood 50° (Pico Zoom Only)		

*Not available with Pico Zoom

	PICO (WITH SPOT 24° LENS)						PICO ZOOM (WITH 50° BEAM SPREAD)					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	917	926	965	853	1107	1168	713	720	750	578	860	908
WATTS	10	10	10	10	10	10	11	11	11	11	11	11
LUMENS PER WATT (lm/w)	92	93	97	85	111	117	65	65	68	53	78	83
CRI	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+

POP & POP ZOOM

1865 LM @ 3000K, 15 WATT, TITLE 24 (POP) / 1062 LM @ 3000K, 15 WATT, TITLE 24 (POP ZOOM)



*For lenses and lens accessories, refer to the accessories page

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	POP	15W	NS	30K	BK
MT48 MicroTrack 48VDC	POP Pop Track Head	15W 15 Watts	NS Narrow Spot 15° SP Spot 24° NF Narrow Flood 35° FL Flood 50°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D* 3000K Warm Dim 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003, Matte White stem SB* Satin Brass SN* Satin Nickel
	POZ Pop Zoom Track Head, Beam Spread NSFL 15°-50°		NSFL Narrow Spot 15° to Flood 50° (Pop Zoom Only)		

*Not compatible with FL (50°) lens

*Not available with Pop Zoom

	POP (WITH FLOOD 50° LENS)						POP ZOOM (WITH 50° BEAM SPREAD)					
COLOR TEMPERATURE	24K	27K	30K	30D*	35K	40K	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	1772	1790	1865	1051	2140	2257	1009	1020	1062	878	1218	1285
WATTS	15	15	15	12	15	15	15	15	15	15	15	15
LUMENS PER WATT (lm/w)	118	119	124	88	143	150	67	68	71	55	81	86
CRI	95+	95+	95+	97+	95+	95+	98+	98+	98+	98+	98+	98+

*30D - Warm Dim (12 Watts), Narrow Flood 35° Lens

MT48 MicroTrack™ TRACK HEADS


48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

PureEdge MT48 Track Heads are compatible with all MicroTrack™ Systems.

FRAME 1 & 2

570 LM @ 3000K, 10 WATT 48VDC CLASS 2, TITLE 24 (FRAME 1) / 571 LM @ 3000K, 15 WATT 48V CLASS 2, TITLE 24 (FRAME 2)



*For color filters and Gobo lenses, refer to the accessories page

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	FRM2	15W	SPNF	30K	BK
MT48 MicroTrack 48VDC	FRM1 Frame 1 Track Head FRM2 Frame 2 Track Head	10W 10 Watts 15W 15 Watts	SPNF Spot 20° to Narrow Flood 30°	24K 2400K Amber White 27K 2700K Very Warm White 30K 3000K Warm White 30D 3000K Warm Dim 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	FRAME 1 (WITH 30° BEAM SPREAD)						FRAME 2 (WITH 30° BEAM SPREAD)					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	542	547	570	439	654	690	542	548	571	440	655	691
WATTS	10	10	10	11	10	10	15	15	15	14	15	15
LUMENS PER WATT (lm/w)	54	55	57	40	65	69	36	37	38	31	44	46
CRI	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+	97+

MINI LIGHT BAR

134 LM @ 3000K, 5 WATT, 12" LENGTH



5W12: 11-7/16" (29cm)
 9W24: 22-13/16" (58cm)
 14W36: 34-5/8" (87cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	MLB	5W12	30K	BK
MT48 MicroTrack 48VDC	MLB Mini Light Bar	5W12 5 Watts, 12" Length 9W24 9 Watts, 24" Length 14W36 14 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK* Black Powder Coat *Mini Light Bar is tucked into track, only lens is visible

	MINI LIGHT BAR											
WATTAGE	6W				11W				17W			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	129	134	154	162	273	284	326	344	427	445	511	538
LUMENS PER WATT (lm/w)	26	27	31	32	30	32	36	38	31	32	36	38
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+



MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

LIGHT BAR

400 LM @ 3000K, 6 WATT, 12" LENGTH, TITLE 24





6W12: 11-11/16" (29.7cm)
11W24: 23-1/4" (59cm)
17W36: 34-13/16" (88.4cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	LB	6W12	30K	BK
MT48 MicroTrack 48VDC	LB Light Bar	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR WITH 140° LENS											
	6W - 12" (11-11/16")				11W - 24" (23-1/4")				17W - 36" (34-13/16")			
WATTAGE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	384	400	459	484	768	800	918	968	1152	1200	1377	1452
LUMENS PER WATT (lm/w)	64	67	76	81	128	133	153	161	192	200	229	242
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR LOUVER

129 LM @ 3000K, 6 WATT, 12" LENGTH, TITLE 24



6W12: 11-11/16" (29.7cm)
11W24: 23-1/4" (59cm)
17W36: 34-13/16" (88.4cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	LBL	6W12	30K	BK
MT48 MicroTrack 48VDC	LBL Light Bar Louver	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR LOUVER & 120° LENS											
	6W - 12" (11-11/16")				11W - 24" (23-1/4")				17W - 36" (34-13/16")			
WATTAGE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	124	129	148	156	248	258	296	312	372	387	444	468
LUMENS PER WATT (lm/w)	21	22	25	26	41	43	49	52	62	65	74	78
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+



MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

LIGHT BAR HEXCELL LOUVER

168 LM @ 3000K, 6 WATT, 12" LENGTH, TITLE 24





6W12: 11-11/16" (29.7cm)
11W24: 23-1/4" (59cm)
17W36: 34-13/16" (88.4cm)

System	Fixture	Wattage	Color Temperature	Finish
MT48	LBH	6W12	30K	BK
MT48 MicroTrack 48VDC	LBH Light Bar Hexcell Louver	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR WITH HEXCELL LOUVER & 120° LENS											
WATTAGE	6W - 12" (11-11/16")				11W - 24" (23-1/4")				17W - 36" (34-13/16")			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	161	168	193	203	323	336	385	407	484	504	578	610
LUMENS PER WATT (lm/w)	27	28	32	34	54	56	64	68	81	84	96	102
CRI	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR ACCENT

548 LM @ 3000K, 9 WATT, 6" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BA	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BA Bar Accent	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle BC Black Fixture Crystal Baffle BG Black Fixture Gold Baffle MB Matte White Fixture Black Baffle MC Matte White Fixture Crystal Baffle MG Matte White Fixture Gold Baffle

	LIGHT BAR ACCENT WITH 30° LENS							
WATTAGE	9W				16W			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	526	548	629	663	1005	1047	1201	1267
LUMENS PER WATT (lm/w)	88	91	105	111	168	175	200	211
CRI	90+	90+	90+	90+	90+	90+	90+	90+



MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

LIGHT BAR ACCENT HEXCELL LOUVER

270 LM @ 3000K, 9 WATT, 16" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BAH	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BAH Bar Accent Hexcell Louver	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle BC Black Fixture Crystal Baffle BG Black Fixture Gold Baffle MB Matte White Fixture Black Baffle MC Matte White Fixture Crystal Baffle MG Matte White Fixture Gold Baffle


	LIGHT BAR ACCENT WITH HEXCELL LOUVER & 30° LENS							
WATTAGE	9W				16W			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	259	270	310	327	493	514	590	622
LUMENS PER WATT (lm/w)	43	45	52	54	82	86	98	104
CRI	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR ACCENT TILT

548 LM @ 3000K, 9 WATT, 6" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BAT	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BAT Bar Accent Tilt	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle BC Black Fixture Crystal Baffle BG Black Fixture Gold Baffle MB Matte White Fixture Black Baffle MC Matte White Fixture Crystal Baffle MG Matte White Fixture Gold Baffle



	LIGHT BAR ACCENT ROTATABLE WITH 30° LENS							
WATTAGE	9W				16W			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	526	548	629	663	1005	1047	1201	1267
LUMENS PER WATT (lm/w)	88	91	105	111	168	175	200	211
CRI	90+	90+	90+	90+	90+	90+	90+	90+




MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

LIGHT BAR ACCENT TILT HEXCELL LOUVER

270 LM @ 3000K, 9 WATT, 16" LENGTH, TITLE 24



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	BATH	9W6	NF	30K	BB
MT48 MicroTrack 48VDC	BATH Bar Accent Tilt Hexcell Louver	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood 30°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BB Black Fixture Black Baffle BC Black Fixture Crystal Baffle BG Black Fixture Gold Baffle MB Matte White Fixture Black Baffle MC Matte White Fixture Crystal Baffle MG Matte White Fixture Gold Baffle





LIGHT BAR ACCENT ROTATABLE WITH HEXCELL LOUVER & 30° LENS

	9W				16W			
WATTAGE								
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	259	270	310	327	493	514	590	622
LUMENS PER WATT (lm/w)	43	45	52	54	82	86	98	104
CRI	90+	90+	90+	90+	90+	90+	90+	90+

LIGHT BAR WALL WASH

548 LM @ 3000K, 9 WATT, 16" LENGTH, TITLE 24




System	Fixture	Wattage	Color Temperature	Finish
MT48	BWW	9W6	30K	BK
MT48 MicroTrack 48VDC	BWW Bar Wall Wash	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

LIGHT BAR WALL WASH

	9W				16W			
WATTAGE								
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K
TOTAL LUMENS	526	548	629	663	1005	1047	1201	1267
LUMENS PER WATT (lm/w)	88	91	105	111	168	175	200	211
CRI	90+	90+	90+	90+	90+	90+	90+	90+

MICROTRACK™ FLEX LIGHT

70 LM@ 3000K, 3 WATT



System

Fixture

Wattage

Length

Color Temperature

MT48

FN2

3W

16FT

30K

MT48 MicroTrack 48VDC

FN2 Flex Light

3W 3 Watts per foot

1-16FT 1-16 Feet

27K 2700K Very Warm White

30K 3000K Warm White

35K 3500K Neutral White

40K 4000K Cool White

	FLEX LIGHT			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	95	99	114	85
WATTS	3	3	3	3
LUMENS PER WATT (lm/w)	32	33	38	28
CRI	90+	90+	90+	90+


MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

TOTEM PENDANT

596 LM @ 3000K, 7 WATT




System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	TTP	7W	SP	30K	BK
MT48 MicroTrack 48VDC	TTP Totem Pendant	7W 7 Watts	SP Spot 20° NF Narrow Flood 24° FL Flood 36° WF Wide Flood 56°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White

	TOTEM PENDANT			
WATTAGE	7W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	572	596	685	721
LUMENS PER WATT (lm/w)	82	85	98	103
CRI	90+	90+	90+	90+

TOWER PENDANT

707 LM @ 3000K, 7 WATT



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	TOP	7W	SP	30K	BK
MT48 MicroTrack 48VDC	TOP Tower Pendant	7W 7 Watts	SP Spot 20° NF Narrow Flood 24° FL Flood 36° WF Wide Flood 47°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White

	TOTEM PENDANT			
WATTAGE	7W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	679	707	813	855
LUMENS PER WATT (lm/w)	97	101	116	122
CRI	90+	90+	90+	90+


MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

MIDAS PENDANT

1776 LM @ 3000K, 15 WATT




System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	MIP	15W	SP	30K	BSB
MT48 MicroTrack 48VDC	MIP Midas Pendant	15W 15 Watts	SP Spot 20° NF Narrow Flood 25° FL Flood 38° WF Wide Flood 50°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White BSB Black and Satin Brass

	MIDAS PENDANT			
WATTAGE	15W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	1705	1776	2042	2149
LUMENS PER WATT (lm/w)	114	118	136	143
CRI	90+	90+	90+	90+

*For lens accessories, refer to the accessories page

DROP PENDANT

1755 LM @ 3000K, 15 WATT



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
MT48	DP	15W	SP	30K	BK
MT48 MicroTrack 48VDC	DP Drop Pendant	15W 15 Watts	SP Spot 20° NF Narrow Flood 25° FL Flood 38° WF Wide Flood 50°	27K 2700K Very Warm White 30K 3000K Warm White 35K 3500K Neutral White 40K 4000K Cool White	BK Black MW Matte White

	DROP PENDANT			
WATTAGE	15W			
COLOR TEMPERATURE	27K	30K	35K	40K
TOTAL LUMENS	1685	1755	2018	2124
LUMENS PER WATT (lm/w)	112	117	135	142
CRI	90+	90+	90+	90+


MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

Accessories

TEENY / SLIM OPTICAL LENS		GLASS LENS	LOUVER	FOCUS LENS	LINEAR SPREAD FILM
					
ORDERING CODE	(STATIC WHITE) OPL-SLM-NS-SW OPL-SLM-SP-SW OPL-SLM-NF-SW OPL-SLM-FL-SW	GL9-AS (ASYMMETRIC) GL9-SF (SOFT DIFFUSER)	L09-H	LF09-SF (SOFT FOCUS), LF09-MF (MEDIUM FOCUS), LF09-WF (WIDE FOCUS)	LF09-LS
LENS SIZE	ø1-5/16" (3.3cm) Diameter				
DESCRIPTIONS	NS (15°), SP (24°), NF (36°), FL (50°)	Glass Lens	Hexcell louver eliminates glare.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination.	1-1/8" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 15°, 24°.

PICO OPTICAL LENS			GLASS LENS	LOUVER	FOCUS LENS	LINEAR SPREAD FILM
						
ORDERING CODE	(STATIC WHITE) OPL-PCO-NS-SW OPL-PCO-SP-SW OPL-PCO-NF-SW OPL-PCO-FL-SW	(WARM DIM) OPL-PCO-NS-WD OPL-PCO-SP-WD OPL-PCO-NF-WD OPL-PCO-FL-WD	GL10-VLS	L010-H	LF10-SF (SOFT FOCUS), LF10-MF (MEDIUM FOCUS), LF10-WF (WIDE FOCUS)	LF10-LS
LENS SIZE	ø2" (5.1cm) Diameter		Glass Oval Spread Lens	Hexcell louver eliminates glare.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination.	1-1/4" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 18°, 24°.
DESCRIPTIONS	NS (18°), SP (24°), NF (40°), FL (50°)					

POP OPTICAL LENS			GLASS LENS	LOUVER	FOCUS LENS	LINEAR SPREAD FILM	SNOOT	
								
ORDERING CODE	(STATIC WHITE) OPL-POP-NS-SW OPL-POP-SP-SW OPL-POP-NF-SW OPL-POP-FL-SW	(WARM DIM) OPL-POP-NS-WD OPL-POP-SP-WD OPL-POP-NF-WD OPL-POP-FL-WD	GL16-LS	L016-H	LF16-SF (SOFT FOCUS), LF16-MF (MEDIUM FOCUS), LF16-WF (WIDE FOCUS)	LF16-LS	POP-ST-BK POP-ST-MW	POP-STA-BK POP-STA-MW
LENS SIZE	ø2-1/2" (6.4cm) Diameter		Glass Linear Spread Lens	Hexcell louver eliminates glare. 2" Dia.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination.	2" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 15°, 25°.	POP Snoot is designed to reduce spill and control glare. In Black or Matte White RAL 9003	Asymmetrical Snoot for Wall Wash with GL12-LS. Reduces spill and control glare. In Black or Matte White RAL 9003
DESCRIPTIONS	NS (15°), SP (24°), NF (36°), FL (50°)							

*Cannot be used in Groove Track

MT48 MicroTrack™ TRACK HEADS

48VDC WITH INTEGRATED LED, ETL LISTED

REV 07.13.26

Accessories


PICO & POP ZOOM		SPREAD LENS	
			
ACCESSORIES FOR PICO & POP		(PICO) PCZ-VLS-BK PCZ-VLS-MW	(POP) POZ-VLS-BK POZ-VLS-MW
LENS SIZE	ø2-1/2" (6.4cm) Diameter	Oval Spread Lens. In Black or Matte White	

FRAME 1 & 2		LENS FILM COLOR FILTER		GOBO LENS	
					
ACCESSORIES FOR FRAME 1 & 2		(FRAME COLOR LENS)		(FRAME GOBO LENS)	
		LF-FRM1-BLU LF-FRM1-RED LF-FRM1-YLW	LF-FRM2-BLU LF-FRM2-RED LF-FRM2-YLW	(FRAME 1) GB-FRM1	(FRAME 2) GB-FRM2
LENS SIZE	ø2-1/2" (6.4cm) Diameter	Frame 1 & 2 Lens Film Color filter produces beams of light. Choose for any of Rosco Color films. Custom color filters available.		Frame 1 & 2 with a Gobo lens projects your logo or design onto any surface using full color options. For custom Gobo, send your drawings and ideas to our design team: design@PureEdgeLighting.com	

MIDAS PENDANT		LOUVER	FOCUS LENS	LINEAR SPREAD FILM
				
ACCESSORIES FOR MIDAS PENDANT		L016-H	LF16-SF (SOFT FOCUS), LF16-MF (MEDIUM FOCUS), LF16-WF (WIDE FOCUS)	LF16-LS
LENS SIZE	ø2-1/2" (6.4cm) Diameter	Hexcell louver eliminates glare. 2" Dia.	Soft focus lens is included with every track head. Diffuses the beam, providing uniform illumination.	2" Dia. Linear Spread Film. Linear spread film: directs the light into an elongated beam. Typical applications using 10°, 15°, 25°.



PDW-100W-DIM-48VDC-WH



DESCRIPTION

Power Dim 2-in-1 is a dimmer with an integrated LED driver that converts 120VAC to low-voltage 48VDC (up to 96W). Designed for installation in a standard single-gang electrical box, it eliminates the need for separate remote drivers, simplifying installation to provide an option that is as cost-effective as it is time efficient.

PureEdge Lighting's Power Driver combines an ELV dimmer and driver in a single, wall-mounted unit.

Kit includes driver/dimmer, faceplate, and mounting hardware.

The integrated design delivers smooth, flicker-free dimming and avoids driver/switch compatibility issues. Features soft start and built-in short-circuit, overload, and thermal protection. Indoor use only.

For custom quotes and layout assistance, send drawings to design@PureEdgeLighting.com.

INTEGRATED DESIGN

- Combines LED driver and dimmer into a single device
- Soft start
- Short circuit protection
- Overload protection
- Thermal overload protection
- Utilizes 6" wire leads

APPLICATIONS

Indoor

MOUNTING

Fits into a standard single-gang wall box, standard hardwire connection

POWER INPUT

- 120VAC
- Power Factor @ full load: >0.99
- THD (Typ.) @ full load: ≤10%
- Efficiency @ full load: 91.0%
- AC Current (Max.): 0.9A

POWER OUTPUT

- Class 2; 48 volts DC
- 96 watts maximum
- Voltage Tolerance: ±0.5V
- Rated current: 4A

DIMENSIONS

4.13" x 2.12" x 1.99"

COMPLIANCE

Class 2, UL, RoHS


Product	Wattage	Control Type	Voltage	Finish
PDW	100W	DIM	48VDC	WH
PDW Power Wall Dimmer	100W 100 Watts	DIM DIM Static White	48VDC 48 Volt DC	WH White

TM30 DATA

48VDC WITH INTEGRATED LED

2400K | Rf: 84.5 | Rg: 94.4

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92	-2.4%	1.5%
2	94.7	-2.1%	-0.0%
3	95.4	-1.9%	-0.1%
4	88.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.6	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-6.3%

2700K | Rf: 87.7 | Rg: 96.1

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.0	-4.3%	2.6%
2	91.6	-2.4%	2.0%
3	93.7	-1.4%	1.9%
4	88.9	-5.6%	-3.1%
5	92.3	-5.5%	-0.5%
6	92.9	-3.5%	0.1%
7	84.5	-7.5%	4.6%
8	90.8	-3.0%	4.4%
9	84.5	-1.3%	8.3%
10	83.9	2.0%	9.8%
11	87.2	5.3%	7.1%
12	89.2	5.4%	-2.6%
13	88.7	0.3%	-7.8%
14	86.8	1.7%	-9.3%
15	87.6	-5.4%	-1.3%
16	83.6	-3.3%	-9.5%

3000K | Rf: 88.1 | Rg: 99.7

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.8%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.8%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%

3500K | Rf: 86.1 | Rg: 95.5

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.8	-3.8%	0.3%
2	92.3	-2.8%	2.1%
3	89.7	-1.0%	4.3%
4	92.6	-1.4%	1.7%
5	91.8	-3.1%	1.3%
6	96.2	0.8%	-0.4%
7	92.9	-3.2%	0.2%
8	94.3	-2.5%	1.5%
9	90.4	-2.5%	5.2%
10	84.3	-1.4%	9.5%
11	83.1	3.5%	9.8%
12	88.2	4.8%	3.4%
13	94.0	2.7%	-2.0%
14	88.7	5.9%	-5.8%
15	88.7	0.7%	-5.9%
16	86.8	-0.7%	-6.7%

4000K | Rf: 87.6 | Rg: 96.8

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.9	-2.4%	2.5%
2	93.3	-0.4%	0.8%
3	94.8	-1.0%	-0.6%
4	87.9	-4.9%	-3.6%
5	85.3	-9.4%	-2.6%
6	90.2	-6.0%	0.2%
7	85.3	-7.6%	4.6%
8	83.7	-4.1%	8.2%
9	79.5	-1.1%	13.8%
10	78.6	1.5%	12.1%
11	83.5	6.4%	7.8%
12	90.9	3.6%	-1.1%
13	88.3	1.7%	-6.3%
14	91.9	-0.4%	-2.2%
15	84.5	-0.9%	-5.5%
16	84.7	-1.1%	-4.4%