



# MTS48 MICRO TRACK

## 48VDC CLASS 2, SURFACE TRACK SYSTEM

ASSEMBLED IN AMERICA

REV 05.02.25



### DESCRIPTION

MTS48 Micro Track is a 48volt surface mounted system housed in the smallest of profiles which offers multiple fixture options in a clean, contemporary style. Mounted directly to the ceiling's drywall, the Micro Track patented design is precision engineered to blend seamlessly on drywall surfaces, eliminating the need for joist modification, and providing unmatched flexibility to make turns and curves along the ceiling. For a clean architectural aesthetic, a paintable slot cover is supplied with track channels, allowing the track luminaires to blend with the track once installed. For custom quotes and layout assistance, send your drawings and ideas to our design team: [design@PureEdgeLighting.com](mailto:design@PureEdgeLighting.com).

### FEATURES

- Track Heads easily attach to the track and adjust, tilt, and rotate using a small screw driver to lock into place
- Designed for use with 48VDC Universal Remote Power Supplies up to 40' away
- Track Heads are available in multiple color temperatures including Warm Dim (30D)
- Track Head Lumen Output up to 1776 Lumens at 30K with multiple fixed and adjustable beam spread options
- Designer-grade Color Rendering 93+ CRI
- Power Feeds offered with end and center feeds and inside corner options, with up to two-96W remote power supplies with center feed
- Straight channels are available in 4' (44") and 8' (92") lengths, with the ability to be cut in the field
- Curved Channels are available in 12" and 20" Radii
- Flexible and L-Connector options
- Opaque Plastic Slot Cover is included with channel concealing slot, and may be painted to match the fixture

### FINISH & MATERIAL

- Slot Cover: Black or Matte White Powder RAL 9003 Powder Coat
- Extruded Aluminum Channel, conductors are a pair of #12 Gauge Copper Busbar

### POWER SUPPLY AND DIMMING (SOLD SEPARATELY)

- 48VDC, Remote Power
- [48V UNI Driver: Universal Dimming](#) (ELV, TRIAC, 0-10V)  
ELV & TRIAC [Smart Dimmer & Switch](#)

### APPLICATIONS

Indoor use only. Ideal applications in residential, commercial, retail and hospitality environments.

### WARRANTY / LABELS

5 year pro-rated warranty. Assembled in America  
ETL (Conforms to UL 1598 and CSA 22.2 #250.0), Class 2 Under 100 Watts



TEENY TRACK HEAD  
702 LUMENS @3000K



PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

**COMPONENTS**



SLOT COVER PROVIDED

MICRO SURFACE 48VDC TRACK



**CHANNELS**

Curved and straight track for a variety of configurations and designs using Extruded Aluminum Channel with 12 gauge buss bar to help eliminate voltage drop. For use with 48VDC Remote Power Supply, sold separately. Includes End Caps, Straight Connector, and paintable, opaque slot covers to conceal conductive connectors and track slots blending seamlessly with the fixture.

System	Circuit	Length in Feet	Finish
<b>MTS48</b>	<b>1C</b>	<b>8FT</b>	<b>BK</b>
MTS48 Micro Track Surface 48V	1C Single Circuit	4FT 44" 8FT 92"	BK Black MW Matte White RAL 9003

System	Circuit	Radius in Inches	Finish
<b>MTSC48</b>	<b>1C</b>	<b>12R</b>	<b>BK</b>
MTSC48 Micro Track 48V Surface Curved	1C Single Circuit	12R 12" Radius 20R 20" Radius	BK Black MW Matte White RAL 9003


**OPAQUE SLOT COVER (INCLUDED WITH MTS48 TRACK ABOVE)**  
 Paintable 1/2" Opaque Slot Covers.



System	Type	Length in Feet	Cover Color
<b>MT48</b>	<b>SCO</b>	<b>8FT</b>	<b>BK</b>
MT48 Micro Track 48V	SCO Opaque Cover for Track Slot	8FT 8'	BK Black WH White (Paintable)

**END POWER FEED**


End Power Feed with junction box powers the track with 48VDC Remote power supplies up to 96 watts. May be used on cement ceiling with only 1/2" dry wall (junction box not used).



System	Circuit & Type	Canopy	Finish
<b>MTS48</b>	<b>EP1</b>	<b>4SQ</b>	<b>BK</b>
MTS48 Micro Track Surface 48V	EP1 End Power Feed Single Circuit	4SQ 4" Square Junction Box Cover 1RE 1" Rectangle Junction Box Cover	BK Black MW Matte White RAL 9003

**CENTER POWER FEED**

Center Power Feed with junction box powers the track with up to two 96 watt, 48VDC remote power supplies.



System	Circuit & Type	Canopy	Finish
<b>MTS48</b>	<b>CP1</b>	<b>4SQ</b>	<b>BK</b>
MTS48 Micro Track Surface 48V	CP1 Center Power Feed Single Circuit	4SQ 4" Square Junction Box Cover 1RE 1" Rectangle Junction Box Cover	BK Black MW Matte White RAL 9003

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

**ACCESSORIES**


**L-SHAPED CONNECTOR**

L-Shaped Connector joins two sections of track 90° apart.




System	Circuit	Type
<b>MTS48</b>	<b>1C</b>	<b>LC</b>
<b>MTS48</b> Micro Track Surface 48V	<b>1C</b> Single Circuit	<b>LC</b> L-Connector Conductive

**FLEX CONNECTOR (INCLUDED WITH EACH L CONNECTOR)**



System	Circuit	Type
<b>MT48</b>	<b>1C</b>	<b>FXC</b>
<b>MT48</b> Micro Track 48V	<b>1C</b> Single Circuit	<b>FXC</b> Flex Connector



System	Circuit	Type
<b>MT48</b>	<b>1C</b>	<b>FXCL</b>
<b>MT48</b> Micro Track 48V	<b>1C</b> Single Circuit	<b>FXCL</b> Flex Connector Long 12"


PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

**ADDITIONAL PARTS**

**VERTICAL CONNECTOR**




System	Circuit	Type
<b>MTS48</b>	<b>1C</b>	<b>VC</b>
<b>MTS48</b> Micro Track Surface 48V	<b>1C</b> Single Circuit	<b>VC</b> Vertical Connector Conductive <b>VNC</b> Vertical Connector Non-Conductive



**STRAIGHT CONNECTOR (INCLUDED WITH EACH TRACK)**

Miniature Straight Connector joins two track sections end to end and is concealed by the slot covers. Included with each section of track.


System	Circuit	Type
<b>MT48</b>	<b>1C</b>	<b>SC</b>
<b>MT48</b> Micro Track 48V	<b>1C</b> Single Circuit	<b>SC</b> Straight Connector Conductive



**END POWER FEED (INCLUDED WITH POWER TRACK)**

End Power feed up to 96 watts at 48 Volts. Can be used to replace lost part.

System	Circuit	Type
<b>MT48</b>	<b>1C</b>	<b>EP</b>
<b>MT48</b> Micro Track 48V	<b>1C</b> Single Circuit	<b>EP</b> End Power Feed



**END CAP (INCLUDED WITH EACH TRACK)**

System	Circuit	Type	Finish
<b>MT48</b>	<b>1C</b>	<b>CA</b>	<b>BK</b>
<b>MT48</b> Micro Track 48V	<b>1C</b> Single Circuit	<b>CA</b> End Cap	<b>BK</b> Black <b>MW</b> Matte White RAL 9003

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

# MTS48 MICRO TRACK

## 48VDC CLASS 2, SURFACE TRACK SYSTEM

REV 05.02.25

PureEdge MT48 Track Heads are compatible with Micro Track (MT48).

**TEENY**  
702 LM @ 3000K, 6 WATT

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>TEE</b>	<b>6W</b>	<b>NF</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	TEE Teeny Trackhead	6W 6 Watts	<b>NS</b> Narrow Spot 15° <b>SP</b> Spot 24° <b>NF</b> Narrow Flood 36° <b>FL</b> Flood 50°	<b>24K</b> 2400K Amber White <b>27K</b> 2700K Very Warm White <b>30K</b> 3000K Warm White <b>30D</b> 3000K Warm Dim <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003

	TEENY					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	667	674	702	414	805	849
WATTS	6	6	6	6	6	6
LUMENS PER WATT (lm/w)	111	112	117	69	134	142
CRI	93+	93+	93+	93+	93+	93+

Accessories:



**SLIM**  
617 LM @ 3000K, 6 WATT

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>SLM</b>	<b>6W</b>	<b>NF</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	SLM Slim Trackhead	6W 6 Watts	<b>NS</b> Narrow Spot 15° <b>SP</b> Spot 24° <b>NF</b> Narrow Flood 36° <b>FL</b> Flood 50°	<b>24K</b> 2400K Amber White <b>27K</b> 2700K Very Warm White <b>30K</b> 3000K Warm White <b>30D</b> 3000K Warm Dim <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003 <b>SB</b> Satin Brass <b>SN</b> Satin Nickel

	SLIM					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	586	592	617	414	708	747
WATTS	6	6	6	6	6	6
LUMENS PER WATT (lm/w)	98	99	103	69	118	124
CRI	93+	93+	93+	93+	93+	93+

Accessories:




PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

# MTS48 MICRO TRACK

## 48VDC CLASS 2, SURFACE TRACK SYSTEM


PureEdge MT48 Track Heads are compatible with Micro Track (MT48).



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>PCO</b>	<b>10W</b>	<b>FL</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	PCO Pico Trackhead	10W 10 Watts	<b>NS</b> Narrow Spot 18° <b>SP</b> Spot 24° <b>NF</b> Narrow Flood 36° <b>FL</b> Flood 50°	<b>24K</b> 2400K Amber White <b>27K</b> 2700K Very Warm White <b>30K</b> 3000K Warm White <b>30D</b> 3000K Warm Dim <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003 <b>SB</b> Satin Brass <b>SN</b> Satin Nickel

	PICO					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	995	1005	1047	690	1201	1267
WATTS	10	10	10	10	10	10
LUMENS PER WATT (lm/w)	99	101	105	69	120	127
CRI	93+	93+	93+	93+	93+	93+

Accessories:



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>POP</b>	<b>14W</b>	<b>NS</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	POP Pop Trackhead	14W 14 Watts	<b>NS</b> Narrow Spot 15° <b>SP</b> Spot 24° <b>NF</b> Narrow Flood 36° <b>FL</b> Flood 50°	<b>24K</b> 2400K Amber White <b>27K</b> 2700K Very Warm White <b>30K</b> 3000K Warm White <b>30D</b> 3000K Warm Dim <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003 <b>SB</b> Satin Brass <b>SN</b> Satin Nickel

	POP					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	1687	1705	1776	971	2038	2149
WATTS	14	14	14	14	14	14
LUMENS PER WATT (lm/w)	121	122	127	69	146	153
CRI	93+	93+	93+	93+	93+	93+

Accessories:



PROJECT	FIXTURE TYPE	DATE
---------	--------------	------



**MTS48 MICRO TRACK**  
48VDC CLASS 2, SURFACE TRACK SYSTEM

REV.05.02.25

PureEdge MT48 Track Heads are compatible with Micro Track (MT48).

**POP ZOOM 15 DEGREES TO 50 DEGREES**  
**905 LM @ 3000K, 14 WATT**

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>POZ</b>	<b>14W</b>	<b>NSFL</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	POZ Pop Zoom Trackhead	14W 14 Watts	NSFL Narrow Spot 15° to Flood 50°	<b>24K</b> 2400K Amber White <b>27K</b> 2700K Very Warm White <b>30K</b> 3000K Warm White <b>30D</b> 3000K Warm Dim <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003 <b>SB</b> Satin Brass <b>SN</b> Satin Nickel

	POP ZOOM
Beam Angle	15°
COLOR TEMPERATURE	30K
TOTAL LUMENS	905
WATTS	14
LUMENS PER WATT (lm/w)	46
CRI	93

Accessories:




POZ-VLS  
Oval Spread Lens

**FRAME 2**  
**905 LM @ 3000K, 14 WATT 48V CLASS 2**

System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>FR2</b>	<b>14W</b>	<b>SPNF</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	FR2 Frame 2 Trackhead	14W 14 Watts	SPNF Spot 20° to Narrow Flood 30°	<b>24K</b> 2400K Amber White <b>27K</b> 2700K Very Warm White <b>30K</b> 3000K Warm White <b>30D</b> 3000K Warm Dim <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003

	FRAME					
COLOR TEMPERATURE	24K	27K	30K	30D	35K	40K
TOTAL LUMENS	860	869	905	966	1038	1095
WATTS	14	14	14	14	14	14
LUMENS PER WATT (lm/w)	61	62	65	69	74	78
CRI	93+	93+	93+	93+	93+	93+

Accessories:




LF-FR2-BLU  
LF-FR2-RED  
LF-FR2-VLW  
Frame 2 Lens Film Color filter produces beams of light. Choose for any of Rosco Color films.



GB-FR2  
Frame 2 Gobo lens projects your logo or design onto any surface. For custom Gobo, send your drawings and ideas to our design team: design@PureEdgeLighting.com

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

**LIGHT BAR**




2417.217A: 11<sup>11/16</sup>" (297mm)  
 2417.217B: 23<sup>1/4</sup>" (590mm)  
 2417.217C: 34<sup>13/16</sup>" (884mm)

System	Fixture	Wattage	Color Temperature	Finish
<b>MT48</b>	<b>LB</b>	<b>6W12</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	LB Light Bar	<b>6W12</b> 6 Watts, 12" Length <b>11W24</b> 11 Watts, 24" Length <b>17W36</b> 17 Watts, 36" Length	<b>30K</b> 3000K Warm White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003

LIGHT BAR WITH 140° LENS			
<b>WATTS</b>	6W	11W	17W
<b>TOTAL LUMENS</b>	400	800	1200

**LIGHT BAR LOUVER**



2417.218A: 11<sup>11/16</sup>" (297mm)  
 2417.218B: 23<sup>1/4</sup>" (590mm)  
 2417.218C: 34<sup>13/16</sup>" (884mm)


System	Fixture	Wattage	Color Temperature	Finish
<b>MT48</b>	<b>LBL</b>	<b>6W12</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	LBL Light Bar Louver	<b>6W12</b> 6 Watts, 12" Length <b>11W24</b> 11 Watts, 24" Length <b>17W36</b> 17 Watts, 36" Length	<b>30K</b> 3000K Warm White	<b>BK</b> Black Powder Coat <b>MW</b> Matte White Powder Coat RAL 9003

LIGHT BAR LOUVER & 120° LENS			
<b>WATTS</b>	6W	11W	17W
<b>TOTAL LUMENS</b>	129	258	387

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--



**LIGHT BAR HEXCELL LOUVER**





2417.231A: 11<sup>11</sup>/<sub>16</sub>" (297mm)  
2417.231B: 23<sup>3</sup>/<sub>4</sub>" (590mm)  
2417.231C: 34<sup>13</sup>/<sub>16</sub>" (884mm)

System	Fixture	Wattage	Color Temperature	Finish
<b>MT48</b>	<b>LBH</b>	<b>6W12</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	LBH Light Bar Hexcell Louver	6W12 6 Watts, 12" Length 11W24 11 Watts, 24" Length 17W36 17 Watts, 36" Length	30K 3000K Warm White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003

	LIGHT BAR WITH HEXCELL LOUVER & 120° LENS		
WATTS	6W	11W	17W
TOTAL LUMENS	168	336	504

**BAR ACCENT**



System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>BA</b>	<b>9W6</b>	<b>NF</b>	<b>30K</b>	<b>BC</b>
MT48 Micro Track 48V	BA Bar Accent	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood	30K 3000K Warm White	BC Black Fixture Crystal Baffle MC Matte White Fixture Crystal Baffle


	BAR ACCENT WITH 30° LENS	
WATTS	9W	16W
TOTAL LUMENS	548	1047

Options:



PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

**BAR ACCENT HEXCELL LOUVER**




System	Fixture	Wattage	Beam Spread	Color Temperature	Finish
<b>MT48</b>	<b>BAH</b>	<b>9W6</b>	<b>NF</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	BAH Bar Accent Hexcell Louver	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	NF Narrow Flood	30K 3000K Warm White	BC Black Fixture Crystal Baffle MC Matte White Fixture Crystal Baffle

BAR ACCENT WITH HEXCELL LOUVER & 30° LENS		
WATTS	9W	16W
TOTAL LUMENS	270	514



**BAR WALL WASH**



System	Fixture	Wattage	Color Temperature	Finish
<b>MT48</b>	<b>BWW</b>	<b>9W6</b>	<b>30K</b>	<b>BK</b>
MT48 Micro Track 48V	BWW Bar Wall Wash	9W6 9 Watts, 6" Length 16W12 16 Watts, 12" Length	30K 3000K Warm White	BK Black Powder Coat MW Matte White Powder Coat RAL 9003


PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

# TM30 DATA

## 48VDC WITH INTEGRATED LED

**2400K** | Rf: 84.5 | Rg: 94.4

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92	-2.4%	1.5%
2	94.7	-2.1%	-0.0%
3	95.4	-1.9%	-0.1%
4	88.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.6	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-6.3%

**2700K** | Rf: 87.7 | Rg: 96.1

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.0	-4.3%	2.6%
2	91.6	-2.4%	2.0%
3	93.7	-1.4%	1.9%
4	88.9	-5.6%	-3.1%
5	92.3	-5.5%	-0.5%
6	92.9	-3.5%	0.1%
7	84.5	-7.5%	4.6%
8	90.8	-3.0%	4.4%
9	84.5	-1.3%	8.3%
10	83.9	2.0%	9.8%
11	87.2	5.3%	7.1%
12	89.2	5.4%	-2.6%
13	88.7	0.3%	-7.8%
14	86.8	1.7%	-9.3%
15	87.6	-5.4%	-1.3%
16	83.6	-3.3%	-9.5%

**3000K** | Rf: 88.1 | Rg: 99.7

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.8%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.8%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%

**3500K** | Rf: 86.1 | Rg: 95.5

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.8	-3.8%	0.3%
2	92.3	-2.8%	2.1%
3	89.7	-1.0%	4.3%
4	92.6	-1.4%	1.7%
5	91.8	-3.1%	1.3%
6	96.2	0.8%	-0.4%
7	92.9	-3.2%	0.2%
8	94.3	-2.5%	1.5%
9	90.4	-2.5%	5.2%
10	84.3	-1.4%	9.5%
11	83.1	3.5%	9.8%
12	88.2	4.8%	3.4%
13	94.0	2.7%	-2.0%
14	88.7	5.9%	-5.8%
15	88.7	0.7%	-5.9%
16	86.8	-0.7%	-6.7%

**4000K** | Rf: 87.6 | Rg: 96.8

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.9	-2.4%	2.5%
2	93.3	-0.4%	0.8%
3	94.8	-1.0%	-0.6%
4	87.9	-4.9%	-3.6%
5	85.3	-9.4%	-2.6%
6	90.2	-6.0%	0.2%
7	85.3	-7.6%	4.6%
8	83.7	-4.1%	8.2%
9	79.5	-1.1%	13.8%
10	78.6	1.5%	12.1%
11	83.5	6.4%	7.8%
12	90.9	3.6%	-1.1%
13	88.3	1.7%	-6.3%
14	91.9	-0.4%	-2.2%
15	84.5	-0.9%	-5.5%
16	84.7	-1.1%	-4.4%

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------