



Pirouette Cascade Round 3 Loops, 2 Swings

## DESCRIPTION

The Pirouette Cascade Round is a flexible, architectural lighting system that blends form and function to create continuous, 360-degree illumination without pixelation. Its sculptural, minimal design provides a striking visual element while delivering exceptional color rendering for a clean, uninterrupted glow.

Designed to offer both a sophisticated aesthetic and an inviting ambiance, the Pirouette Cascade Round enhances interiors with its fluid, seamless flow. Choose from Static White, Warm Dim (27D & 30D), Tunable White (2K4K & 27K6), or TruColor RGBTW which is our premier light engine with a wide spectrum from 1500K-6500K and exceptional color rendering (96+ CRI). TruColor RGBTW takes Tunable White to the next level. With the addition of the red, green, and blue channels to the tunable white we're able to achieve a level of quality, performance, and accuracy that was previously unattainable. TruColor RGBTW can be controlled with either DMX or WiZ Pro wireless controls. With flexible configuration options and precision engineering, the Pirouette Cascade Round serves as both a functional lighting solution and a design statement, making it the perfect solution for a wide range of applications. For custom designs and quotes, send drawings to [design@PureEdgeLighting.com](mailto:design@PureEdgeLighting.com).

## LUMEN PERFORMANCE AT 3000K 5W PER FOOT (1D)

LUMEN OUTPUT	775 lm/ft	EFFICIENCY	138 lm/watt
CRI	93+	Rg	98
BEAM ANGLE	360°	BEAM TOLERANCE	+/- 30CCT

## SPECIFICATIONS

DIMENSIONS	DIA: 1C & 1D = 0.9"
INPUT	24VDC with 5" leads
POWER SUPPLIES	Remote 24VDC power supply required
POWER CONSUMPTION	3 or 5 watts per foot
MAX LENGTH	40' at 5 watts
BENDING	6" minimum radius
MATERIAL	UV Resistant Silicon
OPERATING TEMPERATURE	-4° F (-20° C) to 122° F (+50° C)
AVERAGE LED LIFE	50,000 hrs
WARRANTY	5 Year pro-rated

## LAMP

- Static White Color Temperatures ranging from **2400K** through **4000K**
- Warm Dim: **27D** & **30D** dim down to 1800K, resembling halogen light sources
- Tunable White: **2K4K** and **27K6** grants independent control for adjusting color temperature and intensity
- **TruColor™ RGBTW** Dynamic RGB with Tunable White 1500K-6500K

## REMOTE POWER SUPPLIES\*, DIMMERS & CONTROLS (SOLD SEPARATELY)

24VDC, Class 2 wiring

### Static White

- Pure Smart™ WiZ Pro [Power Supplies](#) & [Smart Controls](#)
- [UNI Driver: Universal Dimming \(ELV, TRIAC, 0-10V\)](#)  
ELV & TRIAC [Smart Dimmer & Switch](#)
- [2-in-1 Power Driver and Dimmer](#)

### Warm Dim

- [UNI Driver: Universal Dimming \(ELV, TRIAC, 0-10V\)](#)
- [Make It Smart: Pure Smart™ Wi-Fi Dimmer](#)
- [2-in-1 Power Driver and Dimmer](#)

### Tunable White

- [0-10V](#): Requires two dimmers, one for intensity and one for color temperature
- [DMX & Controls](#)
- Pure Smart™ WiZ Pro [Power Supplies](#) & [Smart Controls](#)
- [2-in-1 Power Driver and Dimmer](#)

### RGBTW

- [Home Integration Solutions](#)
- Pure Smart™ WiZ Pro [Power Supplies](#) & [Smart Controls](#)

\*In-wall mounting and drop ceiling kits available for select power supplies

## COMPLIANCE

\*Title 24 JA8 compliant for 2700K CCT and above when used with PureEdge remote Universal power supplies, ETL, Class 2, Damp Location, Assembled in USA.

## APPLICATIONS

Designed for indoor use only. Ideal applications include residential, commercial, retail, and hospitality environments.

# TRAPEZE PIROUETTE CASCADE CHANDELIER ROUND

24VDC, STATIC WHITE, WARM DIM, TUNABLE WHITE, & TRUCOLOR

ASSEMBLED IN AMERICA

REV 04.14.26

## 360 LENS OPTIONS



**1C** Cora Weave Flex




**1D** Diffused Flex


### COVER AND WHISPER WEIGHT FINISHES




Trapeze Cora Trimless Detail




TRIMLESS PLASTER-IN & PAINT



TRIM



### 360 ILLUMINATION




Ø0.90" (2.5cm)  
1D & 1C




**1C**  
Swing Cora Flex  
with 12" Satin Brass  
Whisper Weight


**1D**  
Swing Diffused Flex  
with 4" Polished Nickel  
Whisper Weight




DRYWALL CEILING



TRIMLESS VANISHING POINT PLASTER-IN



OR





System	Type	Trapeze Loops and Swings*	Wattage	Diameter on Ceiling of Trapeze Length in Inches	Trapeze Longest Drop Length from Ceiling down in Feet*	Color Temperature	Trim and Whisper Weight Finish
<b>PC</b>	<b>1C</b>	<b>4</b>	<b>5W</b>	<b>D36</b>	<b>5</b>	<b>27K</b>	<b>MW</b>
<b>PC</b> Pirouette Cascade comes with Power supply in Canopy. New or remodel construction	<b>1C</b> Cora Weave Flex, 0.9" Diameter <b>1D</b> Diffused Flex, 0.9" Diameter	<b>3</b> 3 Trapeze <b>4</b> 4 Trapeze <b>5</b> 5 Trapeze	<b>3W</b> 3 watts per foot <b>5W</b> 5 watts per foot	<b>D36</b> Circle with 36" Diameter <b>D42</b> Circle with 42" Diameter <b>D48</b> Circle with 48" Diameter <b>D60</b> Circle with 60" Diameter <b>D72</b> Circle with 72" Diameter <b>D96</b> Circle with 96" Diameter	<b>5-15</b> 5-15' Drop from Ceiling  *Drop options vary depending on fixture diameter, check individual listings below for drop options	<b>24K</b> 2400K Very Warm White <b>27K</b> 2700K Incandescent White <b>27D*</b> 2700K Warm Dim, Dims to 1800K <b>30K</b> 3000K Warm White <b>30D*</b> 3000K Warm Dim, Dims to 1800K <b>35K</b> 3500K Neutral White <b>40K</b> 4000K Cool White <b>2K4K*</b> Tunable White 2000K-4000K <b>27K6*</b> Tunable White 2700K-6500K <b>TC*</b> TruColor RGBTW Red, Green, Blue, and Tunable White 1500K-6500K	<b>BK</b> Black <b>MW</b> Matte White RAL 9003 <b>SB</b> Satin Brass <b>SN</b> Satin Nickel <b>PN</b> Polished Nickel <b>XX*</b> Custom <b>L</b> add L after End Cap finish for Trimless Plaster-in Canopy
		*Swing quantities vary depending on fixture diameter, check individual fixture listings below				*5W Only	*RAL/ Specify RAL Powder Coat Code (ex: #RAL/9007) Additional finishes are available with an extended lead time. Custom quotation is required prior to ordering.

**PIROQUETTE CASCADE LAYOUT - 36" DIAMETER**



**3 LOOPS, 2 SWINGS LAYOUT**

- [10' Drop 3D Model](#)    [13' Drop 3D Model](#)
- [11' Drop 3D Model](#)    [14' Drop 3D Model](#)
- [12' Drop 3D Model](#)    [15' Drop 3D Model](#)



**4 LOOPS, 2 SWINGS LAYOUT**



- [10' Drop 3D Model](#)    [13' Drop 3D Model](#)
- [11' Drop 3D Model](#)    [14' Drop 3D Model](#)
- [12' Drop 3D Model](#)    [15' Drop 3D Model](#)



**PIROQUETTE CASCADE LAYOUT - 42" DIAMETER**



**3 LOOPS, 2 SWINGS LAYOUT**

- [10' Drop 3D Model](#)    [13' Drop 3D Model](#)
- [11' Drop 3D Model](#)    [14' Drop 3D Model](#)
- [12' Drop 3D Model](#)    [15' Drop 3D Model](#)



**4 LOOPS, 2 SWINGS LAYOUT**



- [10' Drop 3D Model](#)    [13' Drop 3D Model](#)
- [11' Drop 3D Model](#)    [14' Drop 3D Model](#)
- [12' Drop 3D Model](#)    [15' Drop 3D Model](#)



**PIROUETTE CASCADE LAYOUT - 48" DIAMETER**



**3 LOOPS, 2 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)



**4 LOOPS, 2 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)



**PIROUETTE CASCADE LAYOUT - 60" DIAMETER**

**3 LOOPS, 3 SWINGS LAYOUT**







- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)

**4 LOOPS, 4 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)

**5 LOOPS, 4 SWINGS LAYOUT**



- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)



**PIROUETTE CASCADE LAYOUT - 72" DIAMETER**



**3 LOOPS, 3 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)





**4 LOOPS, 4 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)



**5 LOOPS, 4 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)



**PIROUETTE CASCADE LAYOUT - 96" DIAMETER**

**3 LOOPS, 3 SWINGS LAYOUT**







- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)

**4 LOOPS, 4 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)


**5 LOOPS, 4 SWINGS LAYOUT**

- [5' Drop 3D Model](#)
- [6' Drop 3D Model](#)
- [7' Drop 3D Model](#)
- [8' Drop 3D Model](#)
- [9' Drop 3D Model](#)
- [10' Drop 3D Model](#)
- [11' Drop 3D Model](#)
- [12' Drop 3D Model](#)
- [13' Drop 3D Model](#)
- [14' Drop 3D Model](#)
- [15' Drop 3D Model](#)




**STATIC WHITE AND WARM DIM**

**WIRING DIAGRAM: Single Junction Box**



**WIRING DIAGRAM: 0-10V**




# TRAPEZE PIROUETTE CASCADE CHANDELIER ROUND

24VDC, STATIC WHITE, WARM DIM, TUNABLE WHITE, & TRUCOLOR


## STATIC WHITE AND WARM DIM

### WIRING DIAGRAM: Pure Smart




**TUNABLE WHITE**

**WIRING DIAGRAM: DMX Dimming**




**WIRING DIAGRAM: 0-10V**




**TUNABLE WHITE**

**WIRING DIAGRAM: Pure Smart Connected by WiZ**




**WIRING DIAGRAM: DALI**




**TRUCOLOR**

**WIRING DIAGRAM: Pure Smart Connected by WiZ**



**TRUCOLOR**

**WIRING DIAGRAM: Pure Smart Integration**



# TRAPEZE PIROUETTE CASCADE CHANDELIER ROUND

24VDC, STATIC WHITE, WARM DIM, TUNABLE WHITE, & TRUCOLOR

REV 04.14.26

## NOMINAL DELIVERED LUMENS

1C CORA WEAVE FLEX - STATIC WHITE & WARM DIM												
WATTS PER FOOT	3W					5W						
COLOR TEMPERATURE	24K	27K	30K	35K	40K	24K	27K	27D	30K	30D	35K	40K
LUMENS PER FOOT (lm/ft)	402	418	423	422	512	642	661	355	680	375	652	822
LUMENS PER WATT (lm/w)	112	117	121	120	145	112	117	63	121	65	120	151
CRI	95+	94+	93+	93+	93+	95+	94+	95+	93+	96+	93+	93+

1D DIFFUSED FLEX - STATIC WHITE & WARM DIM												
WATTS PER FOOT	3W					5W						
COLOR TEMPERATURE	24K	27K	30K	35K	40K	24K	27K	27D	30K	30D	35K	40K
LUMENS PER FOOT (lm/ft)	459	476	482	481	584	732	754	405	775	428	743	937
LUMENS PER WATT (lm/w)	128	133	138	137	166	128	133	71	138	74	137	172
CRI	95+	96+	93+	93+	93+	95+	94+	95+	93+	96+	93+	93+

1C CORA WEAVE FLEX - 2K4K TUNABLE WHITE							
WATTS PER FOOT	5W						
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	258	334	334	337	351	403	393
LUMENS PER WATT (lm/w)	55	69	67	66	67	77	76
CRI	93+	93+	93+	96+	96+	93+	93+

1D DIFFUSED FLEX - 2K4K TUNABLE WHITE							
WATTS PER FOOT	5W						
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	294	380	380	384	400	459	448
LUMENS PER WATT (lm/w)	62	78	76	75	76	88	86
CRI	93+	93+	93+	96+	96+	93+	93+

1C CORA WEAVE FLEX - 27K6 TUNABLE WHITE							
WATTS PER FOOT	5W						
COLOR TEMPERATURE	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	214	254	261	268	293	315	300
LUMENS PER WATT (lm/w)	54	51	52	54	59	63	75
CRI	94+	93+	92+	92+	92+	92+	91+

1D DIFFUSED FLEX - 27K6 TUNABLE WHITE							
WATTS PER FOOT	5W						
COLOR TEMPERATURE	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	244	290	298	306	334	359	342
LUMENS PER WATT (lm/w)	49	46	48	49	53	58	68
CRI	94+	93+	92+	92+	92+	92+	91+

1C CORA WEAVE FLEX - TRUCOLOR RGBTW									
WATTS PER FOOT	5W								
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K
LUMENS PER FOOT (lm/ft)	98	111	115	122	127	136	139	111	104
LUMENS PER WATT (lm/w)	19	22	24	28	30	30	29	28	35
CRI	92+	94+	95+	95+	96+	97+	97+	92+	90+

1D DIFFUSED FLEX - TRUCOLOR RGBTW									
WATTS PER FOOT	5W								
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K
LUMENS PER FOOT (lm/ft)	101	114	118	125	239	140	143	114	107
LUMENS PER WATT (lm/w)	48	54	56	30	58	34	68	54	51
CRI	93+	93+	93+	96+	96+	96+	94+	94+	94+


# LED STRIP TM30 DATA

5W | 7W STATIC WHITE, WARM DIM, TUNABLE WHITE, RGBTW

**TM-30-15 DATA:** The data below is for bare LED Static White Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

**2400K** | Rf: 84.5 | Rg: 94.4

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92	-2.4%	1.5%
2	94.7	-2.1%	-0.0%
3	95.4	-1.9%	-0.1%
4	88.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.6	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-6.3%

**2700K** | Rf: 87.7 | Rg: 96.1

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.0	-4.3%	2.6%
2	91.6	-2.4%	2.0%
3	93.7	-1.4%	1.9%
4	88.9	-5.6%	-3.1%
5	92.3	-5.5%	-0.5%
6	92.9	-3.5%	0.1%
7	84.5	-7.5%	4.6%
8	90.8	-3.0%	4.4%
9	84.5	-1.3%	8.3%
10	83.9	2.0%	9.8%
11	87.2	5.3%	7.1%
12	89.2	5.4%	-2.6%
13	88.7	0.3%	-7.8%
14	86.8	1.7%	-9.3%
15	87.6	-5.4%	-1.3%
16	83.6	-3.3%	-9.5%

**3000K** | Rf: 88.1 | Rg: 99.7

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.8%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.8%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%

**3500K** | Rf: 86.1 | Rg: 95.5

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.8	-3.8%	0.3%
2	92.3	-2.8%	2.1%
3	89.7	-1.0%	4.3%
4	92.6	-1.4%	1.7%
5	91.8	-3.1%	1.3%
6	96.2	0.8%	-0.4%
7	92.9	-3.2%	0.2%
8	94.3	-2.5%	1.5%
9	90.4	-2.5%	5.2%
10	84.3	-1.4%	9.5%
11	83.1	3.5%	9.8%
12	88.2	4.8%	3.4%
13	94.0	2.7%	-2.0%
14	88.7	5.9%	-5.8%
15	88.7	0.7%	-5.9%
16	86.8	-0.7%	-6.7%

**4000K** | Rf: 87.6 | Rg: 96.8

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.9	-2.4%	2.5%
2	93.3	-0.4%	0.8%
3	94.8	-1.0%	-0.6%
4	87.9	-4.9%	-3.6%
5	85.3	-9.4%	-2.6%
6	90.2	-6.0%	0.2%
7	85.3	-7.6%	4.6%
8	83.7	-4.1%	8.2%
9	79.5	-1.1%	13.8%
10	78.6	1.5%	12.1%
11	83.5	6.4%	7.8%
12	90.9	3.6%	-1.1%
13	88.3	1.7%	-6.3%
14	91.9	-0.4%	-2.2%
15	84.5	-0.9%	-5.5%
16	84.7	-1.1%	-4.4%


# LED STRIP TM30 DATA

5W | 7W STATIC WHITE, WARM DIM, TUNABLE WHITE, RGBTW

**TM-30-15 DATA:** The data below is for bare LED Warm Dim Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

**2700D** | Rf: 90.7 | Rg: 101.1

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.9	-4.1%	1.1%
2	91.8	-2.2%	3.2%
3	89.0	0.2%	5.0%
4	92.9	-1.1%	0.8%
5	93.9	1.1%	1.7%
6	93.3	3.3%	0.0%
7	93.1	-0.5%	-1.9%
8	97.2	-0.3%	-0.9%
9	93.4	-1.0%	3.2%
10	89.9	-0.1%	5.6%
11	87.0	4.7%	7.2%
12	89.2	5.8%	-0.2%
13	89.1	3.5%	-6.7%
14	86.3	4.1%	-9.2%
15	91.4	-2.0%	-3.6%
16	84.7	-2.1%	-10.3%

**3000D** | Rf: 90.6 | Rg: 101.1

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	91.5	-3.5%	1.3%
2	92.2	-1.8%	3.0%
3	89.3	0.5%	4.8%
4	92.7	-1.1%	0.6%
5	93.3	0.5%	1.4%
6	93.8	2.7%	-0.8%
7	91.2	-2.1%	-0.2%
8	97.0	-0.5%	-0.7%
9	92.5	-0.7%	3.8%
10	88.3	0.9%	7.1%
11	87.5	3.9%	7.6%
12	88.2	6.2%	-0.2%
13	89.9	3.4%	-6.0%
14	86.9	4.4%	-8.5%
15	91.9	-1.9%	-2.9%
16	84.7	-1.3%	-10.6%

# LED STRIP TM30 DATA


5W | 7W STATIC WHITE, WARM DIM, TUNABLE WHITE, RGBTW

REV 04.14.26

**TM-30-15 DATA:** The data below is for LS5 bare Lazer Strips. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

## 2000K ONLY (2K4K) | Rf: 84.3 | Rg: 96.9

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	80.3	-8.9%	1.7%
2	79.7	-7.0%	7.8%
3	78.9	-2.9%	10.0%
4	89.5	-0.5%	5.1%
5	94.4	0.7%	1.7%
6	92.1	2.4%	-0.3%
7	89.4	-2.4%	-5.9%
8	89.7	-6.4%	-0.2%
9	86.0	-4.9%	4.6%
10	81.8	-3.4%	9.3%
11	83.1	3.3%	9.7%
12	85.8	5.6%	3.3%
13	85.6	6.2%	-12.8%
14	61.7	-1.9%	-19.0%
15	79.7	-3.3%	-12.9%
16	78.1	-7.9%	-10.6%

## 3000K (2K4K) | Rf: 90.2 | Rg: 101.4

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.9	-3.8%	1.3%
2	91.7	-1.9%	3.3%
3	88.7	0.7%	5.1%
4	92.4	-1.0%	0.7%
5	92.9	0.9%	1.7%
6	93.1	3.3%	-0.6%
7	91.0	-1.8%	-0.4%
8	97.0	0.2%	-1.1%
9	92.8	-0.5%	3.6%
10	88.3	1.0%	7.0%
11	87.1	3.8%	7.8%
12	87.6	6.5%	-0.3%
13	89.3	3.6%	-6.3%
14	86.1	4.5%	-9.1%
15	91.6	-1.9%	-3.1%
16	83.8	-1.5%	-11.2%

## 4000K ONLY (2K4K) | Rf: 89.6 | Rg: 99.1

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	91.3	-2.5%	1.0%
2	95.3	-0.5%	0.5%
3	94.3	-0.7%	1.1%
4	91.1	-3.4%	-1.1%
5	89.5	-5.6%	0.0%
6	94.6	-1.4%	1.3%
7	93.2	-3.0%	2.6%
8	91.3	-1.8%	4.6%
9	86.5	-0.9%	9.1%
10	83.3	-0.5%	9.5%
11	83.3	4.9%	9.0%
12	89.7	4.1%	1.7%
13	90.1	3.6%	-4.3%
14	93.4	5.2%	-2.1%
15	87.4	0.4%	-4.3%
16	86.6	0.4%	-6.1%


# LED STRIP TM30 DATA

5W | 7W STATIC WHITE, WARM DIM, TUNABLE WHITE, RGBTW

**TM-30-15 DATA:** The data below is for Tunable White bare LED Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

## 2000K ONLY (2K6K/27K6) | Rf: 90.6 | Rg: 98.5

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	87.7	-5.5%	1.2%
2	88.7	-3.9%	4.2%
3	90.5	-1.5%	4.3%
4	95.0	-1.7%	0.8%
5	95.2	-0.2%	2.1%
6	94.2	1.6%	1.9%
7	95.9	-0.8%	-2.2%
8	95.5	-1.7%	1.3%
9	93.8	-1.4	2.6%
10	91.9	-0.7%	4.2%
11	91.3	3.6%	3.7%
12	91.2	4.2%	-1.0%
13	86.6	3.8%	-12.7%
14	67.2	-3.0%	-16.3%
15	84.9	-3.3%	-9.4%
16	84.2	-5.7%	-7.5%

## 3000K (2K6K/27K6) | Rf: 90.5 | Rg: 100.7

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	91.5	-3.5%	1.2%
2	92.4	-1.8%	2.7%
3	89.8	0.3%	4.5%
4	92.4	-1.7%	0.4%
5	93.3	-0.1%	1.4%
6	94.5	2.1%	-0.6%
7	91.0	-2.5%	0.3%
8	96.9	-0.8%	-0.2%
9	91.6	-0.9%	4.6%
10	86.7	0.7%	7.8%
11	86.3	3.8%	8.5%
12	88.3	6.1%	0.6%
13	90.9	3.1%	-5.2%
14	87.3	4.7%	-7.9%
15	92.1	-1.9%	-2.5%
16	84.5	-0.9%	-10.9%

## 4000K ONLY (2K6K/27K6) | Rf: 86.4 | Rg: 96.1

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	86.5	-5.5%	1.3%
2	90.4	-3.0%	2.3%
3	89.8	-2.1%	3.6%
4	89.1	-3.4%	0.4%
5	88.5	-5.9%	0.1%
6	93.6	-3.0%	-0.4%
7	88.9	-6.2%	1.7%
8	87.3	-5.0%	4.9%
9	82.4	-3.6%	11.3%
10	77.4	-1.8%	12.7%
11	79.8	4.9%	11.4%
12	88.7	4.4%	2.7%
13	88.7	4.0%	-5.1%
14	91.2	2.2%	-3.8%
15	82.7	-0.1%	-9.2%
16	82.8	-2.2%	-7.6%


# LED STRIP TM30 DATA

5W | 7W STATIC WHITE, WARM DIM, TUNABLE WHITE, RGBTW

**TM-30-15 DATA:** The data below is for TruColor™ RGBTW (S5W7) bare LED Strips. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.


## 2000K (TruColor™ RGBTW)

View Angle:2 Deg




## 2200K (TruColor™ RGBTW)

View Angle:2 Deg




## 2400K (TruColor™ RGBTW)

View Angle:2 Deg




## 2700K (TruColor™ RGBTW)

View Angle:2 Deg




## 3000K (TruColor™ RGBTW)

View Angle:2 Deg




## 3500K (TruColor™ RGBTW)

View Angle:2 Deg




## 4000K (TruColor™ RGBTW)

View Angle:2 Deg



## 5700K (TruColor™ RGBTW)

View Angle:2 Deg



## 6500K (TruColor™ RGBTW)

View Angle:2 Deg

