

# TIE STIX WALL 2-LIGHT DYNAMIC/TUNABLE WHITE

## ADJUSTABLE REMOTE 24VDC POWER SUPPLY, HUMAN CENTRIC LIGHTING

DESIGNED BY GREGORY KAY | ASSEMBLED IN AMERICA

REV 05.26.21



**TXW2AR-5W-2RE-22-2K6K-ZWN**  
SHOWN AT 2400K

### DESCRIPTION

The Tie Stix Wall 2-Light Adjustable fixture features an opaque flat lens that illuminates smooth dot-free LEDs with a 100° beam spread. Channel is available in a variety of Real Hard Wood and Metal Finishes. Dynamic Tunable White LED technology offers the latest advancements in lighting technology. The Variable White Dynamic Tunable option offers full range dimming at full brightness from 2000K (Sunset) to 6500K (Day Light White) color temperatures or 2700k-6500K (27K6). Sizes range from 12 to 46 inches with a variety of mounting options (see below). Title 24 Compliant.

### REMOTE POWER SUPPLIES, DIMMERS & CONTROLS (SOLD SEPARATELY)\*

- 24VDC, Class 2 wiring
- 0-10V: Requires two dimmers, one for intensity and one for kelvin color temperature
- DMX: Dynamic Color Changing use our proprietary Tunable White Controller CDMX-2XK

\* In-Wall Mounting and drop ceiling Kits available for select power supplies

### METAL CHANNEL FINISHES



### WOOD CHANNEL FINISHES



\*Wood finishes are authentic natural products, exact color and grain may vary. If you are trying to match an existing material, please contact us for a finish sample. We are able to accommodate some requests to pair our wood finishes with COM.

### CANOPY AND HARDWARE FINISHES



### LUMEN PERFORMANCE

@3000K, 4.8W per Foot

Lumen Output:	287 Lm/Ft
Efficiency:	72 lm/watt
CRI:	93+
Beam Angle:	100°

### PHYSICAL ATTRIBUTES

Mounting Options:	<b>4SQ:</b> Canopy Mounts to standard 4" electrical box with round plaster plate. <b>2RE:</b> Canopy Mounts to standard 4" electrical box with single gang plaster ring or single gang electrical box. <b>1RE:</b> Canopy Mounts to Slim Profile junction box (included) recommend for new construction application.
Material:	Real Hardwood NOT LAMINATE, NOT MDF. High Grade Aluminum. LED Soft Strip Tape Light.
Compliance:	ADA, Damp Rated, ETL listed, Class 2 wiring, Title 24
Warranty:	5 Year Pro-Rated Warranty

### APPLICATIONS

Commercial: Hospitality, Office Buildings/Spaces, Conference Spaces, Commercial Real Estate, Hallway lighting, Health Care, Human Centric Lighting  
Residential: Foyer, Home Office, Media Room, Game Rooms, Human Centric Variable White Dynamic LED

### APPROVALS

Class 2 Wiring up to 100 watts, Damp Location Suitable, ETL listed. Title 24 with select power supplies, Made in America.

System	Wattage	Canopy	Nominal Size (L) Inches	Color Temperature	Canopy and Hardware Finish	Channel Finish
<b>TXW2AR</b>	<b>5W</b>	<b>4SQ</b>	<b>12</b>	<b>2K6K</b>	<b>S</b>	<b>WM</b>
<b>TXW2AR</b> Tie Stix Wall 2-Light, Remote Power Supply (Order Separately pgs 4-6)	<b>5W</b> 5 Watt	<b>1RE</b> 1" Rectangle with Junction Box <b>2RE</b> 2" x 4" Rectangle <b>4SQ</b> 4.6" Square	<b>12</b> 13.2" <b>29</b> 30.6" <b>15</b> 15.6" <b>34</b> 34.8" <b>17</b> 18.0" <b>46</b> 46.8" <b>22</b> 22.8"	<b>2K6K</b> Tunable White 2000K-6500K <b>27K6</b> Tunable White 2700K-6500K	<b>S</b> Satin Nickel <b>C</b> Chrome <b>Z</b> Antique Bronze <b>B</b> Satin Black <b>W</b> White	<b>BK</b> Satin Black <b>BZ</b> Antique Bronze <b>CH</b> Chrome <b>SN</b> Satin Nickel <b>WH</b> White <b>SB</b> Satin Brass <b>WM</b> Wood Maple <b>WN</b> Wood Walnut <b>WC</b> Wood Cherry <b>WO</b> Wood White Oak <b>WE</b> Wood Espresso

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------




# TIE STIX WALL 2-LIGHT DYNAMIC/TUNABLE WHITE

ADJUSTABLE REMOTE 24VDC POWER SUPPLY, HUMAN CENTRIC LIGHTING

REV 05.26.21

## Nominal Lamp Data: Lamp data for the Tie Stix 2-Light Adjustable

WATTS PER FOOT	TXW2AR															
	2K6K							27K6								
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	27K	30K	35K	40K	45K	57K	65K
LUMENS PER FOOT (lm/ft)	223	234	246	257	281	292	304	289	280	279	287	295	304	292	289	280
LUMENS PER WATT (lm/w)	56	51	53	56	61	64	76	72	71	70	72	72	71	71	72	71
CRI	83+	83+	92+	92+	92+	94+	94+	93+	93+	93+	93+	94+	94+	94+	93+	93+



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

**TIE STIX WALL 2-LIGHT DYNAMIC/TUNABLE WHITE**  
 ADJUSTABLE REMOTE 24VDC POWER SUPPLY, HUMAN CENTRIC LIGHTING

REV 05.26.21

**WOOD CHANNEL FINISHES**

**METAL CHANNEL FINISHES**



TXW2A-5W-1RE-22-27K-SWN



TXW2A-5W-1RE-22-27K-BSB



TXW2A-5W-1RE-22-27K-ZWC



TXW2A-5W-1RE-22-27K-BWH



TXW2A-5W-1RE-22-27K-ZWM



TXW2A-5W-1RE-22-27K-WBZ



TXW2A-5W-1RE-22-27K-ZWN



TXW2A-5W-1RE-22-27K-WSB



TXW2A-5W-2RE-22-27K-ZWN



TXW2A-5W-2RE-22-27K-BBK



TXW2A-5W-4SQ-22-27K-ZWC



TXW2A-5W-4SQ-22-27K-BSB



TXW2A-5W-4SQ-22-27K-SWM



TXW2A-5W-4SQ-22-27K-CBK



TXW2A-5W-4SQ-22-27K-SWN



TXW2A-5W-4SQ-22-27K-CCH


PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

# INDOOR TUNABLE WHITE 0-10V 96 WATT LED POWER SUPPLY


24VDC INDOOR CONSTANT VOLTAGE, TWO CHANNEL CONTROLS, FOR INTENSITY AND COLOR TEMPERATURE




PSB-96W-010-24VDC-2XK



TOP VIEW



SIDE VIEW



PSB-96W-010-24VDC-2XK-TB  
(T-BAR GRID CEILING)

STANDARD & T-BAR DIMENSIONS		
	A	B
PSB-96W-010-24VDC-2XK	6.48"	12.15"
PSB-2X96W-010-24VDC-2XK	10"	14"
PSB-3X96W-010-24VDC-2XK	13"	17"
PSB-4X96W-010-24VDC-2XK	13"	17"

## DESCRIPTION

Accepts input voltage in a range of 120 - 277VAC and outputs 24VDC power up to 96 watts. The low voltage output dims down to 1% when two additional wires are connected to a 0-10V dimmer. The enclosure provides a space inside for electrical connections. In-Wall Power Supply Kit includes power supply, box cover and stud hangers. T-Bar Mounting Kit includes power supply, box cover, and T-bar hangers for installing Junction Box above ceiling with in easy reach. Comes with 4ft of 14 gauge pair Teflon cables with quick secure connectors. Power Supply features short circuit, overload and over temperature protection.

## APPLICATIONS

Indoor, Damp Location

## MOUNTING

Surface mounted with conduit access

## POWER INPUT

120-277VAC

## POWER OUTPUT

Class 2; 24 volts DC 4A, up to 96 watts maximum

## EFFICIENCY

90%

## AMBIENT OPERATING TEMPERATURE

-25° C to 40° C

## DIMMING

#1 Controls the intensity. #2 Controls the Color Temperature. 0-10V (dimmer needs to be capable to dim to 0% without ON/OFF switch)

## DIMMING CURVE

Linear, Logarithmic 100% - 0% (HydraDrive)

## COMPLIANCE


Made in the USA, UL, CE, Title 28, Plenum for use in Accordance with UL 2043. JA8 compliant when used with Pure Edge Tunable White Products.

Product	Wattage	Dimming	Voltage	Color Temperature	Options
<b>PSB</b>	<b>96W</b>	<b>010</b>	<b>24VDC</b>	<b>2XK</b>	<b>STANDARD</b> (Leave Blank)
<b>PSB</b> Power Supply with Enclosure Box with Tunable White 0-10V Controller	<b>96W</b> 96 Watts <b>2X96W</b> 2x96 Watts <b>3X96W</b> 3x96 Watts <b>4X96W</b> 4x96 Watts	<b>010</b> 0-10 Volt Dimming	<b>24VDC</b> 24 Volt DC	<b>2XK</b> Tunable White	<b>TB</b> T-Bar Grid Ceiling <b>IW*</b> In-Wall Kit

\*96 watts only



PSB-96W-010-24VDC-2XK-IW




PSB-2X96W-010-24VDC-2XK-IW (IN WALL KIT)

IN-WALL DIMENSIONS		
	A	B
PSB-96W-010-24VDC-2XK-IW	8.5"	14.25"


# INDOOR TUNABLE WHITE 0-10V 96 WATT LED POWER SUPPLY

24VDC INDOOR CONSTANT VOLTAGE, TWO CHANNEL CONTROLS, FOR INTENSITY AND COLOR TEMPERATURE


**Application:** 0-10V dimming for Tunable White LED Strip/Fixture



## T-BAR GRID CEILING




## IN WALL KIT



# TUNABLE WHITE DMX CONTROLLER AND POWER SUPPLIES

24VDC INDOOR CONSTANT VOLTAGE POWER SUPPLIES WITH DRIVERS

REV 05.26.21



## DESCRIPTION:

The Tunable White Touch Controller offers fast and accurate Color Temperature adjustment and the ability to regulate the Brightness Independently. The modern Glass faceplate features illuminated indicators, and a back-lit night light that softly illuminates the controller when powered off. Designed for Tunable White, and dual-color LED installations within a single zone. The two Vertical Touch sliders are precise and sensitive, allowing you to fine-tune your perfect Color Temperature at any point between **2000K** (Sunset) to **6500K** (Daylight White) while selecting over 250 levels of Brightness in a smooth, uninterrupted transition. Create Thousands of White Color Combinations while maintaining even Brightness and overall saturation. Easily save three pre-set scenes for different times of the day. Support health, performance, and general well-being using Human-Centric lighting by fine-tuning the biological effects that light has on the circadian cycle using the latest in LED technology. Includes a power adapter that fits behind the controller within a standard junction box and fits inside a standard single-gang receptacle (not for use in a multi-gang box). Use with an insulated, 24 AWG stranded, tinned copper wire (Belden #9841). Power Supplies are Sold Separately. Includes a 5 year pro-rated warranty.

## APPLICATIONS:

Indoor

## OUTPUT SIGNAL:

USITT DMX 512 (1990)

## INSTALLATION:



Fits in a single gang 2.5" deep junction box. Not compatible with multi-gang boxes.

## LABELS:

ROHS, FCC, Damp Location, ETL/UL

## POWER INPUT:

120-240VAC




## COLOR CHANGING (DMX) POWER SUPPLIES

	PSB-100W-24VDC-2XK	PSB-2X100W-24VDC-2XK	PSB-3X100W-24VDC-2XK	PSB-4X100W-24VDC-2XK
<b>ORDERING CODE</b>				
<b>SPECIFICATIONS</b>				
<b>MAXIMUM LOAD OF LED STRIP LENGTH</b>	100W 5 WATTS - 20FT MAX. 10 WATTS - 10FT MAX.	2X100W 5 WATTS 2 X 20FT MAX. 10 WATTS - 2 X 10FT MAX.	3X100W 5 WATTS 3 X 20FT MAX. 10 WATTS - 3 X 10FT MAX.	4X100W 5 WATTS 4 X 20FT MAX. 10 WATTS - 4 X 10FT MAX.
<b>INPUT VOLTAGE</b>	120-277VAC	120-277VAC	120-277VAC	120-277VAC
<b>OUTPUT VOLTAGE</b>	24VDC	24VDC	24VDC	24VDC
<b>DIMENSIONS</b>	12.4" X 6.48" X 2.18"	14" X 10" X 3"	17" X 10" X 3"	17" X 10" X 3"
<b>CLASSIFICATION</b>	CLASS 2	CLASS 2	CLASS 2	CLASS 2
<b>T-BAR MOUNTING</b>	<b>PSB-100W-24VDC-2XK-TB</b>	<b>PSB-2X100W-24VDC-2XK-TB</b>	<b>PSB-3X100W-24VDC-2XK-TB</b>	<b>PSB-4X100W-24VDC-2XK-TB</b>
<b>IN-WALL MOUNTING</b>	<b>PSB-100W-24VDC-2XK-IW</b>	NA	NA	NA
<b>DMX TUNABLE WHITE DIMMING &amp; CONTROLS</b>				
<b>TUNABLE WHITE TOUCH CONTROLLER (CDMX1-2XK)</b>	•	•	•	•


- Flicker free dimming
- Aluminum casing for optimal heat dissipation
- Isolated output power per NEC and UL safety requirements
- UL & ETL recognized/ listed, meets UL 8750, 1310 requirements

- Auto-reset; short circuit, overload and thermal protection
- Class 2 power supply
- Efficient, High power factor > 0.90



**T-Bar Mounting Kit:** Includes power supply, box cover, and T-bar hangers for installing Junction Box above ceiling with in easy reach. Comes with 4ft of 14 gauge pair Teflon cables with quick secure connectors.

**Ordering Codes:**  
 PSB-100W-24VDC-2XK-TB  
 PSB-2x100W-24VDC-2XK-TB  
 PSB-3x100W-24VDC-2XK-TB  
 PSB-4x100W-24VDC-2XK-TB



**8.5" x 14" In-Wall Mounting Kit:** Includes power supply, box cover and stud hangers for installing Junction Box in wall. Select "IW" in the options section of compatible power supply ordering codes if an In-Wall Mounting Kit is needed.

**Ordering Codes:**  
 PSB-100W-24VDC-2XK-IW


# WALL/VANITY TM30 DATA

ADJUSTABLE REMOTE 24VDC POWER SUPPLY, HUMAN CENTRIC LIGHTING

**TM-30-15 DATA:** The data below is for SS5C bare LED Soft Strips. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

## 2000K ONLY (2K6K) | Rf: 84.3 | Rg: 96.9

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	80.3	-8.9%	1.7%
2	79.7	-7.0%	7.8%
3	78.9	-2.9%	10.0%
4	89.5	-0.5%	5.1%
5	94.4	0.7%	1.7%
6	92.1	2.4%	-0.3%
7	89.4	-2.4%	-5.9%
8	89.7	-6.4%	-0.2%
9	86.0	-4.9%	4.6%
10	81.8	-3.4%	9.3%
11	83.1	3.3%	9.7%
12	85.8	5.6%	3.3%
13	85.6	6.2%	-12.8%
14	61.7	-1.9%	-19.0%
15	79.7	-3.3%	-12.9%
16	78.1	-7.9%	-10.6%

## 3000K (2K6K) | Rf: 90.2 | Rg: 101.4

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.9	-3.8%	1.3%
2	91.7	-1.9%	3.3%
3	88.7	0.7%	5.1%
4	92.4	-1.0%	0.7%
5	92.9	0.9%	1.7%
6	93.1	3.3%	-0.6%
7	91.0	-1.8%	-0.4%
8	97.0	0.2%	-1.1%
9	92.8	-0.5%	3.6%
10	88.3	1.0%	7.0%
11	87.1	3.8%	7.8%
12	87.6	6.5%	-0.3%
13	89.3	3.6%	-6.3%
14	86.1	4.5%	-9.1%
15	91.6	-1.9%	-3.1%
16	83.8	-1.5%	-11.2%

## 4000K ONLY (2K6K) | Rf: 89.6 | Rg: 99.1

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	91.3	-2.5%	1.0%
2	95.3	-0.5%	0.5%
3	94.3	-0.7%	1.1%
4	91.1	-3.4%	-1.1%
5	89.5	-5.6%	0.0%
6	94.6	-1.4%	1.3%
7	93.2	-3.0%	2.6%
8	91.3	-1.8%	4.6%
9	86.5	-0.9%	9.1%
10	83.3	-0.5%	9.5%
11	83.3	4.9%	9.0%
12	89.7	4.1%	1.7%
13	90.1	3.6%	-4.3%
14	93.4	5.2%	-2.1%
15	87.4	0.4%	-4.3%
16	86.6	0.4%	-6.1%

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------