
REV.03.20.17 ASSEMBLED IN AMERICA





Description:

Glide can be seamlessly integrated into Edge Lighting Monorail systems. The fixture may be mounted to ceiling rails at a 90 degree angle with use of an included ceiling anchor. Glide Wood Downlight is a linear LED lighting fixture that features a direct milky white (no LED spots) lens and an optional louver. At 7.5 watts per foot, the 12VAC fixture contains very warm white or warm white 92+CRI LEDs. Fixture lengths are available from 36 to 120 inches. Includes corresponding mounting hardware. Glide features adjustable 12 foot cables for flexibility when mounting to the rail. Fixture includes 5 year warranty. For custom designs and quotes, send drawings to design@PureEdgeLighting.com.

System Compatibility:

Monorail

Applications:

Indoor - conference rooms, kitchens, dining rooms, architectural lighting, general lighting and retail

Lamp: 50,000 Hour Lamp Life

Version	Watts	Lumens		92CRI
	per Foot	per Watt	per Foot	27K, 30K
7W	7.5	34	255	•

Lumen values are based on the 3000K LED test without louver.

Fixture Finish:




Monorail Connector Finish:



Louver Options





ROJECT: FIXTURE TYPE: DATE: LIGHTING

REV03.20.17 ASSEMBLED IN AMERICA

