

KNIFE EDGE CEILING TRUCOLOR™ RGBTW

24VDC PLASTER-IN LED SYSTEM, 5 CHANNEL CONTROL



DESCRIPTION

Knife Edge Ceiling with 24V TruColor™ RGBTW technology combines five tunable LED channels for exceptional color accuracy. With a true Knife Edge profile, there is no visible sightline of the lens or light shield, delivering a seamless, visual field across adjacent surfaces. The Knife Edge system generates a sophisticated and seamlessly sharp architectural element, providing consistent lighting across neighboring surfaces. Remote Power supplies are required and sold separately. Coordinate installation with electrical and drywall contractors. Includes a 5-year pro-rated warranty. For custom quotes and layout assistance, send drawings to design@PureEdgeLighting.com. Designed by Gregory Kay.

DESIGN NOTE

Knife Edge Ceiling can be installed on a single wall surface, such as the perimeter of the ceiling, or in a soffit, to accentuate or highlight coves and other architectural elements. Ambient and harmonious, the plaster-in LED system blends into 5/8" thick drywall to enhance the contemporary aesthetic of interior spaces. Knife Edge offers unsurpassed precision and flexibility that transforms spaces into thoughtful and refined works of art.

INCLUDED COMPONENTS

Junction Box, Power Connector, End Caps, Power Feed (left or right), Adjustable Mounting Bars, Backer Plate, Knife Edge Ceiling Channel(s), Drywall Screws, LED Strip, and Lens(es)

MAXIMUM LENGTHS BEFORE RE-FEEDING

- 5W5DC - 20' End Feed
- 5W7DC - 12' End Feed
- 5W10DC - 10' End Feed

LAMP PERFORMANCE

- 5W5DC 360lm/ft 5W @ 3000K
- 5W7DC 526m/ft 7W @3000K
- 5W10DC 622lm/ft 10W @3000K
- Average life: 50,000 hours

TRUCOLOR™ RGBTW TECHNOLOGY

PureEdge Pure Smart TruColor™ technology uses five channels of tunable LEDs, composed of **RGBTW** red, blue, green, and Tunable White (**1500K-6500K**). With our precision-engineered, proprietary color mixing, we produce one of the widest, most accurate spectrums available, giving our customers access to the warm glow of the sunset (1500K-2400K golden hour) to the pure white light of the mid-day sun (5700K) and everything in between. TruColor™ LED's achieve an average CRI-Color Rendering Index of 94+ and a Duv of +/-0.0021 in relation to the blackbody curve at any point on the spectrum of tunable white CCT. Dynamic Color Changing functionality provides millions of possibilities for intricate customization, rich saturated or secondary colors, and unprecedented ease of installation, making RGBTW the ideal choice for residential and commercial applications. TruColor™ RGBTW adds more than just decorative flexibility; it also helps to support a healthy Circadian Rhythm and well-being. Let TruColor™ transform your space and the people within it. [Click here for all Other Color Temperatures](#).

REMOTE POWER SUPPLIES*, DIMMERS & CONTROLS (SOLD SEPARATELY)

24VDC, Class 2 wiring

- [Home Integration Solutions](#)
- Pure Smart™ WiZ Pro [Power Supplies & Smart Controls](#)
- [DMX to WiZ Interface](#), [Power Supply & Controls](#)

*In-Wall mounting and drop ceiling kits available for select power supplies

APPLICATIONS

Indoor damp or dry locations only. Ideal for ceiling perimeters and outlining architectural elements in residential, commercial, retail, education, or healthcare institutions and hospitality environments.

COMPLIANCE

ETL, Class 2, Damp Location, Assembled in USA.

PureEdge is the Original Designer of 5/8" Drywall Products, Backed by Over 30 Years of Precision Manufacturing and Design.

System	Type	Watts Per Foot	Length in Feet	Color Temperature	Finish
KNE	WL	S5W5	10FT	TC	WH
KNE Knife Edge Ceiling	SF Soffit WL Wall	S5W5 5 watts RGB & 5 watts Tunable White (20ft Max) S5W7 5 watts RGB & 7 watts Tunable White (12ft Max) S5W10 5 watts RGB & 10 watts Tunable White (10ft Max)	1-20FT 20' End Feed (S5W5) 1-12FT 12' End Feed (S5W7) 1-10FT 10' End Feed (S5W10)	TC TruColor™ RGBTW Red, Green, Blue, and Tunable White 1500K-6500K	WH White RAL 9010

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

KNIFE EDGE CEILING TRUCOLOR™ RGBTW

24VDC PLASTER-IN LED SYSTEM, 5 CHANNEL CONTROL

NOMINAL DELIVERED LUMENS

DESCRIPTION	S5W5									S5W7									S5W10									
WATTS PER FOOT	4.6W									6.4W									8.3W									
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K	20K	22K	24K	27K	30K	35K	40K	57K	65K	20K	22K	24K	27K	30K	35K	40K	57K	65K	
LUMENS PER FOOT (lm/ft)	162	243	295	331	342	361	390	274	252	201	334	429	487	500	526	515	303	274	213	341	458	537	591	634	617	347	315	
LUMENS PER WATT (lm/w)	60	53	68	78	81	83	93	93	92	60	87	70	82	81	86	88	88	86	61	43	58	70	75	81	74	95	79	
CRI	91.8	93.8	94.5	94.9	95.5	96.9	97.2	92.1	89.8	93	95	96	97	97	98	97	95	93	92.7	94.5	95.7	96.5	97.4	98.1	97	93.6	91.6	
Duv	-0.004	-0.001	-0.003	-0.006	-0.006	-0.003	-0.001	-0.005	-0.006	-0.003	0.000	0.003	0.003	0.003	0.001	0.000	0.003	0.003	-0.003	-0.001	-0.002	-0.004	-0.003	-0.001	0.000	-0.004	-0.005	
Rf	91	93	94	94	95	94	94	92	90	92	93	95	95	95	95	94	92	91	92	93	95	95	95	95	94	92	91	
Rg	105	101	103	105	104	102	100	102	103	104	100	102	103	103	101	100	102	103	104	100	103	104	103	102	100	102	103	
R9	90	90	90	94	97	97	91	81	70	91	90	90	94	95	93	93	79	67	91	90	90	94	95	93	90	79	69	
R13	92	94	95	95	94	96	99	90	87	92	95	96	96	97	99	99	91	88	92	94	96	96	97	100	99	92	89	
R15	99	99	99	98	97	97	97	89	85	99	99	99	99	99	98	97	90	85	99	99	99	99	99	98	97	90	86	
WATTS/FOOT	2.7	4.55	4.35	4.25	4.25	4.35	4.2	2.95	2.75	3.35	3.85	6.15	5.95	6.15	6.15	5.84	3.45	3.2	3.5	8	7.9	7.7	7.85	7.8	8.3	3.65	4	

LENGTH LOAD CHARTS: To determine the necessary wire gauge use our [Voltage Drop Calculator](#).

S5W5 WATTS PER FOOT				
LENGTH IN FEET	RGB Wattage	Tunable White Wattage	Pure Smart™ WIZ Pro Wattage	DMX Wattage
1	5	5	5	10
2	10	10	10	20
3	15	15	15	30
4	20	20	20	40
5	25	25	25	50
6	30	30	30	60
7	35	35	35	70
8	40	40	40	80
9	45	45	45	90
10	50	50	50	100
11	55	55	55	
12	60	60	60	
13	65	65	65	
14	70	70	70	
15	75	75	75	
16	80	80	80	
17	85	85	85	
18	90	90	90	
19	95	95	95	
20	100	100	100	

S5W7 WATTS PER FOOT			
LENGTH IN FEET	RGB Wattage	Tunable White Wattage	Pure Smart™ WIZ Pro Wattage
1	5	7	7
2	10	14	14
3	15	21	21
4	20	28	28
5	25	35	35
6	30	42	42
7	35	49	49
8	40	56	56
9	45	63	63
10	50	70	70
11	55	77	77
12	60	84	84

S5W10 WATTS PER FOOT			
LENGTH IN FEET	RGB Wattage	Tunable White Wattage	WIZ Pro Wattage
1	5	10	10
2	10	20	20
3	15	30	30
4	20	40	40
5	25	50	50
6	30	60	60
7	35	70	70
8	40	80	80
9	45	90	90
10	50	100	100

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--



KNIFE EDGE CEILING TRUCOLOR™ RGBTW

24VDC PLASTER-IN LED SYSTEM, 5 CHANNEL CONTROL


REV 11.18.25

WALL INSTALLATION

Wall Power feed may be mounted to end or center of run. Includes two power feed connectors.




SIDE VIEW



SIDE VIEW



with curved wall to ceiling for Ganzfeld Effect in the corners




System	Type	Power Feed	Color Temperature	Finish
KNE	WL	CP	RGBTW	WH
KNE Knife Edge Ceiling DIY	WL Wall	CP Center Power Feed EPL End Power Feed Left EPR End Power Feed Right <small>*Power Feed options shown on page 7</small>	RGBTW Red, Green, Blue, and Tunable White 1500K-6500K	WH White RAL 9010

SOFFIT INSTALLATION

Soffit Power feed may be mounted to end or center of run. Includes two power feed connectors.



SIDE VIEW



DIRECTION OF LIGHT


System	Type	Power Feed*	Color Temperature	Finish
KNE	SF	CP	RGBTW	WH
KNE Knife Edge Ceiling DIY	SF Soffit	CP Center Power Feed EPL End Power Feed Left EPR End Power Feed Right <small>*Power Feed options shown on page 7</small>	RGBTW Red, Green, Blue, and Tunable White 1500K-6500K	WH White RAL 9010

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


KNIFE EDGE CEILING

24VDC PLASTER-IN LED SYSTEM, STATIC WHITE

KNIFE EDGE CORNERS



FLAT END CAPS




PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

KNIFE EDGE CEILING TRUCOLOR™ RGBTW

24VDC PLASTER-IN LED SYSTEM, 5 CHANNEL CONTROL


ADDITIONAL PARTS



JUNCTION BOX FOR WALL INSTALLATION

One Junction Box is included with Knife Edge Ceiling. Order additional Junction Box separately to rough-in electrical wiring before drywall installation. Quick shipment available.


System	Installation	Component
KNE	WL	JBOX
KNE Knife Edge Ceiling	WL Wall	JBOX Junction Box



JUNCTION BOX FOR SOFFIT INSTALLATION

One Junction Box is included with Knife Edge Ceiling. Order additional Junction Box separately to rough-in electrical wiring before drywall installation. Quick shipment available.

System	Installation	Component
KNE	SF	JBOX
KNE Knife Edge Ceiling	SF Soffit	JBOX Junction Box



L CONNECTORS


Each connector is 6" in length. Included with Power Feeds above.

System	Type	Component	Color Temperature
SS	PFE	KE-L	RGBTW
SS Stomp Strip/Soft Strip	PFE Power Feed	KE-L Knife Edge Left KE-R Knife Edge Right	RGBTW Red, Green, Blue, and Tunable White 1500K-6500K


KNIFE EDGE CEILING TRUCOLOR™ RGBTW

24VDC PLASTER-IN LED SYSTEM, 5 CHANNEL CONTROL


DIMENSIONAL DRAWINGS - WALL INSTALLATION



DIMENSIONAL DRAWINGS - SOFFIT INSTALLATION



SIGHTLINE DISTANCES




PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


KNIFE EDGE CEILING TRUCOLOR™ RGBTW

24VDC PLASTER-IN LED SYSTEM, 5 CHANNEL CONTROL


END FEED - LEFT



END FEED - RIGHT



CENTER FEED



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


TM30 DATA

24VDC PLASTER-IN LED SYSTEM, STATIC WHITE & WARM DIM

TM-30-15 DATA: The data below is for Pure Smart TruColor™ RGBTW Lamps.


2000K (TruColor™ RGBTW)

View Angle: 2 Deg




2200K (TruColor™ RGBTW)

View Angle: 2 Deg




2400K (TruColor™ RGBTW)

View Angle: 2 Deg




2700K (TruColor™ RGBTW)

View Angle: 2 Deg




3000K (TruColor™ RGBTW)

View Angle: 2 Deg




3500K (TruColor™ RGBTW)

View Angle: 2 Deg




4000K (TruColor™ RGBTW)

View Angle: 2 Deg




5700K (TruColor™ RGBTW)

View Angle: 2 Deg



6500K (TruColor™ RGBTW)

View Angle: 2 Deg



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--