


LUCA 2.7" WARM DIM 120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS



DESCRIPTION

Introducing the Luca 2.7 "The Bringer of Light" Downlight Series—a beacon of innovation in lighting technology. Designed for high-performance, these downlights are crafted to enhance hospitality, retail, commercial, and luxury residential environments. Featuring precision optics, the Luca downlights deliver a beam that reaches the very top of the wall, creating an elegant wash of light. With a Color Rendering Index (CRI) surpassing 90, these lights ensure exceptional color accuracy, making them an ideal choice for spaces where ambiance and visual clarity are paramount.

The Luca Downlight series delivers captivating illumination across a wide spectrum, creating a visually engaging experience within any space. With its extensive range of design and installation options, our Luca 2.7 Downlight is versatile for a wide array of new construction and remodel applications. Moreover, the compact form factor of the Luca 2.7 allows for installation in spaces with limited clearance.

Discover a new era of lighting performance and versatility with the Luca 2.7 Downlight Series, where superior optics, lumen performance, and outstanding color consistency converge to transform a space. For personalized quotes and expert layout assistance, share your drawings and concepts with our design team at design@PureEdgeLighting.com

SPECIFICATIONS

TRIM OPTIONS	Trim, Trimless, Round, Square for Fixed & Adjustable		
FINISH	Reflector: White, Black, Haze Silver (low-glare), Trims: White, Black, Custom		
ADJUSTABLE	30° Tilt, 360° Rotation		
OPTICS	15°, 25°, 30°, 40°, 45°, 55°		
WATTAGE	16W	20W	24W
LUMENS @ 3000K, 30°	1123 Lm	1346 Lm	1507 Lm
EFFICACY	70 Lm/W	75 Lm/W	63 Lm/W
CCT	3000D		
AVERAGE CRI	90+		
INPUT VOLTAGE	120V ELV/TRIAC, 120V-277V & 0-10V & DALI/DMX		
CONSTRUCTION	Housing: Galvanized Steel Heat Sink, Trims and Reflectors: Die-Cast Aluminum		
ACCESSORIES	Clear Glass & Soft Diffusing Film (Included) Linear Spread Glass Lens, Wide Diffused Glass Lens, or Hexcell Louver		

DIMMING	Universal Dimming TRIAC/ELV: 100% – 3% 0-10V: 100% – 0.1% dim to off DALI2: 100% – 0.1% dim to off Pure Smart™ 100% – 5% Pure Smart™ Wi-Fi Dimmer TRIAC/ELV 2.4GHz Wi-Fi. No Hub needed. Voice control with Goggle Assistant, Alexa, Siri, Shortcuts, and IFTTT
CUT OUT SIZE	Round: Ø3", Square: 3"
CEILING THICKNESS	0.5" - 1"
ENVIRONMENT	Suitable for damp locations
CERTIFICATIONS	ETL Listed. Meets Title 24 (JA8) requirements. Down Light Trim - Wet Listed. Adjustable - Damp listed* *Glass Lens to be used in showers and similar environments
AVERAGE LIFE	50,000 Hours
WARRANTY*	5 Years *See published warranty terms for detailed information

NOMINAL LAMP DATA

	LUCA 2.7 STATIC WHITE		
WATTS PER FOOT	16W	20W	24W
COLOR TEMPERATURE	30D	30D	30D
LUMENS	629	988	1106
LUMENS PER WATT (lm/w)	39	49	46
CRI	93	98	98

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS

REV 04.28.25


#1 Select LUCA 2.7 Beam, Color Temperature, Trim Options

System	Beam Spread	Color Temperature	Trim Shape	Trim Function	Reflector Finish	Trim Finish
L27	NF	30D	R	D	W	L
L27 Luca 2.7 Light Engine	NS* Narrow Spot 15° SP Spot 25° NF Narrow Flood 35° FL Flood 45° WF Wide Flood 55° *NS: 16 Watt Only	30D 3000K Warm Dim	R Round S Square	D Downlight A Adjustable P Pinhole/Adjustable	W White H Haze B Black C Custom	W White B Black L Trimless C Custom




#2 Select Housing & Driver Type

REMODEL NON-IC with 120V DRIVER




Product	Housing Type	Rating Type	Wattage/Lumens	Dimming
L27	RM	NIC	20W	UN
L27 Luca 2.7 Downlight	RM Remodel	NIC Non-Insulation Contact	16W 16 Watts/1123 Lumens 20W 20 Watts/1346 Lumens 24W 24 Watts/1507 Lumens	UN TRIAC/MLV, ELV 120V Input 01 0-10V 120V/277V Input DA DALI 2 120V/277V Input

NEW CONSTRUCTION FRAME NON-IC with 120V DRIVER



Product	Housing Type	Rating Type	Wattage/Lumens	Dimming
L27	NCF	NIC	20W	UN
L27 Luca 2.7 Downlight	NCF New Construction Frame	NIC Non-Insulation Contact	16W 16 Watts/1123 Lumens 20W 20 Watts/1346 Lumens 24W 24 Watts/1507 Lumens	UN TRIAC/MLV, ELV 120V Input 01 0-10V 120V/277V Input DA DALI 2 120V/277V Input

NEW CONSTRUCTION HOUSING IC WITH 120V DRIVER



Product	Housing Type	Rating Type	Wattage/Lumens	Dimming
L27	NCH	IC	16W	UN
L27 Luca 2.7 Downlight	NCH New Construction Housing	IC Insulation Contact	16W 16 Watts/1123 Lumens	UN TRIAC/MLV, ELV 120V Input 01 0-10V 120V/277V Input DA DALI 2 120V/277V Input

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS


REV 04.28.25

LUCA 2.7 WALL WASH TRIM OPTIONS



Fixed Downlight





Round Trim




Round Trimless



Square Trim




Square Trimless




Adjustable Downlight




Round Trim




Round Trim Pinhole




Round Trimless




Round Trimless Pinhole




Square Trim




Square Trim Pinhole



Square Trimless



Square Trimless Pinhole



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

LUCA 2.7" WARM DIM 120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS

LUCA 2.7 TRIM & REFLECTOR OPTIONS

ROUND TRIM

Black Trim

White Trim



Black Reflector



White Reflector



Haze Reflector



Pinhole Trim

SQUARE TRIM

Black Trim

White Trim



Black Reflector



White Reflector



Haze Reflector





Pinhole Trim

LUCA 2.7" WARM DIM 120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS

BEAM SPREAD & LENSES

LOW GLARE REFLECTOR

Designed with a 30 degree cut-off angle, the Luca provides high output and efficiency while maximizing visual comfort.




OPTICS

Our Luca Downlight has been meticulously designed to deliver exceptional performance and visual comfort. With its deep baffle design and a 30° cut-off, it effectively minimizes glare while providing a consistent and high-quality distribution of white light.

Our Adjustable Downlight features a 30° tilt for precise aiming and control.

SELECT UP TO TWO ACCESSORIES



In addition to the included glass wet Lens and soft diffusion film we offer a variety of beam spreads, and lens accessories to tailor the output and beam shape for specific applications. The Linear spread lens glass produces an elliptical illumination pattern, while the Wide diffused glass lens evenly distribute the light. Additionally, the Hexcell Louver is available for enhanced glare control.

REPLACEMENT OPTICS

Product	Type	Beam Spread*	Color Temperature
LEN	L2.7	NF	SW
LEN Lens	L2.7 Luca 2.7	SP Spot 25° NF Narrow Flood 35° FL Flood 45°	SW Static White

*Restrictions: NS & WF not available for replacement optics

Accessories (up to 2)

Product	Type
GL13	L
GL13 Glass 1 5/8" (40mm) Diameter	C Clear Glass Wet Lens L Linear Spread Glass Lens W Wide Diffuse Glass Lens
LF13 Lens Film 1 5/8" (40mm) Diameter	S Soft Diffusion Film
L013 Louver 1 5/8" (40mm) Diameter	H Hexcell Louver

LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS



REV 04.28.25

LUCA 2.7 FOOT CANDLE DISTRIBUTION (CONTINUED)



D - Distance From Luca fixture, FC - Initial foot candles at the center of beam, DIA - Diameter

16W at 3000K



NARROW SPOT
15°





SPOT
25°





NARROW FLOOD
30°



FLOOD
40°



WIDE FLOOD
55°



LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS



REV 04.28.25

LUCA 2.7 FOOT CANDLE DISTRIBUTION (CONTINUED)



D - Distance From Luca fixture, FC - Initial foot candles at the center of beam, DIA - Diameter

20W at 3000K



SPOT
25°





NARROW FLOOD
35°



FLOOD
45°



WIDE FLOOD
55°



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS



REV 04.28.25

LUCA 2.7 FOOT CANDLE DISTRIBUTION (CONTINUED)



D - Distance From Luca fixture, FC - Initial foot candles at the center of beam, DIA - Diameter

24W at 3000K



SPOT 25°





NARROW FLOOD 35°



FLOOD 45°



WIDE FLOOD 55°



LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS



REV 04.28.25

LUCA 2.7 FOOT CANDLE DISTRIBUTION (CONTINUED)



D - Distance From Luca fixture, FC - Initial foot candles at the center of beam, DIA - Diameter

26W at 3000K



SPOT
25°





NARROW FLOOD
35°



FLOOD
45°




WIDE FLOOD
55°




LUCA 2.7" WARM DIM

120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS

TRIAC / FORWARD PHASE / LEADING EDGE DIMMING (TRI)
 Input 120VAC 50/60Hz
 Range 3% - 100%




ELV / REVERSE PHASE / TRAILING EDGE DIMMING (TRI)
 Input 120VAC 50/60Hz
 Range 3% - 100%




0-10V DIMMING (010)
 Input 120VAC-277VAC 50/60Hz
 Range 0.1% - 100% Dim to Off

NOTE
 Cap off unused wires individually.
 DO NOT cap together.



DALI DIMMING (DAL)
 Input 120VAC-277VAC 50/60Hz
 Range 0.1% - 100% Dim to Off

NOTE
 Cap off unused wires individually.
 DO NOT cap together.



TM30 DATA


120V-277V, RECESSED FIXED & ADJUSTABLE DOWNLIGHTS

REV 04.28.25

TM-30-15 DATA: The data below is for bare LED Warm Dim Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

3000D | Rf: 90.6 | Rg: 101.1

Color Vector Graphic



■ Test
 ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	91.5	-3.5%	1.3%
2	92.2	-1.8%	3.0%
3	89.3	0.5%	4.8%
4	92.7	-1.1%	0.6%
5	93.3	0.5%	1.4%
6	93.8	2.7%	-0.8%
7	91.2	-2.1%	-0.2%
8	97.0	-0.5%	-0.7%
9	92.5	-0.7%	3.8%
10	88.3	0.9%	7.1%
11	87.5	3.9%	7.6%
12	88.2	6.2%	-0.2%
13	89.9	3.4%	-6.0%
14	86.9	4.4%	-8.5%
15	91.9	-1.9%	-2.9%
16	84.7	-1.3%	-10.6%